
chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assembled Ethernet cable, shielded, 4-pair, 26 AWG stranded (7-wire), RAL 5021 (water blue), RJ45 connector/IP20 to RJ45 connector/IP20, line, length: 20 m

Commercial data

Item number	1423033
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	ABNABM
Product key	ABNABM
Catalog page	Page 386 (C-2-2019)
GTIN	4055626323749
Weight per piece (including packing)	931.2 g
Weight per piece (excluding packing)	924.2 g
Customs tariff number	85444210
Country of origin	CN

chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Technical data

Product properties

Product type	Data cable preassembled
Sensor type	Ethernet
Number of positions	8
No. of cable outlets	1
Cable outlet	straight

Data management status

Article revision	00

Insulation characteristics

Degree of pollution	2

Electrical properties

Rated voltage (III/3)	72 V (DC)
Transmission medium	Copper
Transmission characteristics (category)	CAT5 (IEC 11801:2002)

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 750

Material specifications

Flammability rating according to UL 94	V2

Connector

Connection 1

Type	Plug straight RJ45
Handle color	gray
Material	CuSn (Contact)
	Ni/Au (Contact surface)
	PC (Contact carriers)
	PA (Housing)
Insertion/withdrawal cycles	≥ 750
Degree of protection	IP20

Connection 2

Type	Plug straight RJ45
Handle color	gray
Material	CuSn (Contact)
	Ni/Au (Contact surface)
	PC (Contact carriers)

chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

	PA (Housing)
Insertion/withdrawal cycles	≥ 750
Degree of protection	IP20

Cable/line

Cable length	20.00 m

Ethernet flexible CAT5, 4-pair, SF/UTP [94Z]

Number of positions	8
Shielded	yes
Cable type	Ethernet flexible CAT5, 4-pair, SF/UTP [94Z]
Conductor structure	4x2xAWG26/7, SF/UTP
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	4x 2x 0.14 mm²
Wire diameter incl. insulation	0.92 mm
External cable diameter	6.20 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021
Conductor material	Bare Cu litz wires
Material wire insulation	PE
Single wire, color	white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Thickness, insulation	0.19 mm (Signal line)
Twisted pairs	2 cores to the pair
Overall twist	4 pairs
Optical shield covering	85 %
Max. conductor resistance	≤ 290 Ω/km (at 20 °C)
Insulation resistance	≥ 500 MΩ*km (at 20 °C)
Wave impedance	100 Ω ±15 Ω (at 100 MHz)
Test voltage Core/Core	700 V (50 Hz, 1 min.)
Test voltage Core/Shield	700.00 V (50 Hz, 1 min.)
Smallest bending radius, fixed installation	51.2 mm
Smallest bending radius, movable installation	51.2 mm
Halogen-free	according to IEC 60754-1
Flame resistance	IEC 60332-1-2
Resistance to oil	in accordance with DIN EN 60811-2-1
Ambient temperature (operation)	-20 °C ... 80 °C
	-20 °C ... 80 °C
	-20 °C ... 80 °C
Ambient temperature (installation)	-20 °C ... 80 °C

Environmental and real-life conditions

Ambient conditions

chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 70 °C (RJ45 connector)

chanhvinh.com


NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Drawings

Circuit diagram




chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Schematic diagram



Connector pin assignment plug RJ45

chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1423033

EAC
Approval ID: 19060508

chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Classifications

ECLASS

ECLASS-11.0	27060308
ECLASS-12.0	27061801
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

NBC-R4AC/20,0-94Z/R4AC - Network cable

1423033

https://www.phoenixcontact.com/gb/products/1423033

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk