chanhvinh.com

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Bus system cable, VARAN (100 Mbps), 6-position, SANTOPRENE halogen-free/TPE halogen-free, black RAL 9005, shielded, free cable end, on Socket angled M12 SPEEDCON, coding: A, cable length: 15 m

Commercial Data

Item number	1428649
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	BF1CMM
Product Key	BF1CMM
Catalog Page	Page 324 (PC-2011)
GTIN	4046356322928
Weight per Piece (including packing)	1,156 g
Weight per Piece (excluding packing)	1,150 g
Customs tariff number	85444290
Country of origin	PL

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	6
Application	Standard
No. of cable outlets	1
Coding	A - standard

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Interfaces

Bus system	VARAN
Signal type/category	VARAN, 100 Mbps

LED signaling

Status display	No
Status display present	No

Electrical properties

Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	30 V AC
	30 V DC
Nominal current I_N	2 A
Transmission medium	Copper

Material specifications

Color Handle area	black
Flammability rating according to UL 94	HB
Sealing material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Cable gland material	Zinc die-cast, nickel-plated

Connection data

Pin assignment

Contact | Color (signal designation) | Contact (optional)	1 (Socket)
	4 (Socket)
	6 (Socket) = BU (Power)

chanhvinh.com

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

	7 (Socket) = BN (Power)
	5 (Socket) = GNWH (RD+)
	8 (Socket) = GN (RD-)
	2 (Socket) = OGWH (TD+)
	3 (Socket) = OG (TD-)

Connector

Connection 1

Head design	free cable end

Head 2

Head design	Socket
Head cable outlet	angled
Head thread type	M12
Head locking type	SPEEDCON
Coding	A

Cable / line

Cable length	15 m
Cable weight	81 kg/km
Number of positions	6
Shielded	yes
Cable type	VARAN [970]
Conductor structure signal line	19x 0.13 mm
AWG signal line	24
Conductor cross section	4x 0.25 mm² (Signal line)
	2x 0.38 mm² (Power supply)
Wire diameter incl. insulation	1.35 mm (Signal line)
	1.5 mm (Power supply)
External cable diameter	7.8 mm ±0.2 mm
Outer sheath, material	SANTOPRENE halogen-free
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	Brown, blue, white/orange, white/green, green, orange
Type of pair shielding	Tinned copper braided shield, 95 % covering
Overall twist	1 star quad and 2 wires with 2 fillers
Max. conductor resistance	77 Ω/m (Data cable)
Insulation resistance	5 GΩ*km (Data cable)
Wave impedance	100 Ω ±15 %
Working capacitance	50 nF (Data cable)
Nominal voltage, cable	125 V (Data cable)
	48 V (Power supply)
Test voltage	2000 V (Power supply)

chanhvinh.com

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

	max. 700 V AC (Data cable)
Smallest bending radius, fixed installation	≥ 93 mm
Smallest bending radius, movable installation	≥ 93 mm
Max. bending cycles	3000000
Halogen-free	in accordance with DIN EN 50267-2-1
Ambient temperature (operation)	-20 °C ... 80 °C (Cable)
Ambient temperature (installation)	0 °C ... 50 °C

Cable structure

Signal type/category	VARAN, 100 Mbps

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

chanhvinh.com


Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649


Drawings

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side

Dimensional drawing



M12 x 1 socket, angled, shielded


chanhvinh.com

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

Circuit diagram



Contact assignment of the M12 socket

chanhvinh.com

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

Approvals

EAC
Approval ID: RU C-DE.BL08.B.00286

EAC
Approval ID: RU D-DE.HB35.B.00387

chanhvinh.com

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060307

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Bus system cable - SAC-6P-15,0-970/FR SCO

1428649

https://www.phoenixcontact.com/gb/products/1428649

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk