
chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



AS-Interface EPDM flat conductor in yellow, 2 x 1.5 mm^2, 100 m ring

Commercial Data

Item number	1432402
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	BF1LFA
Product Key	BF1LFA
Catalog Page	Page 438 (C-2-2019)
GTIN	4046356349291
Weight per Piece (including packing)	6,963 g
Weight per Piece (excluding packing)	6,717 g
Customs tariff number	85444995
Country of origin	DE

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Technical Data

Product properties

Product type	Data cable by the meter
Number of positions	2

Interfaces

Signal type/category	AS-Interface

Dimensions

Width	10 mm
Height	4 mm

Cable / line

Cable length	100 m
Cable weight	85 kg/km
Number of positions	2
Shielded	no
Conductor type	Flat-ribbon conductor
Conductor structure signal line	76x 0.16 mm
AWG signal line	16
Conductor cross section	1.5 mm²
Wire diameter incl. insulation	2.5 mm
Outer sheath, material	EPDM (rubber)
External sheath, color	lemon yellow RAL 1012
Conductor material	Tin-plated Cu litz wires
Material wire insulation	EPDM (rubber)
Single wire, color	brown, blue
Thickness, insulation	approx. 0.5 mm
Nominal voltage, cable	32 V (Uo)
Test voltage	1000 V AC
Other resistance	Resistant to ozone
Special properties	Silicone-free
Ambient temperature (operation)	-40 °C ... 85 °C (cable, fixed installation)
	-25 °C ... 85 °C (Cable, flexible installation)
Cable type	Flat-ribbon conductor
Signal type/category	AS-Interface
Cable structure	2 x 1.5 mm²
Conductor structure signal line	76x 0.15 mm
AWG signal line	16
Wire diameter incl. insulation	2.5 mm

FO cable

Transmission medium	Copper

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C (Flexibly installed)
	-40 °C ... 85 °C (fixed routing)
Ambient temperature (storage/transport)	-40 °C ... 85 °C

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Approvals

EAC
Approval ID: RU D-DE.HB35.B.00385

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Classifications

ECLASS

ECLASS-9.0	27062002
ECLASS-10.0.1	27060106
ECLASS-11.0	27061801

ETIM

ETIM 8.0	EC003249

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Accessories

Stripping tool

Stripping tool - WIREFOX ASI - 1212154

https://www.phoenixcontact.com/gb/products/1212154



Stripping pliers, for AS interface flat-ribbon cables, any desired stripping length

Seal

Seal - ASI SACB KABEL-ENDDICHTUNG - 1692336

https://www.phoenixcontact.com/gb/products/1692336



End sealing for AS-Interface flat-ribbon conductor, can be used on both sides, color:Black

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Fastening clip

Fastening clip - VS-ASI-2FC-FIX - 1404757

https://www.phoenixcontact.com/gb/products/1404757



Fastening clip for two AS-Interface flat conductors, self-adhesive and with a 3 mm hole for additional fastening, plastic, gray

Panel feed-through

Panel feed-through - Q 1,5/4A50/24-M20KU-ESA-ASI BK - 1437274

https://www.phoenixcontact.com/gb/products/1437274



Panel feed-through with QUICKON fast connection technology, for accommodating one or two AS-i flat-ribbon conductors, on the rear side with four 0.5 m long individual wires 1.5 mm^2

chanhvinh.com

Flat-ribbon conductor - VS-ASI-FC-EPDM-YE 100M

1432402

https://www.phoenixcontact.com/gb/products/1432402

Conductor connectors

Conductor connectors - Q 1,5/4IDC/24-24KU-KU-ASI-BK - 1585058

https://www.phoenixcontact.com/gb/products/1585058



Flat conductor connector with QUICKON fast connection technology, 4-pos., for connecting one or two AS-interface flat conductors

Panel feed-through

Panel feed-through - Q 1,5/4FL/24-M20KU-ESA-ASI BK - 1437261

https://www.phoenixcontact.com/gb/products/1437261



Panel feed-through with QUICKON fast connection technology, for accommodating one or two AS-i flat conductors, on the rear side with manual solder/slip-on connection 4.8 x 0.8 mm

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk