chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Socket straight M12 SPEEDCON, coding: A, on Socket straight M12 SPEEDCON, coding: A and Plug straight M12 SPEEDCON, coding: A, cable length: 1 m, all connectors unshielded, Shield connected to pin 1

Commercial Data

Item number	1436039
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF1GAD
Product Key	BF1GAD
Catalog Page	Page 434 (C-2-2019)
GTIN	4046356432283
Weight per Piece (including packing)	170.4 g
Weight per Piece (excluding packing)	153.24 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	5
Application	Standard
No. of cable outlets	1
Shielded	no
Coding	A - standard

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Interfaces

Bus system	CANopen®/DeviceNet™
Signal type/category	CANopen®
	DeviceNet™
	CANopen®
	DeviceNet™

LED signaling

Status display	No
Status display present	No

Electrical properties

Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A
Transmission medium	Copper

Material specifications

Color Handle area	black
Flammability rating according to UL 94	HB
Sealing material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Cable gland material	Zinc die-cast, nickel-plated


Dimensions

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Dimensional drawing	
Center distance	21 mm

Connection data

Pin assignment

Contact | Color (signal designation) | Contact (optional)	1 (Distributor) = SR (shield) = 1 (Plug) = 1 (Socket)
	2 (Distributor) = RD (V+) = 2 (Plug) = 2 (Socket)
	3 (Distributor) = BK (V-) = 3 (Plug) = 3 (Socket)
	4 (Distributor) = WH (CAN_H) = 4 (Plug) = 4 (Socket)
	5 (Distributor) = BU (CAN_L) = 5 (Plug) = 5 (Socket)

Connector

Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	A

Head 2

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	A

Cable / line

Cable length	1 m
Cable weight	90 kg/km
UL AWM Style	21198 (80°C/300 V)
Number of positions	4
Shielded	yes
Cable type	CANopen®/DeviceNet™, PUR, violet [920]
Conductor structure signal line	19x 0.13 mm
AWG signal line	24
Conductor cross section	2x 0.25 mm² (Data cable)
	2x 0.34 mm² (Power supply)
	1x 0.34 mm² (Drain wire)
Wire diameter incl. insulation	1.95 mm ±0.05 mm (Data cable)
	1.4 mm ±0.05 mm (Power supply)

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

External cable diameter	6.7 mm ±0.3 mm
Outer sheath, material	PUR
External sheath, color	red lilac RAL 4001
Conductor material	Tin-plated Cu litz wires
Material wire insulation	Foamed PE (Data cable)
	PE (Power supply)
Single wire, color	red-black, blue-white
Twisted pairs	2 cores to the pair
Type of pair shielding	Plastic-coated aluminum foil, aluminum side outside
Overall twist	2 pairs around a drain wire in the center to the core
Optical shield covering	80 %
Insulation resistance	≥ 5 GΩ*km (Data cable)
	≥ 5 GΩ*km (Power supply)
Loop resistance	≤ 181.80 Ω/km (Data cable)
	≤ 114.80 Ω/km (Power supply)
Wave impedance	120 Ω ±10 % (with 1 MHz)
Cable capacity	nom. 40 nF/km (Data cable)
Nominal voltage, cable	≤ 300 V (Peak value, not for high-power applications)
Test voltage Core/Core	2000 V (50 Hz, 1 min.)
Test voltage Core/Shield	2000 V (50 Hz, 1 min.)
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Max. bending cycles	5000000
Shield attenuation	≤ 22.9 dB/km (with 1 MHz)
	≤ 16.4 dB/km (At 500 kHz)
	≤ 9.5 dB/km (At 125 kHz)
Halogen-free	in accordance with DIN VDE 0472 part 815
	according to IEC 60754-1
Flame resistance	IEC 60332-1-2
	in accordance with ISO 6722-1 5.22 (UN ECE-R 118.01)
Other resistance	Low adhesion
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-30 °C ... 70 °C (Cable, flexible installation)
	-20 °C ... 60 °C (for installation)
	-20 °C ... 60 °C (cable, drag chain applications)

Cable structure

Cable type	CANopen®/DeviceNet™, PUR, violet
Signal type/category	CANopen®
	DeviceNet™
Outer sheath, material	PUR
External sheath, color	red lilac RAL 4001

Ambient conditions

Ambient temperature (operation)	-20 °C ... 75 °C (Cable, flexible installation)

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

	-40 °C ... 80 °C (cable, fixed installation)

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)
	-40 °C ... 80 °C (cable, fixed installation)
	-20 °C ... 75 °C (Cable, flexible installation)

Standards and regulations

Standards/specifications	IEC 61076-2-101

chanhvinh.com


Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039


Drawings

Dimensional drawing



M12 SPEEDCON plug, straight

Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side


chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039


https://www.phoenixcontact.com/gb/products/1436039

Circuit diagram



Contact assignment of the M12 socket and the M12 plug

Dimensional drawing



M12-SPEEDCON socket, Y-distributor


chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039


https://www.phoenixcontact.com/gb/products/1436039

Dimensional drawing



M12-SPEEDCON socket, straight

Schematic diagram



Pin assignment M12 socket, 5-pos., A-coded, socket side view

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Approvals

EAC
Approval ID: RU C-DE.BL08.B.00286

UL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	125 V	4 A	-	-

cUL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	125 V	4 A	-	-

EAC
Approval ID: RU D-DE.HB35.B.00387

cULus Listed

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060307

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Accessories

Torque screwdriver

Torque screwdriver - TSD 04 SAC - 1208429

https://www.phoenixcontact.com/gb/products/1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

Torque screwdriver

Torque screwdriver - TSD-M 1,2NM - 1212224

https://www.phoenixcontact.com/gb/products/1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0. 3 - 1.2 Nm

chanhvinh.com

Adapter insert

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600

https://www.phoenixcontact.com/gb/products/1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

Tool

Tool - SAC BIT M12-D15 - 1208432

https://www.phoenixcontact.com/gb/products/1208432



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Sealing cap

Sealing cap - PROT-M12 FS-PA-CHAIN - 1430873

https://www.phoenixcontact.com/gb/products/1430873

M12 sealing cap made of plastic with fixing band, for sensor cables, for free M12 plugs



Locking clip

Locking clip - SAC-M12-EXCLIP-M - 1558988

https://www.phoenixcontact.com/gb/products/1558988

Locking clip for the pin side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

Screw plug

Screw plug - PROT-M12 MS-PA-CHAIN - 1430899

https://www.phoenixcontact.com/gb/products/1430899

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



Locking clip

Locking clip - SAC-M12-EXCLIP-F - 1558991

https://www.phoenixcontact.com/gb/products/1558991

Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

H distributor

H distributor - SAC-5PH-M-F/2XF SH1 SCO - 1417414

https://www.phoenixcontact.com/gb/products/1417414



H distributor, 5-position, shielded, Plug straight M12, coding: A, on Socket straight M12, coding: A and Socket straight M12, coding: A, Thread M12 not rotatable, Parallel distributor

T distributor

T distributor - SAC-5P-M12T/2XM12 VP - 1541186

https://www.phoenixcontact.com/gb/products/1541186



T distributor, 5-position, unshielded, Plug straight M12, coding: A, on Socket straight M12, coding: A and Socket straight M12, coding: A, Parallel distributor

chanhvinh.com

Bus system cable - SAC-5PY-F/2X 1,0-920-MS-FS

1436039

https://www.phoenixcontact.com/gb/products/1436039

T distributor

T distributor - SAC-5PT-F/F-M VP - 1424712

https://www.phoenixcontact.com/gb/products/1424712



T distributor, CANopen®, DeviceNet™, 5-position, unshielded, Socket straight M12, coding: A, on Socket straight M12, coding: A and Plug straight M12, coding: A, Parallel distributor

Termination resistor

Termination resistor - SAC-5P-M12MS CAN TR - 1507816

https://www.phoenixcontact.com/gb/products/1507816



Terminating resistor CANopen®/DeviceNet™ M12

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk