chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sensor/actuator cable, 3-position, PVC, black RAL 9005, free cable end, on Valve connector C (8 mm), with 1 LED, connected with Z diode, connected with Z diode, cable length: 3 m

Your advantages

- Easy and safe: 100% electrically tested plug-in components
- Convenient: increased machine availability thanks to quick and easy diagnostics

Commercial Data

Item number	1439515
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF1DEA
Product Key	BF1DEA
Catalog Page	Page 229 (C-2-2019)
GTIN	4046356505321
Weight per Piece (including packing)	130 g
Weight per Piece (excluding packing)	118.3 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Technical Data

Product properties

Product type	Sensor/actuator cable with valve connector
Number of positions	3
Application	Standard
No. of cable outlets	1
Shielded	no

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	24 V AC
	24 V DC
Nominal current I_N	4 A
Protective circuit	Z diode

LED signaling

Status display	1 LED
Status display present	yes

Material specifications

Color Handle area	black
Flammability rating according to UL 94	V0
Sealing material	TPU (Seal molded)
Material housing valve plug	TPU
Contact material	CuSn
Valve plug contact insert material	PA 6.6
Contact surface material	Sn

Connector

Header 1

Head design	free cable end

Head 2

Head design	Valve connector
Head thread type	C (8 mm)
Status indicator head	1 LED

Cable / line

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Cable length	3 m
UL AWM Style	2464
Number of positions	3
Shielded	no
Cable type	PVC black [PVC]
Conductor structure signal line	16x 0.20 mm
AWG signal line	20
Conductor cross section	3x 0.5 mm²
Wire diameter incl. insulation	1.5 mm ±0.05 mm
External cable diameter	4.8 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	black 1, black 2, green/yellow
Overall twist	3 wires, twisted
Max. conductor resistance	39 Ω/km (at 20 °C)
Insulation resistance	≥ 20 MΩ*km
Nominal voltage, cable	300 V
Test voltage	1200 V
Minimum bending radius, fixed installation	5 x D
Flame resistance	DIN VDE 0482
	DIN EN 50265-2-1
Resistance to oil	in accordance with DIN EN 60811-2-1
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

Cable structure

Cable type	PVC black
Outer sheath, material	PVC
External sheath, color	black RAL 9005

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-20 °C ... 85 °C (valve plug)

Standards and regulations

Valve connector

Standards/specifications	EN 175301-803

chanhvinh.com


Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515


Drawings

Dimensional drawing



Valve connector, type C

Dimensional drawing



Valve connector, type C, side view


chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515


https://www.phoenixcontact.com/gb/products/1439515

Schematic diagram



Valve connector connector pin assignment, type C

Circuit diagram



Contact assignment of the valve plug

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Approvals

EAC
Approval ID: RU D-DE.HB35.B.00387

CSAus
Approval ID: 13631

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	24 V	6 A	-	-

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Classifications

ECLASS

ECLASS-9.0	27060312
ECLASS-10.0.1	27060312
ECLASS-11.0	27060312

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	31251500

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Accessories

Torque screwdriver

Torque screwdriver - TSD-M 1,2NM - 1212224

https://www.phoenixcontact.com/gb/products/1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0. 3 - 1.2 Nm

Insert label

Insert label - PABA WH/23 - 1013779

https://www.phoenixcontact.com/gb/products/1013779



Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Screw insert

Screw insert - SF-BIT-PH 2-70 - 1212583

https://www.phoenixcontact.com/gb/products/1212583




Screw bit, PH crosshead, E6.3-1/4" drive, size: PH 2 x 70 mm, suitable for holder according to DIN 3126-F6.3/ISO 1173

Insert label

Insert label - PABA YE/23 - 1013782

https://www.phoenixcontact.com/gb/products/1013782



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Marker pen

Marker pen - B-STIFT - 1051993

https://www.phoenixcontact.com/gb/products/1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

Diagonal cutter

Diagonal cutter - CUTFOX-S VDE - 1212207

https://www.phoenixcontact.com/gb/products/1212207



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Stripping tool

Stripping tool - WIREFOX SAC-1 - 1212757

https://www.phoenixcontact.com/gb/products/1212757



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

Stripping tool

Stripping tool - WIREFOX SAC - 1212623

https://www.phoenixcontact.com/gb/products/1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Stripping tool

Stripping tool - WIREFOX 10 - 1212150

https://www.phoenixcontact.com/gb/products/1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm^2, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm^2 stranded/1.5 mm^2 solid, replaceable stripping blade

Protective hose adapter

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884

https://www.phoenixcontact.com/gb/products/1422884



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

chanhvinh.com

Sensor/actuator cable - SAC-3P- 3,0-PVC/C-1L-Z

1439515

https://www.phoenixcontact.com/gb/products/1439515

Protective hose

Protective hose - WP-PA HF 13,0 BK - 3240681

https://www.phoenixcontact.com/gb/products/3240681



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

Protective hose

Protective hose - WP-PA HF-HB 13,0 BK - 3240839

https://www.phoenixcontact.com/gb/products/3240839



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk