chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sensor/actuator flush-type socket, 4-pos., M12 SPEEDCON, rear/screw mounting with M16 thread, with 0.5 m TPE litz wire, 4 x 0.34 mm^2

Your advantages

- Pre-assembled with litz wires for immediate use
- Customer-specific assemblies and litz wire lengths available
- Sealed on the litz wire side for optimum leak-tightness
- All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- For high transmission safety: shield connection to the housing with optional EMC nut
- SPEEDCON fast locking system reduces cabling times

Commercial Data

Item number	1444681
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	ABQCDH
Product Key	ABQCDH
GTIN	4046356567428
Weight per Piece (including packing)	48.8 g
Weight per Piece (excluding packing)	47.5 g
Customs tariff number	85444290
Country of origin	DE

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Technical Data

Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Safety note

Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	• The products are suitable for applications in plant, controller, and electrical device engineering.
	• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
	• Assembled products may not be manipulated or improperly opened.
	• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
	• When using the product in direct connection with third-party manufacturers, the user is responsible.
	• For operating voltages > 50 V AC, conductive connector housings must be grounded
	• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
	• Observe the corresponding technical data. You will find information: o On the product o On the packing label o In the supplied documentation o Online at phoenixcontact.com/products under the product
	• Only use tools recommended by Phoenix Contact
	• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

	• Ensure that the protective or functional ground has been properly connected.
	• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
	• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

Product properties

Product type	Circular connectors (device side)
Number of positions	4
No. of cable outlets	1
Shielded	no
Coding	A-coded

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP65 (When plugged in)
Degree of protection	IP65/IP67
Ambient temperature (operation)	-25 ... -85 (Plug / socket)
	-40 °C ... 85 °C (without mechanical actuation)
	-25 °C ... 85 °C (Cable, flexible installation)
	-40 °C ... 85 °C (cable, fixed installation)

Connector

Insertion/withdrawal cycles	> 100

Connection 1

Head design	Socket
Head thread type	M12
Coding	A-coded

Electrical properties

Rated surge voltage	2.5 kV AC
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	250 V
Nominal current I_N	4 A

Material specifications

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Flammability rating according to UL 94	V0
Sealing material	FKM
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Cable gland material	Zinc die-cast, nickel-plated

Connection data

Conductor connection

Connection method	Individual wires

Mounting

Mounting type	Rear wall/screw mounting
Assembly instructions	With flat nut

Standards and regulations

M12

Standards/specifications	according to IEC 61076-2-101

Cable / line

Cable length	2

Cable structure

Cable type	TPE litz wire
Signal type/category	Universal
Conductor material	Tin-plated Cu litz wires
Conductor structure signal line	7x 0.25 mm
AWG signal line	22
Material wire insulation	TPE
Thickness, insulation	0.21 mm (Core insulation)
Wire diameter incl. insulation	1.2 mm ±0.07 mm
Single wire, color	brown, white, blue, black

Electrical properties

Nominal voltage, cable	300 V
Test voltage, cable	2000 V AC
Conductor resistance	≤ 57.6 mΩ/m
Cable insulation resistance	≥ 20 MΩ*km

Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C (Cable, flexible installation)
	-40 °C ... 85 °C (cable, fixed installation)

chanhvinh.com


Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681


Drawings

Schematic diagram



Pin assignment M12 socket, 4-pos., A-coded, view female side

Dimensional drawing



M12 flush-type socket


chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Dimensional drawing



Housing cutout for M16 fastening thread, mounting panel with thread


chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Dimensional drawing



Housing cutout for M16 fastening thread, mounting panel with feed-through hole (alternatively with area as anti-rotation protection for panel thicknesses > 2 mm up to max. 4.5 mm)


chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Circuit diagram



Contact assignment of the M12 socket

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Approvals

EAC

cULus Recognized

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	250 V	4 A	22 - 20	-

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Classifications

ECLASS

ECLASS-9.0	27440102
ECLASS-10.0.1	27440102
ECLASS-11.0	27440102

ETIM

ETIM 8.0	EC002635

UNSPSC

UNSPSC 21.0	39121400

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Accessories

Screw plug

Screw plug - PROT-M12 - 1680539

https://www.phoenixcontact.com/gb/products/1680539



An M12 screw plug for the unoccupied M12 sockets of the sensor/actuator cable, boxes and flush-type connectors

Screw plug

Screw plug - PROT-M12 SH - 1503302

https://www.phoenixcontact.com/gb/products/1503302



An M12 screw plug for the unoccupied M12 sockets of the shielded sensor/actuator cable, boxes and flush-type connectors

chanhvinh.com

Device connector, rear mounting - SACC-DSI-M12FS-4P-M16/2,0

1444681

https://www.phoenixcontact.com/gb/products/1444681

Screw plug

Screw plug - PROT-M12 FB - 1555538

https://www.phoenixcontact.com/gb/products/1555538



M12 high-grade steel screw plug, for unoccupied M12 sockets of the sensor/actuator cables, boxes and flush-type connectors for the food industry

Flat gasket

Flat gasket - SACC-M16-SEAL CLM - 1430394

https://www.phoenixcontact.com/gb/products/1430394

M16 flat gasket for M12 flush-type connectors with M16 fastening thread



Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk