chanhvinh.com

VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replacement plug for PV special combined lightning current and surge arrester from the VAL-SPP-T2-1000DC-PV-2+V-UT... product family.

Your advantages

- Easy and safe installation with forward-thinking handling and safety features
- Reliable system protection with maximum performance and endurance
- Can be used in a wide range of applications due to the optimized design and broad portfolio
- Simple planning due to comprehensive digital data and selectors

Commercial data

Item number	1466779
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	CL138Z
GTIN	4063151862251
Weight per piece (including packing)	63.6 g
Weight per piece (excluding packing)	61.2 g
Country of origin	DE

chanhvinh.com

VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Technical data

Product properties

Product type	Replacement plug
Product family	VAL-SPP
IEC test classification	PV II
	PV T2
EN type	T2
IEC power supply system	DC
Type	Male
Number of positions	1
Installation location	Indoor
Installation location of the disconnect device	Internal
Accessibility	Accessible
Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)
Surge protection fault message	optical


Insulation characteristics

Overvoltage category	III
Pollution degree	2

Connection data

Connection method	pluggable

Dimensions

Dimensional drawing	
Width	17.5 mm
Height	54.2 mm
Depth	61.5 mm
Horizontal pitch	1 Div.

Material specifications

Color	light gray (RAL 7035)
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PA 6.6-FR 20 % GF
Material group	I
Housing material	PA 6.6-FR 20 % GF

chanhvinh.com

VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Protective circuit

Residual current I_{PE}	≤ 350 µA AC
	≤ 100 µA DC
Standby power consumption P_C	≤ 60 mVA
Nominal discharge current I_n (8/20) µs	20 kA
Maximum discharge current I_{max} (8/20) µs	40 kA
Total discharge current I_{total} (8/20) µs	40 kA
Voltage protection level U_p	≤ 4.2 kV (2 plugs in series)
Residual voltage U_{res}	≤ 4.2 kV (at In, 2 plugs in series)
	≤ 3.6 kV (at 10 kA, 2 plugs in series)
	≤ 3.2 kV (at 5 kA, 2 plugs in series)
	≤ 3 kV (at 3 kA, 2 plugs in series)
Response time t_A	≤ 25 ns

PV protective circuit

Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)

Protective circuit DC voltage side (DC)

Open circuit voltage U_{OCSTC}	1000 V DC (2 plugs in series)
Maximum discharge current I_{max} (8/20) µs	40 kA
Response time t_A	≤ 25 ns
Total discharge current I_{total} (8/20) µs	40 kA
Insulation resistance R_{iso}	> 5 MΩ (at 500 V DC)
Nominal discharge current I_n (8/20) µs	20 kA
Continuous operating current I_{CPV}	≤ 100 µA DC
Maximum continuous operating voltage U_{CPV}	1200 V DC (2 plugs in series)
Short-circuit current rating I_{SCPV}	15000 A
Residual voltage U_{res}	≤ 4.2 kV (at In, 2 plugs in series)
	≤ 3.6 kV (at 10 kA, 2 plugs in series)
	≤ 3.2 kV (at 5 kA, 2 plugs in series)
	≤ 3 kV (at 3 kA, 2 plugs in series)
Residual current I_{PE}	≤ 350 µA AC
	≤ 100 µA DC
Voltage protection level U_p	≤ 4.2 kV (2 plugs in series)
Standby power consumption P_C	≤ 60 mVA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20C
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (assembly)	-5 °C ... 50 °C
Altitude	≤ 5000 m (amsl)

chanhvinh.com

VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation)	5g (5-500 Hz/2.5 h/XYZ)

Standards and regulations

Standards/specifications	EN 61643-31
Note	2019
Standards/specifications	IEC 61643-31
Note	2018

Mounting

Mounting type	on base element

chanhvinh.com


VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Drawings

Dimensional drawing



Circuit diagram



chanhvinh.com

VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/in/products/1466779

IECEE CB Scheme
Approval ID: NL-109183

CCA
Approval ID: NTR NL-8030

KEMA-KEUR
Approval ID: 71-133324

chanhvinh.com

VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Classifications

ECLASS

ECLASS-11.0	27130890
ECLASS-13.0	27171492

ETIM

ETIM 9.0	EC002496

chanhvinh.com

VAL-SPP-T2-1000DC-PV-P - Type 2 surge protection plug

1466779

https://www.phoenixcontact.com/in/products/1466779

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in