chanhvinh.com

# SAC-4P-100,0-PUR/0,34 - Cable reel

1501663

https://www.phoenixcontact.com/pc/products/1501663

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



By the meter, Cable reel, PUR halogen-free, black-gray RAL 7021, 4-wire, color single wire: brown, white, blue, black, cable length: 100 m

## Commercial data

| | |
|---|---|
| Item number | 1501663 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Product key | BF1LBA |
| Catalog page | Page 302 (C-2-2019) |
| GTIN | 4017918813352 |
| Weight per piece (including packing) | 2,558 g |
| Weight per piece (excluding packing) | 2,524.8 g |
| Customs tariff number | 85444995 |
| Country of origin | DE |

chanhvinh.com

# SAC-4P-100,0-PUR/0,34 - Cable reel

1501663

https://www.phoenixcontact.com/pc/products/1501663

## Technical data


### Product properties

| | |
|---|---|
| Product type | Cable by the meter |
| Application | Connector |
| Number of positions | 4 |
| Shielded | no |

### Cable/line

| | |
|---|---|
| Cable length | 100 m |

PUR halogen-free black [PUR]

| | |
|---|---|
| Dimensional drawing |  |
| Cable weight | 30 kg/km |
| UL AWM Style | 20549 / 10493 (80°C/300 V) |
| Number of positions | 4 |
| Shielded | no |
| Cable type | PUR halogen-free black [PUR] |
| Conductor structure signal line | 42x 0.10 mm |
| AWG signal line | 22 |
| Conductor cross section | 4x 0.34 mm² (Signal line) |
| Wire diameter incl. insulation | 1.27 mm ±0.02 mm |
| External cable diameter | 4.20 mm ±0.15 mm |
| Outer sheath, material | PUR |
| External sheath, color | black-gray RAL 7021 |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | PP |
| Single wire, color | brown, white, blue, black |
| Thickness, insulation | ≥ 0.21 mm |
| Thickness, outer sheath | approx. 0.50 mm |
| Overall twist | 4 wires, twisted |
| Max. conductor resistance | ≤ 58 Ω/km |
| Insulation resistance | ≥ 1 GΩ*km |
| Nominal voltage, cable | ≤ 300 V |
| Test voltage | ≥ 3000 V |
| Minimum bending radius, fixed installation | 5 x D |

chanhvinh.com

# SAC-4P-100,0-PUR/0,34 - Cable reel

1501663

https://www.phoenixcontact.com/pc/products/1501663

| | |
|---|---|
| Minimum bending radius, flexible installation | 10 x D |
| Smallest bending radius, fixed installation | 21 mm |
| Smallest bending radius, movable installation | 42 mm |
| Dynamic load capacity (bending) | Max. bending cycles: 10000000, Bending radius: 10 x D, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s² |
| Halogen-free | in accordance with DIN VDE 0472 part 815 |
| | in accordance with DIN EN 50267-2-1 |
| Flame resistance | in accordance with UL 758/1581 FT2 |
| | DIN EN 60332-2-2 (20 s) |
| Resistance to oil | in accordance with DIN EN 60811-2-1 |
| Other resistance | Highly resistant to acids, alkaline solutions and solvents |
| | hydrolysis and microbe resistant |
| | partly UV-resistant (in accordance with DIN EN ISO 4892-2-A) |
| | Low adhesion |
| | abrasion-resistant |
| Special properties | Flexible cable conduit capable |
| | Silicone-free |
| | Free of substances which would hinder coating with paint or varnish |
| | flexible |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -25 °C ... 80 °C (Cable, flexible installation) |

chanhvinh.com

# SAC-4P-100,0-PUR/0,34 - Cable reel

1501663

https://www.phoenixcontact.com/pc/products/1501663

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/1501663

**EAC-RoHS**
Approval ID: RU D-DE.HB35.B.00371

chanhvinh.com

# SAC-4P-100,0-PUR/0,34 - Cable reel

1501663

https://www.phoenixcontact.com/pc/products/1501663

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27061801 |
| ECLASS-12.0 | 27061801 |
| ECLASS-13.0 | 27061801 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC003249 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 26121600 |

chanhvinh.com

# SAC-4P-100,0-PUR/0,34 - Cable reel

1501663

https://www.phoenixcontact.com/pc/products/1501663

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

EF3.0 Climate Change

| | |
|---|---|
| CO2e kg | 50.068 kg CO2e |

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com