chanhvinh.com

Connector component - RCK-TWUM/BL16+3/15,5PUR-U

1511488

https://www.phoenixcontact.com/gb/products/1511488

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Socket M23, angled, 19-pos., with 15.5 m master cable

Commercial Data

Item number	1511488
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	ABRDBB
Product Key	ABRDBB
GTIN	4017918903596
Weight per Piece (including packing)	3,040 g
Weight per Piece (excluding packing)	3,040 g
Customs tariff number	85444290
Country of origin	DE

chanhvinh.com

Connector component - RCK-TWUM/BL16+3/15,5PUR-U

1511488

https://www.phoenixcontact.com/gb/products/1511488

Technical Data

Product properties

Number of positions	19
Application	Sensor/actuator box

Electrical properties

Nominal voltage U_N	48 V AC
	60 V DC

LED signaling

Status display present	No

Material specifications

Color	black
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA
Material of contact surface, master cable side	gold-plated
Housing material	PUR

Cable / line

Cable length	15.5 m
Cable weight	183.7 kg/km
UL AWM Style	20549 (80°C/300 V)
Number of positions	19
Shielded	no
Cable type	PUR/PVC black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	16x 0.5 mm² (Signal line)
	3x 1 mm² (power line)
Wire diameter incl. insulation	1.5 mm ±0.1 mm (Signal line)
	2.1 mm ±0.1 mm (power line)
External cable diameter	10.5 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, green/yellow, white, green, yellow, gray, pink, red, black, violet, gray/pink, red/blue, white/green, brown/green, white/yellow, yellow/brown, white/gray, gray/brown
Inner sheath thickness	≥ 0.15 mm
Thickness, outer sheath	≥ 0.76 mm
Overall twist	Wires twisted in layers

chanhvinh.com

Connector component - RCK-TWUM/BL16+3/15,5PUR-U

1511488

https://www.phoenixcontact.com/gb/products/1511488

Nominal voltage, cable	300 V
Test voltage	2000 V
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	10 x D
Max. bending cycles	1500000
Flame resistance	according to DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803
Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

Master cable data/connection data

Connection method	M23 socket

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-40 °C ... 90 °C (for fixed installation)
Ambient temperature (storage/transport)	-5 °C ... 80 °C (for flexible installation)

chanhvinh.com


Connector component - RCK-TWUM/BL16+3/15,5PUR-U

1511488

https://www.phoenixcontact.com/gb/products/1511488

Drawings

Schematic diagram



Pin assignment M23 socket, 19-pos., female side view

chanhvinh.com

Connector component - RCK-TWUM/BL16+3/15,5PUR-U

1511488

https://www.phoenixcontact.com/gb/products/1511488

Classifications

ECLASS

ECLASS-9.0	27060311
ECLASS-10.0.1	27060311
ECLASS-11.0	27060311

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Connector component - RCK-TWUM/BL16+3/15,5PUR-U

1511488

https://www.phoenixcontact.com/gb/products/1511488

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk