chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Bus system cable, INTERBUS (16 Mbps), 5-position, PUR halogen-free, may green RAL 6017, shielded, free cable end, on Socket straight M12 SPEEDCON, coding: B, cable length: 10 m

Commercial Data

Item number	1517932
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF1CKB
Product Key	BF1CKB
Catalog Page	Page 198 (C-6-2019)
GTIN	4017918968052
Weight per Piece (including packing)	722.6 g
Weight per Piece (excluding packing)	716 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	5
Application	Standard
No. of cable outlets	1
Shielded	yes
Coding	B - inverse

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Interfaces

Bus system	INTERBUS
Signal type/category	INTERBUS, 16 Mbps

LED signaling

Status display	No
Status display present	No

Electrical properties

Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A
Transmission medium	Copper

Material specifications

Flammability rating according to UL 94	V0
Sealing material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA 6.6
Cable gland material	Zinc die-cast, nickel-plated

Connection data

Pin assignment

Contact | Color (signal designation) | Contact (optional)	1 (Socket) = YE (DO)
	2 (Socket) = GN (DO)
	3 (Socket) = GY (DI)

chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

	4 (Socket) = PK (DI)
	5 (Socket) = BN (GND)

Connector

Header 1

Head design	free cable end

Head 2

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	B

Cable / line

Cable length	10 m
Cable weight	70 kg/km
Number of positions	6
Shielded	yes
Cable type	INTERBUS [900]
Signal speed	0.66 c
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross section	3x 2x 0.22 mm²
External cable diameter	8 mm
Outer sheath, material	PUR
External sheath, color	may green RAL 6017
Conductor material	Bare Cu litz wires
Material wire insulation	PE
Single wire, color	Green-yellow, white-brown, gray-pink
Twisted pairs	2 cores to the pair
Overall twist	3 pairs to the core
Insulation resistance	≥ 5 GΩ*km
Coupling resistance	< 250.00 mΩ/m (at 30 MHz)
Loop resistance	≤ 159.80 Ω/km
Wave impedance	120 Ω ±20 % (at 64 kHz)
	100 Ω ±15 % (with 1 MHz)
Cable capacity	≤ 60 nF/km (At 800 Hz)
Nominal voltage, cable	250 V (Peak value, not for high-power applications)
Test voltage Core/Core	1500 V_{rms}
Test voltage Core/Shield	1000 V_{rms}
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	15 x D
Max. bending cycles	5000000

chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

Near end crosstalk attenuation (NEXT)	≥ 61 dB (at 772 kHz)
	≥ 59 dB (with 1 MHz)
	≥ 55 dB (at 2 MHz)
	≥ 50 dB (at 4 MHz)
	≥ 46 dB (at 8 MHz)
	≥ 44 dB (at 10 MHz)
	≥ 41 dB (at 16 MHz)
	≥ 40 dB (at 20 MHz)
Shield attenuation	≤ 15 dB/km (at 256 kHz)
	≤ 24 dB/km (at 772 kHz)
	≤ 27 dB/km (with 1 MHz)
	≤ 52 dB/km (at 4 MHz)
	≤ 84 dB/km (at 10 MHz)
	≤ 112 dB/km (at 16 MHz)
	≤ 119 dB/km (at 20 MHz)
Flame resistance	according to VDE 0472, Part 4, test type B
	according to IEC 60332-1
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-30 °C ... 70 °C (Cable, flexible installation)

Cable structure

Cable type	INTERBUS
Signal type/category	INTERBUS, 16 Mbps
Outer sheath, material	PUR
External sheath, color	green RAL 6017

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

chanhvinh.com


Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932


Drawings

Circuit diagram



Contact assignment of the M12 socket

Schematic diagram



Pin assignment M12 socket, 5-pos., B-coded, female side


chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

Dimensional drawing



M12 x 1 socket, straight, shielded

chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

Approvals

EAC
Approval ID: RU D-DE.HB35.B.00387

chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060307

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Bus system cable - SAC-5P-10,0-900/FSB SCO

1517932

https://www.phoenixcontact.com/gb/products/1517932

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk