
chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug straight M8, on free cable end, cable length: 15 m, Connector unshielded

Commercial Data

Item number	1575754
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	BF1BDD
Product Key	BF1BDD
Catalog Page	Page 432 (C-2-2019)
GTIN	4046356423854
Weight per Piece (including packing)	810.5 g
Weight per Piece (excluding packing)	810.5 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Technical Data

Notes

General	Further products with variable cable lengths can be found in the accessories section

Product properties

Product type	Data cable preassembled
Number of positions	5
Application	Standard
No. of cable outlets	1
Shielded	yes
Coding	B - inverse

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Interfaces

Bus system	CANopen®/DeviceNet™
Signal type/category	CANopen®
	DeviceNet™
	CANopen®
	DeviceNet™

LED signaling

Status display	No

Electrical properties

Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	30 V AC
	30 V DC
Nominal current I_N	4 A
Transmission medium	Copper

Material specifications

Color Handle area	black
Flammability rating according to UL 94	HB
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Cable gland material	Zinc die-cast, nickel-plated

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Connection data

Pin assignment

Contact | Color (signal designation) | Contact (optional)	1 (Plug) = SR (shield)
	2 (Plug) = RD (V+)
	4 (Plug) = BK (V-)
	3 (Plug) = WH (CAN_H)
	5 (Plug) = BU (CAN_L)

Connector

Connection 1

Head design	Plug
Head cable outlet	straight
Head thread type	M8

Head 2

Head design	free cable end

Cable / line

Cable length	15 m
Cable weight	90 kg/km
UL AWM Style	21198 (80°C/300 V)
Number of positions	4
Shielded	yes
Cable type	CANopen®/DeviceNet™, PUR, violet [920]
Conductor structure signal line	19x 0.13 mm
AWG signal line	24
Conductor cross section	2x 0.25 mm² (Data cable)
	2x 0.34 mm² (Power supply)
	1x 0.34 mm² (Drain wire)
Wire diameter incl. insulation	1.95 mm ±0.05 mm (Data cable)
	1.4 mm ±0.05 mm (Power supply)
External cable diameter	6.7 mm ±0.3 mm
Outer sheath, material	PUR
External sheath, color	red lilac RAL 4001
Conductor material	Tin-plated Cu litz wires
Material wire insulation	Foamed PE (Data cable)
	PE (Power supply)
Single wire, color	red-black, blue-white
Twisted pairs	2 cores to the pair
Type of pair shielding	Plastic-coated aluminum foil, aluminum side outside
Overall twist	2 pairs around a drain wire in the center to the core
Optical shield covering	80 %
Insulation resistance	≥ 5 GΩ*km (Data cable)

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

	≥ 5 GΩ*km (Power supply)
Loop resistance	≤ 181.80 Ω/km (Data cable)
	≤ 114.80 Ω/km (Power supply)
Wave impedance	120 Ω ±10 % (with 1 MHz)
Cable capacity	nom. 40 nF/km (Data cable)
Nominal voltage, cable	≤ 300 V (Peak value, not for high-power applications)
Test voltage Core/Core	2000 V (50 Hz, 1 min.)
Test voltage Core/Shield	2000 V (50 Hz, 1 min.)
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Max. bending cycles	5000000
Shield attenuation	≤ 22.9 dB/km (with 1 MHz)
	≤ 16.4 dB/km (At 500 kHz)
	≤ 9.5 dB/km (At 125 kHz)
Halogen-free	in accordance with DIN VDE 0472 part 815
	according to IEC 60754-1
Flame resistance	IEC 60332-1-2
	in accordance with ISO 6722-1 5.22 (UN ECE-R 118.01)
Other resistance	Low adhesion
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-30 °C ... 70 °C (Cable, flexible installation)
	-20 °C ... 60 °C (for installation)
	-20 °C ... 60 °C (cable, drag chain applications)

Cable structure

Cable type	CANopen®/DeviceNet™, PUR, violet
Signal type/category	CANopen®
	DeviceNet™
Outer sheath, material	PUR
External sheath, color	red lilac RAL 4001

Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

chanhvinh.com


Bus system cable - SAC-5P-M 8MS/15,0-920

1575754


https://www.phoenixcontact.com/gb/products/1575754

Drawings

Dimensional drawing



Circuit diagram




chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Schematic diagram



Pin assignment, pin side, M8, 5-pos., B-coded

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Approvals

UL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	30 V	3 A	-	-

cUL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	30 V	3 A	-	-

EAC
Approval ID: RU D-DE.HB35.B.00387

cULus Listed

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Classifications

ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060307

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer’s declaration available under “Downloads”

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Accessories

Termination resistor

Termination resistor - SAC-5P-M 8MS DN TR - 1435988

https://www.phoenixcontact.com/gb/products/1435988



Termination resistor, DeviceNet™, M8, 5-pos.

Bus system cable

Bus system cable - SAC-5P-M 8MS/920/... - 1575767

https://www.phoenixcontact.com/gb/products/1575767



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug straight M8, on free cable end, cable length: Free input (0.2 ... 40.0 m), Connector unshielded

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920


1575754

https://www.phoenixcontact.com/gb/products/1575754

Bus system cable

Bus system cable - SAC-5P-M 8MR/920/... - 1575903

https://www.phoenixcontact.com/gb/products/1575903



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug angled M8, on free cable end, cable length: Free input (0.2 ... 40.0 m), Connector unshielded

Bus system cable

Bus system cable - SAC-5P-M 8FS/920/... - 1575819

https://www.phoenixcontact.com/gb/products/1575819



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, free cable end, on Socket straight M8, cable length: Free input (0.2 ... 40.0 m), Connector unshielded

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920


1575754

https://www.phoenixcontact.com/gb/products/1575754

Bus system cable

Bus system cable - SAC-5P-M 8FR/920/... - 1575916

https://www.phoenixcontact.com/gb/products/1575916



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, free cable end, on Socket angled M8, cable length: Free input (0.2 ... 40.0 m), Connector unshielded

Bus system cable

Bus system cable - SAC-5P-M 8MS-M 8FS/920/... - 1575893

https://www.phoenixcontact.com/gb/products/1575893



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug straight M8, on Socket straight M8, cable length: Free input (0.2 ... 40.0 m), Connector unshielded

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Bus system cable

Bus system cable - SAC-5P-M 8MR-M 8FS/920/... - 1575932

https://www.phoenixcontact.com/gb/products/1575932



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug angled M8, on Socket straight M8, cable length: Free input (0.2 ... 40.0 m), Connector unshielded

Bus system cable

Bus system cable - SAC-5P-M 8MR-M 8FR/920/... - 1575945

https://www.phoenixcontact.com/gb/products/1575945



Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug angled M8, on Socket angled M8, cable length: Free input (0.2 ... 40.0 m), Connector unshielded

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Torque screwdriver

Torque screwdriver - TSD 02 SAC - 1208487

https://www.phoenixcontact.com/gb/products/1208487



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

Tool

Tool - SAC BIT M8-D10 - 1208461

https://www.phoenixcontact.com/gb/products/1208461



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Sealing cap

Sealing cap - PROT-M 8 FS-PA-CHAIN - 1430857

https://www.phoenixcontact.com/gb/products/1430857

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 plugs



Data connector

Data connector - SACC-M12FS-5PL SH DN - 1424672

https://www.phoenixcontact.com/gb/products/1424672



Data connector, CANopen®, DeviceNet™, 5-position, shielded, Socket straight M12, Coding: A, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Data connector

Data connector - SACC-M12MS-5PL SH DN - 1424670

https://www.phoenixcontact.com/gb/products/1424670



Data connector, CANopen®, DeviceNet™, 5-position, shielded, Plug straight M12, Coding: A, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

Data connector

Data connector - SACC-M12FR-5PL SH DN - 1424673

https://www.phoenixcontact.com/gb/products/1424673



Data connector, CANopen®, DeviceNet™, 5-position, shielded, Socket angled M12, Coding: A, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Data connector

Data connector - SACC-M12MR-5PL SH DN - 1424671

https://www.phoenixcontact.com/gb/products/1424671



Data connector, CANopen®, DeviceNet™, 5-position, shielded, Plug angled M12, Coding: A, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

Data connector

Data connector - SACC-M12FS-5QO SH DN - 1422760

https://www.phoenixcontact.com/gb/products/1422760



Data connector, CANopen®, DeviceNet™, 5-position, halogen-free, shielded, Socket straight M12 SPEEDCON, Coding: A, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

chanhvinh.com

Bus system cable - SAC-5P-M 8MS/15,0-920

1575754

https://www.phoenixcontact.com/gb/products/1575754

Data connector

Data connector - SACC-M12M12FS-8QO SH ETH - 1422759

https://www.phoenixcontact.com/gb/products/1422759



Data connector, CANopen®, DeviceNet™, 5-position, halogen-free, shielded, Plug straight M12 SPEEDCON, Coding: A, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk