chanhvinh.com

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable plug in molded plastic, Straight, plastic molded, number of positions: 12, type of locking: Screw locking mechanism, cable length: 5 m, shielded: yes, color of outer sheath: orange RAL 2003

Your advantages

- Our standard: robust halogen-free PUR cable
- Simple and safe: 100% electrically tested and assembled ready for use
- Designs with preassembled cables on one or both sides
- High flexibility: customer-specific assemblies and cable lengths can be supplied

Commercial data

Item number	1619248
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	ABRDFA
Product key	ABRDFA
Catalog page	Page 216 (C-2-2019)
GTIN	4046356833424
Weight per piece (including packing)	619 g
Weight per piece (excluding packing)	540 g
Customs tariff number	85444290
Country of origin	DE

chanhvinh.com

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248

Technical data

Product properties

Product type	Signal and power cable

Data management status

Article revision	09

Connector

Connector specifications

Type	Straight, plastic molded
Housing material	Zinc die-cast
Type of locking	Screw locking mechanism
Degree of protection	IP67, when in locked state
No. of pos.	12
Direction of rotation	Standard
Contact switching type	Socket
Insertion/withdrawal cycles	50
Contact resistance	< 0.3 mΩ
Max. current	8 A
Voltage	48 V AC
	74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV
Ambient temperature (operation)	-40 °C ... 105 °C

Cable specifications

Cable type	RSL9YSLC11Y
Shielded	yes
Cable structure	4 x 2 x 0.25 mm² + 2 x 0.5 mm²
Cable structure (AWG)	24 AWG/4pr + 20 AWG/2c
External cable diameter	8.00 mm
Outer sheath, material	TPU
Material wire insulation	PP
External sheath, color	orange RAL 2003
Test voltage	1 kV
Rated current	9 A
Smallest bending radius, fixed installation	40 mm
Smallest bending radius, movable installation	60 mm
Ambient temperature (operation) for fixed installation	-40 °C ... 80 °C
Ambient temperature (operation) for flexible installation	-20 °C ... 60 °C

Electrical properties

chanhvinh.com

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248

Nominal current I_N	9 A

Cable/line

Cable length	5 m

chanhvinh.com


K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248


Drawings

Dimensional drawing



Dimensional drawing

Circuit diagram




chanhvinh.com

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248

Schematic diagram



Connector pin assignment

chanhvinh.com

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1619248

EAC
Approval ID: 19060508

UL Listed
Approval ID: E335019-20140707

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Power	48 V	5 A	-	-
Signal	48 V	2 A	-	-

cUL Listed
Approval ID: E335019-20140707

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Power	48 V	5 A	-	-
Signal	48 V	2 A	-	-

cULus Listed

chanhvinh.com

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248

Classifications

ECLASS

ECLASS-11.0	27060106
ECLASS-12.0	27060106
ECLASS-13.0	27060106

ETIM

ETIM 9.0	EC003250

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

https://www.phoenixcontact.com/gb/products/1619248

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(b), 6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	9578f33d-670e-4d0a-9982-0dfb944cb675

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk