chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable

1656301

https://www.phoenixcontact.com/pc/products/1656301

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assembled D-SUB cable shielded, 25-pos., stranded (7-wire), cable color RAL 7000 (gray), IP20 degree of protection, head 1 with socket shell 3 and straight cable outlet, head 2 with pin shell 3 and straight cable outlet, length: 2 m

Commercial data

Item number	1656301
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	ABNCAS
Catalog page	Page 218 (C-2-2013)
GTIN	4046356029780
Weight per piece (including packing)	230.5 g
Weight per piece (excluding packing)	230.5 g
Customs tariff number	85444290
Country of origin	CN

chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable

1656301

https://www.phoenixcontact.com/pc/products/1656301

Technical data

Product properties

Product type	Data cable preassembled
Type	D-SUB
Sensor type	Universal
Number of positions	25
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	III
Degree of pollution	2

Electrical properties

Rated current	1 A
Operating voltage	30 V
Transmission medium	Copper

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 50

Material specifications

Housing material	PVC
Contact material	Copper alloy
Contact surface material	gold-plated
Outer sheath, material	PVC

Connection data

Connection technology

Connection method	D-SUB

Conductor connection

Connection method	D-SUB

Connector

Connection 1

Type	Socket straight D-SUB 25
Degree of protection	IP20

Connection 2

Type	Plug straight D-SUB 25
Degree of protection	IP20

chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable

1656301

https://www.phoenixcontact.com/pc/products/1656301

Cable/line

Outer sheath, material	PVC
Cable cross section	0.08 mm²
Conductor structure signal line	7.00 mm
AWG signal line	28

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	0 °C ... 70 °C


chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable


1656301

https://www.phoenixcontact.com/pc/products/1656301

Drawings



Circuit diagram



Connector pin assignment


chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable

1656301

https://www.phoenixcontact.com/pc/products/1656301

Schematic diagram



Pin connector pattern

chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable

1656301

https://www.phoenixcontact.com/pc/products/1656301

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/1656301

EAC
Approval ID: 19060508

chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable

1656301

https://www.phoenixcontact.com/pc/products/1656301

Classifications

ECLASS

ECLASS-12.0	27060390
ECLASS-11.0	27060390
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

VS-25-DSUB-20-LI-2,0 - D-SUB cable

1656301

https://www.phoenixcontact.com/pc/products/1656301

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com