chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug angled M8, coding: A, with 2 LEDs, on Socket angled M8, coding: A, with 2 LEDs, cable length: 0.6 m

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Convenient: increased machine availability thanks to quick and easy diagnostics

## Commercial data

| | |
|---|---|
| Item number | 1682113 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | BF1BBA |
| Product key | BF1BBA |
| Catalog page | Page 188 (C-2-2019) |
| GTIN | 4017918158774 |
| Weight per piece (including packing) | 20.6 g |
| Weight per piece (excluding packing) | 20.6 g |
| Customs tariff number | 85444290 |
| Country of origin | PL |

chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

## Technical data

### Product properties

| | |
|---|---|
| Product type | Sensor/actuator cable |
| Application | Standard |
| Number of positions | 3 |
| No. of cable outlets | 1 |
| Shielded | no |
| Coding | A |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | II |
| Degree of pollution | 3 |

### Material specifications

| | |
|---|---|
| Flammability rating according to UL 94 | HB |
| Seal material | NBR |
| Material of grip body | TPU, hardly inflammable, self-extinguishing |
| Contact material | CuSn |
| Contact surface material | Ni/Au |
| Contact carrier material | TPU GF |
| Material for screw connection | Zinc die-cast, nickel-plated |

### Electrical properties

| | |
|---|---|
| Insulation resistance | ≥ 100 MΩ |
| Nominal voltage $U_N$ | 24 V DC |
| Nominal current $I_N$ | 4 A |

### Mechanical properties

Mechanical data

| | |
|---|---|
| Insertion/withdrawal cycles | ≥ 100 |

### Signaling

| | |
|---|---|
| Status display | 2 LEDs |
| Status display present | Yes |

### Connection data

Conductor connection

| | |
|---|---|
| Tightening torque | 0.2 Nm (M8 connectors) |

### Connector

Connection 1

| | |
|---|---|
| Type | Plug angled M8 |

chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

| | |
|---|---|
| Number of positions | 3 |
| Coding type | A |


Connection 2

| | |
|---|---|
| Type | Socket angled M8 |
| Number of positions | 3 |
| Coding type | A |

## Cable/line

| | |
|---|---|
| Cable length | 0.6 m |

PUR halogen-free black [PUR]

| | |
|---|---|
| Dimensional drawing |  |
| Cable weight | 18 kg/km |
| UL AWM Style | 20549 / 10493 (80°C/300 V) |
| Number of positions | 3 |
| Shielded | no |
| Cable type | PUR halogen-free black [PUR] |
| Conductor structure signal line | 32x 0.10 mm |
| AWG signal line | 24 |
| Conductor cross section | 3x 0.25 mm² (Signal line) |
| Wire diameter incl. insulation | 1.17 mm ±0.02 mm |
| External cable diameter | 3.60 mm ±0.15 mm |
| Outer sheath, material | PUR |
| External sheath, color | black-gray RAL 7021 |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | PP |
| Single wire, color | brown, blue, black |
| Thickness, insulation | ≥ 0.21 mm (Core insulation) |
| Thickness, outer sheath | approx. 0.50 mm |
| Overall twist | 3 wires, twisted |
| Length of twist, overall twist | 40 mm |
| Max. conductor resistance | ≤ 78 Ω/km (at 20 °C) |
| Insulation resistance | ≥ 100 GΩ*km (at 20 °C) |
| Nominal voltage, cable | ≤ 300 V |
| Test voltage | ≥ 3000 V |
| Smallest bending radius, fixed installation | 18 mm |
| Smallest bending radius, movable installation | 36 mm |

chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

| | |
|---|---|
| Dynamic load capacity (bending) | Max. bending cycles: 10000000, Bending radius: 44 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s² |
| Halogen-free | in accordance with DIN VDE 0472 part 815 |
| Flame resistance | in accordance with UL 758/1581 FT2 |
| | DIN EN 60332-2-2 (20 s) |
| Resistance to oil | in accordance with DIN EN 60811-2-1 |
| Other resistance | hydrolysis and microbe resistant |
| | Highly resistant to acids, alkaline solutions and solvents |
| | Resistant to salt water |
| | partly UV-resistant (in accordance with DIN EN ISO 4892-2-A) |
| Special properties | Flexible cable conduit capable |
| | Silicone-free |
| | Free of substances which would hinder coating with paint or varnish |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -25 °C ... 80 °C (Cable, flexible installation) |

## Environmental and real-life conditions

### Ambient conditions

| | |
|---|---|
| Degree of protection | IP65 |
| | IP67 |
| | IP68 |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
| | -40 °C ... 80 °C (cable, fixed installation) |
| | -5 °C ... 80 °C (Cable, flexible installation) |

## Standards and regulations

| | |
|---|---|
| Standard designation | M8 connector |
| Standards/specifications | IEC 61076-2-104 |

chanhvinh.com


# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113


## Drawings

Dimensional drawing




Socket M8 x 1, angled, with LED

Schematic diagram




Pin assignment M8 plug, 3-pos., view male side


chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable


1682113

https://www.phoenixcontact.com/gb/products/1682113

Circuit diagram




Dimensional drawing




M8 x 1 male plug, angled version


chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113


https://www.phoenixcontact.com/gb/products/1682113

Schematic diagram



Layout of connector pin assignments

Schematic diagram




Pin assignment M8 socket, 3-pos., view female side


chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

Schematic diagram



Layout of connector pin assignments

chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1682113

**UL Listed**
Approval ID: FILE E 221474

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 24 V | 4 A | - | - |

**cUL Listed**
Approval ID: FILE E 221474

| | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|---|---|---|---|---|
| | 24 V | 4 A | - | - |

**EAC-RoHS**
Approval ID: RU D-DE.HB35.B.00387

**cULus Listed**

chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC001855 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 26121600 |

chanhvinh.com

# SAC-3P-M 8MR/0,6-PUR/M 8FR-2L - Sensor/actuator cable

1682113

https://www.phoenixcontact.com/gb/products/1682113

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk