chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: A, with 2 LEDs, cable length: 1.5 m

Your advantages

- Easy and safe: 100% electrically tested plug-in components
- Convenient: increased machine availability thanks to quick and easy diagnostics

Commercial Data

Item number	1694185
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF1CBA
Product Key	BF1CBA
Catalog Page	Page 188 (C-2-2019)
GTIN	4017918177386
Weight per Piece (including packing)	43.9 g
Weight per Piece (excluding packing)	43 g
Customs tariff number	85444290
Country of origin	PL

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Technical Data

Product properties

Product type	Sensor/actuator cable
Number of positions	3
Application	Standard
No. of cable outlets	1
Coding	A - standard

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Color Handle area	transparent
Flammability rating according to UL 94	HB
Sealing material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Cable gland material	Zinc die-cast, nickel-plated

Electrical properties

Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	24 V DC
Nominal current I_N	4 A
Protective circuit	unwired

Connection data

Conductor connection

Tightening torque	0.4 NmM12 connector

Connector

Insertion/withdrawal cycles	≥ 100

Connection 1

Head design	free cable end

Head 2

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	A

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Status indicator head	2 LEDs

LED signaling

Status display	2 LEDs
Status display present	yes

Cable / line

Cable length	1.5 m
Cable weight	23 kg/km
UL AWM Style	20549
Number of positions	3
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	3x 0.34 mm² (Signal line)
Wire diameter incl. insulation	1.27 mm ±0.02 mm (Signal line)
External cable diameter	3.85 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	brown, blue, black
Thickness, insulation	≥ 0.21 mm (Core insulation)
	approx. 0.5 mm (Outer cable sheath)
Overall twist	3 wires, twisted
Max. conductor resistance	max. 58 Ω/km (at 20 °C)
Insulation resistance	≥ 100 GΩ*km (at 20 °C)
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 3000 V
Smallest bending radius, fixed installation	19 mm
Smallest bending radius, movable installation	38 mm
Max. bending cycles	10000000
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with UL 758/1581 FT2
	DIN EN 60332-2-2 (20 s)
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Highly resistant to acids, alkaline solutions and solvents
	hydrolysis and microbe resistant
	partly UV-resistant in accordance with DIN EN ISO 4892-2-A
Special properties	Flexible cable conduit capable
	Silicone-free
	Free of substances which would hinder coating with paint or varnish

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-25 °C ... 80 °C (Cable, flexible installation)

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations

M12

Standards/specifications	IEC 61076-2-101

chanhvinh.com


Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185


Drawings

Dimensional drawing



Socket M12 x 1, straight, with LED

Schematic diagram



Pin assignment M12 socket, 3-pos., A-coded, view female side


chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Circuit diagram



Contact assignment of M12 sockets with LED

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Approvals

UL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	24 V	4 A	-	-

cUL Listed
Approval ID: FILE E 221474

	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	24 V	4 A	-	-

EAC
Approval ID: RU D-DE.HB35.B.00387

cULus Listed

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Classifications

ECLASS

ECLASS-9.0	27060311
ECLASS-10.0.1	27060311
ECLASS-11.0	27060311

ETIM

ETIM 8.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Accessories

Insert label

Insert label - PABA WH/23 - 1013779

https://www.phoenixcontact.com/gb/products/1013779




Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

Insert label

Insert label - PABA YE/23 - 1013782

https://www.phoenixcontact.com/gb/products/1013782



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Marker pen

Marker pen - B-STIFT - 1051993

https://www.phoenixcontact.com/gb/products/1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

Diagonal cutter

Diagonal cutter - CUTFOX-S VDE - 1212207

https://www.phoenixcontact.com/gb/products/1212207



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Stripping tool

Stripping tool - WIREFOX SAC-1 - 1212757

https://www.phoenixcontact.com/gb/products/1212757



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

Stripping tool

Stripping tool - WIREFOX SAC - 1212623

https://www.phoenixcontact.com/gb/products/1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Stripping tool

Stripping tool - WIREFOX 10 - 1212150

https://www.phoenixcontact.com/gb/products/1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm^2, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm^2 stranded/1.5 mm^2 solid, replaceable stripping blade

Protective hose adapter

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884

https://www.phoenixcontact.com/gb/products/1422884



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Protective hose

Protective hose - WP-PA HF 13,0 BK - 3240681

https://www.phoenixcontact.com/gb/products/3240681



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

Protective hose

Protective hose - WP-PA HF-HB 13,0 BK - 3240839

https://www.phoenixcontact.com/gb/products/3240839



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Screw plug

Screw plug - PROT-M12 MS-PA-CHAIN - 1430899

https://www.phoenixcontact.com/gb/products/1430899

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



Locking clip

Locking clip - SAC-M12-EXCLIP-F - 1558991

https://www.phoenixcontact.com/gb/products/1558991



Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Torque screwdriver

Torque screwdriver - TSD 04 SAC - 1208429

https://www.phoenixcontact.com/gb/products/1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

Torque screwdriver

Torque screwdriver - TSD-M 1,2NM - 1212224

https://www.phoenixcontact.com/gb/products/1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

chanhvinh.com

Sensor/actuator cable - SAC-3P- 1,5-PUR/M12FS-2L

1694185

https://www.phoenixcontact.com/gb/products/1694185

Adapter insert

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600

https://www.phoenixcontact.com/gb/products/1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

Tool

Tool - SAC BIT M12-D15 - 1208432

https://www.phoenixcontact.com/gb/products/1208432



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

Phoenix Contact 2022 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk