chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protection plug with integrated multi-stage status indicator on the module for three signal wires. For HF applications. Nominal voltage: 5 V DC

Your advantages

- Predictive monitoring with 3-stage LED display
- Integration of the status message into the system controller via group remote signaling
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs
- Maximum ease of maintenance, thanks to the 2-piece design
- Maximum protection for MCR applications with high discharge capacity

Commercial data

Item number	2800783
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL2151
Product key	CL2151
Catalog page	Page 313 (NTK-2014)
GTIN	4046356645263
Weight per piece (including packing)	48.5 g
Weight per piece (excluding packing)	44 g
Customs tariff number	85363010
Country of origin	DE

chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

Technical data

Notes

General

Note	Remote signaling as well as the power supply are established by inserting the connector into the base element.

Product properties

Product type	Replacement plug
Product family	PLUGTRAB IQ
Type	Male
Wire pairs per module	2


Electrical properties

Nominal voltage U_N	5 V DC

Connection data

Connection method	pluggable

Dimensions

Dimensional drawing	
Width	17.7 mm
Height	45 mm
Depth	53.4 mm
Horizontal pitch	1 Div.
Complete module width	17.7 mm
Complete module height	91.1 mm
Complete module depth	77.5 mm

Material specifications

Color	black (RAL 9005)
	black (RAL 9005)
Flammability rating according to UL 94	V-0
Housing material	PA 6.6

Protective circuit

Direction of action	Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground
Maximum continuous voltage U_C	6 V DC
	4 V AC

chanhvinh.com

Rated current	600 mA (40 °C)
Surge protection fault message	Optical, multi-stage

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 %

Standards and regulations

Air clearances and creepage distances

Standards/regulations	IEC 60664-1

Mounting

Mounting type	on base element

chanhvinh.com


PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

Drawings

Dimensional drawing



chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171503

ETIM

ETIM 9.0	EC001466

UNSPSC

UNSPSC 21.0	39121600

chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2479045a-33cc-4d6b-a26d-843fa9e726aa

chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

Accessories

ZBF 5:UNBEDRUCKT - Zack Marker strip, flat

0808642

https://www.phoenixcontact.com/gb/products/0808642



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.1 x 5.2 mm, Number of individual labels: 10

ZBF 5/WH-100:UNBEDRUCKT - Zack Marker strip, flat

0808668

https://www.phoenixcontact.com/gb/products/0808668



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 5 mm, lettering field size: 5.15 x 5.15 mm, Number of individual labels: 1000

chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

ZBN 18:UNBEDRUCKT - Zack marker strip

2809128

https://www.phoenixcontact.com/gb/products/2809128



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

ZBN 18 CUS - Zack marker strip

0825059

https://www.phoenixcontact.com/gb/products/0825059



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 18 mm, lettering field size: 18 x 5 mm, Number of individual labels: 5

chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

SSA 3-6 - Shield connection

2839295

https://www.phoenixcontact.com/gb/products/2839295



Shield fast connection for 3 ... 6 mm cable diameter. Potential connecting cable: 200 mm, 1 mm^2, color: black

SSA 5-10 - Shield connection

2839512

https://www.phoenixcontact.com/gb/products/2839512



Shield fast connection for 5 ... 10 mm cable diameter. Potential connecting cable: 200 mm, 1 mm^2, color: black

chanhvinh.com

PT-IQ-3-PB-P - Surge protection plug

2800783

https://www.phoenixcontact.com/gb/products/2800783

X-PEN 0,35 - Marker pen

0811228

https://www.phoenixcontact.com/gb/products/0811228



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk