chanhvinh.com

ST-REL2-KG120/1 - Relay connectors

2823654

https://www.phoenixcontact.com/gb/products/2823654

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Relay connector, fitted with miniature switching relay, contacts (AgNi): Medium to large loads, 1 N/O contact, 120 V AC/DC input voltage, with light indicator, can be plugged into basic terminal blocks

Commercial data

Item number	2823654
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	DK61B2
Product key	DK61B2
Catalog page	Page 87 (IF-2005)
GTIN	4017918077495
Weight per piece (including packing)	35.52 g
Weight per piece (excluding packing)	33.48 g
Customs tariff number	85364900
Country of origin	DE

chanhvinh.com

ST-REL2-KG120/1 - Relay connectors

2823654

https://www.phoenixcontact.com/gb/products/2823654

Technical data

Product properties

Product type	Relay Module
Operating mode	100% operating factor
Mechanical service life	approx. 2x 10^7 cycles

Data management status

Date of last data management	19.03.2025

Electrical properties

Maximum power dissipation for nominal condition	0.6 W
Test voltage (Winding/contact)	2.5 kV AC (50 Hz, 1 min., winding/contact)

Input data

Coil side

Nominal input voltage U_N	120 V AC/DC
Input voltage range	96 V AC/DC ... 127.2 V AC/DC (20 °C)
Drive and function	monostable
Drive (polarity)	polarized
Typical input current at U_N	5 mA
Typical response time	7 ms (with DC)
Typical release time	11 ms (with DC)
Protective circuit	Bridge rectifier, varistor
Operating voltage display	yes

Output data

Switching

Contact switching type	1 N/O contact
Type of switch contact	Single contact
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Limiting continuous current	6 A
Maximum inrush current	8 A
Interrupting rating (ohmic load) max.	95 W (at 24 V DC)
	50 W (at 48 V DC)
	45 W (at 60 V DC)
	45 W (at 110 V DC)
	75 W (at 220 V DC)
	1500 VA (for 250 V AC)

Dimensions

Width	14.6 mm

chanhvinh.com

ST-REL2-KG120/1 - Relay connectors

2823654

https://www.phoenixcontact.com/gb/products/2823654

Height	33 mm
Depth	66.5 mm

Material specifications

Color	green (RAL 6021)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC
	IEC 60255/DIN VDE 0435 (in relevant parts)
	DIN EN 50178/VDE 0160 (in relevant parts)
	EN 60730/DIN VDE 0631
	DIN VDE 0160 (in relevant parts)

Mounting

Mounting type	Plug-in mounting

chanhvinh.com


ST-REL2-KG120/1 - Relay connectors

2823654

https://www.phoenixcontact.com/gb/products/2823654

Drawings

Circuit diagram



chanhvinh.com

ST-REL2-KG120/1 - Relay connectors

2823654

https://www.phoenixcontact.com/gb/products/2823654

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/2823654

EAC
Approval ID: RU*C-DE.*08.B.00010

chanhvinh.com

ST-REL2-KG120/1 - Relay connectors

2823654

https://www.phoenixcontact.com/gb/products/2823654

Classifications

ECLASS

ECLASS-13.0	27371601

ETIM

ETIM 9.0	EC001437

UNSPSC

UNSPSC 21.0	39122300

chanhvinh.com

ST-REL2-KG120/1 - Relay connectors

2823654

https://www.phoenixcontact.com/gb/products/2823654

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Hexahydromethylphthalic anhydride(CAS: n/a)
	Lead(CAS: 7439-92-1)
SCIP	797b814e-a241-4f3b-924b-3a0ebe8b68dc

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk