chanhvinh.com

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/gb/products/2832250

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Patch cable, CAT5, assembled, 0.3 m

Commercial data

Item number	2832250
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	ABNABG
Product key	ABNABG
Catalog page	Page 721 (C-2-2019)
GTIN	4046356043984
Weight per piece (including packing)	22.63 g
Weight per piece (excluding packing)	22.5 g
Customs tariff number	85444210
Country of origin	DE

chanhvinh.com

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/gb/products/2832250

Technical data

Product properties

Product type	Data cable preassembled
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45

Electrical properties

Contact resistance	≤ 0.003 Ω (IEC 60603-7)
Nominal voltage U_N	150 V_{rms}
Nominal current I_N	1.5 A
Transmission speed	1 Gbps

Mechanical properties

Mechanical data

Insertion force per signal contact	30.00 N
Extraction force per signal contact	50 N

Material specifications

Flammability rating according to UL 94	V0
Outer sheath, material	LSFROH

Dimensions

Width	12.6 mm
Height	6.6 mm
Length	40.05 mm

External dimensions

External diameter max.	6 mm

Connector

Connection 1

Type	Plug straight RJ45
Shielded	yes
Insertion/withdrawal cycles	≥ 750
Degree of protection	IP20

Connection 2

Type	Plug straight RJ45

Cable/line

Cable length	0.30 m
Cable structure	2x2xAWG26/7, SF/UTP

chanhvinh.com

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/gb/products/2832250

External cable diameter	5.80 mm
Outer sheath, material	LSFROH
Single wire, number of litz wires	8
Single wire, material	Cu litz wire
Single wire, cross section	0.14 mm²
Shielding	SF/UTP
Smallest bending radius, fixed installation	50 mm (under load)
Smallest bending radius, movable installation	25 mm (without load)
Halogen-free	according to IEC 60754-1
Concentration of fumes	in accordance with IEC 61034
Flame resistance	according to IEC 60332-3C

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-10 °C ... 60 °C

Standards and regulations

Flame resistance	according to IEC 60332-3C
Concentration of fumes	in accordance with IEC 61034

chanhvinh.com

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/gb/products/2832250

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/2832250

EAC
Approval ID: 19060508

chanhvinh.com

chanhvinh.com

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/gb/products/2832250

Classifications

ECLASS

ECLASS-11.0	27060308
ECLASS-12.0	27060308
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/gb/products/2832250

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk