
chanhvinh.com

PT 4X1+F-BE - Surge protection base-element

2839376

https://www.phoenixcontact.com/pc/products/2839376

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Base element for protective plug PT with protective circuit for 4 signal wires, with gas-filled surge arrester between the connections 3-4 (GND) and 9-10, for mounting on NS 35/7.5 and NS 35/15, housing width: 17.5 mm

Your advantages

- Maximum ease of maintenance, thanks to the 2-piece design
- Easy selection for all possible demands in MCR applications with a complete product portfolio
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs

Commercial data

Item number	2839376
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	CL2111
Catalog page	Page 135 (C-4-2019)
GTIN	4017918182809
Weight per piece (including packing)	57.89 g
Weight per piece (excluding packing)	51.529 g
Customs tariff number	85363010
Country of origin	DE

chanhvinh.com

PT 4X1+F-BE - Surge protection base-element

2839376

https://www.phoenixcontact.com/pc/products/2839376

Technical data

Notes

Notes on operation	In the base elements PT...+F-BE, the connections 9/10 (GND) are linked to the mounting foot via a gas-filled surge arrester.

Product properties

Product type	Base element
Product family	PLUGTRAB PT
Type	Base element, DIN rail mounting
Number of positions	4
Surge protection fault message	none

Insulation characteristics

Overvoltage category	III
Pollution degree	2


Electrical properties

Nominal voltage U_N	48 V AC

Connection data

Connection method	Screw connection
Screw thread	M3
Tightening torque	0.5 Nm
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section rigid	0.2 mm² ... 4 mm²
Conductor cross section AWG	24 ... 12

Dimensions

Dimensional drawing	
Width	17.7 mm
Height	90 mm
Depth	51.5 mm (incl. DIN rail 7.5 mm)
Horizontal pitch	1 Div.

Material specifications

Color	black (RAL 9005)
	Copper color
Flammability rating according to UL 94	V-0
Housing material	PA 6.6

chanhvinh.com

PT 4X1+F-BE - Surge protection base-element

2839376

https://www.phoenixcontact.com/pc/products/2839376

Mechanical properties

Mechanical data

Open side panel	No

Protective circuit

Direction of action	Signal Ground/Shield-Earth Ground
Maximum continuous voltage U_C	77 V DC
	55 V AC
Rated current	300 mA (45 °C)
Resistance per path	4.7 Ω 10 %
Surge protection fault message	none
Max. required back-up fuse	315 mA (T)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m (amsl)

Standards and regulations

Standards/specifications	IEC 61643-21
Note	2000 + corrigendum 2001 + A1:2008, modified + A2:2012
Standards/specifications	EN 61643-21
Note	2001 + A1:2009 + A2:2013

Mounting

Mounting type	DIN rail: 35 mm

chanhvinh.com


PT 4X1+F-BE - Surge protection base-element

2839376


https://www.phoenixcontact.com/pc/products/2839376

Drawings

Dimensional drawing



Diagram




chanhvinh.com

PT 4X1+F-BE - Surge protection base-element

2839376

https://www.phoenixcontact.com/pc/products/2839376

Circuit diagram



chanhvinh.com

PT 4X1+F-BE - Surge protection base-element

2839376

https://www.phoenixcontact.com/pc/products/2839376

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/2839376

EAC
Approval ID: EAC-Zulassung

DNV GL
Approval ID: TAE00001N6

EAC
Approval ID: RU C-DE.*09.B.00169

UL Listed
Approval ID: FILE E 138168

cUL Listed
Approval ID: FILE E 333250

UL Listed
Approval ID: FILE E 333250

chanhvinh.com

PT 4X1+F-BE - Surge protection base-element

2839376

https://www.phoenixcontact.com/pc/products/2839376

Classifications

ECLASS

ECLASS-13.0	27171592

ETIM

ETIM 9.0	EC002497

UNSPSC

UNSPSC 21.0	39121600

chanhvinh.com

PT 4X1+F-BE - Surge protection base-element

2839376

https://www.phoenixcontact.com/pc/products/2839376

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com