chanhvinh.com

# PLC-BPT- 24DC/21-21 - Relay base

2900283

https://www.phoenixcontact.com/pc/products/2900283

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



14 mm PLC basic terminal block with Push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 2 changeover contacts, input voltage 24 V DC

## Commercial data

| | |
|---|---|
| Item number | 2900283 |
| Packing unit | 10 pc |
| Minimum order quantity | 1 pc |
| Product key | DK62B2 |
| GTIN | 4046356510165 |
| Weight per piece (including packing) | 58 g |
| Weight per piece (excluding packing) | 45.8 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

chanhvinh.com

# PLC-BPT- 24DC/21-21 - Relay base

2900283

https://www.phoenixcontact.com/pc/products/2900283

## Technical data

### Notes

Utilization restriction

| | |
|---|---|
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |

### Product properties

| | |
|---|---|
| Product type | Relay socket |
| Product family | PLC-INTERFACE |
| Application | Universal |
| Operating mode | 100% operating factor |

### Input data

| | |
|---|---|
| Nominal input voltage $U_N$ | 24 V DC |
| | The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from the nominal input voltage of the base with integrated upstream circuit |
| Protective circuit | Freewheeling diode |
| Nominal input voltage $U_N$ | 24 V DC |
| | The nominal voltage of the plug-on electromechanical relay or solid-state relay (see necessary accessories) deviates from the nominal input voltage of the base with integrated upstream circuit |

### Connection data

| | |
|---|---|
| Connection method | Push-in connection |
| Stripping length | 10 mm |
| Conductor cross section rigid | 0.14 mm² ... 2.5 mm² |
| Conductor cross section flexible | 0.14 mm² ... 2.5 mm² |
| | 0.2 mm² ... 2.5 mm² (Single ferrule) |
| | 2x 0.5 mm² ... 1 mm² (TWIN ferrule) |
| Conductor cross section AWG | 26 ... 14 |

### Signaling

| | |
|---|---|
| Status display | LED |

### Dimensions

| | |
|---|---|
| Width | 14 mm |
| Height | 80 mm |
| Depth | 94 mm |

### Material specifications

| | |
|---|---|
| Color | gray (RAL 7042) |
| Flammability rating according to UL 94 | V0 (Housing) |

chanhvinh.com

# PLC-BPT- 24DC/21-21 - Relay base

2900283

https://www.phoenixcontact.com/pc/products/2900283

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ... 60 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

## Approvals

CE

| | |
|---|---|
| Certificate | CE-compliant |

UKCA

| | |
|---|---|
| Certificate | UKCA-compliant |

Shipbuilding approval

| | |
|---|---|
| Certificate | TAE0000196 |

Corrosive gas test

| | |
|---|---|
| Identification | ISA-S71.04. G3 Harsh Group |
| | EN 60068-2-60 |
| Temperature | D |
| Humidity | A |
| Vibration | B/C |
| EMC | B |
| Enclosure | Required protection according to the Rules shall be provided upon installation on board |

## EMC data

| | |
|---|---|
| Electromagnetic compatibility | Conformance with EMC directive |
| Low Voltage Directive | Conformance with Low Voltage Directive |

## Mounting

| | |
|---|---|
| Mounting type | DIN rail mounting |
| Assembly note | in rows with zero spacing |
| Mounting position | any |

chanhvinh.com

# PLC-BPT- 24DC/21-21 - Relay base

2900283

https://www.phoenixcontact.com/pc/products/2900283

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/2900283

**cUL Recognized**
Approval ID: E238705

**UL Recognized**
Approval ID: E238705

**EAC**
Approval ID: RU D-DE.B*00573/18

**DNV GL**
Approval ID: TAE0000196

**cULus Recognized**

chanhvinh.com

# PLC-BPT- 24DC/21-21 - Relay base

2900283

https://www.phoenixcontact.com/pc/products/2900283

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27371603 |
| ECLASS-12.0 | 27371603 |
| ECLASS-13.0 | 27371603 |

### ETIM

| | |
|---|---|
| ETIM 9.0 | EC001456 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39122300 |

chanhvinh.com

# PLC-BPT- 24DC/21-21 - Relay base

2900283

https://www.phoenixcontact.com/pc/products/2900283

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(a), 7(c)-I |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | Hexahydromethylphthalic anhydride(CAS: n/a) |
| | Lead(CAS: 7439-92-1) |
| SCIP | 2f15e92b-cdab-4104-b987-d5505833268e |

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com