chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Preassembled relay module with Push-in connection, consisting of: relay base, power contact relay, plug-in display/interference suppression module, and retaining bracket. Contact switching type: 2 changeover contacts. Input voltage: 24 V AC

Product description

The pluggable electromechanical and solid-state relays in the RIFLINE complete product range and the base are recognized and approved in accordance with UL 508. The relevant approvals can be called up at the individual components in question.

Commercial data

Item number	2903333
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	DK6529
Catalog page	Page 327 (C-5-2019)
GTIN	4046356732284
Weight per piece (including packing)	69.03 g
Weight per piece (excluding packing)	67.8 g
Customs tariff number	85364110
Country of origin	CN

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Set consists of

RIF-1-BPT/2X21 - Relay base

2900931

https://www.phoenixcontact.com/pc/products/2900931



Relay base RIF-1..., for miniature power relay with 1 or 2 changeover contacts or solid-state relays of the same design, Push-in connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

REL-MR- 24AC/21-21 - Single relay

2961435

https://www.phoenixcontact.com/pc/products/2961435



Plug-in miniature power relay, with power contact, 2 changeover contacts, input voltage 24 V AC

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

RIF-LV-12-24 UC - Plug-in module

2900942

https://www.phoenixcontact.com/pc/products/2900942



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 12 V AC ... 24 V AC / DC ±20 %

RIF-RH-1 - Retaining bracket

2900953

https://www.phoenixcontact.com/pc/products/2900953



Relay retaining bracket, with ejector function and holder for marking material, suitable for RIF-1 relay base, for 16 mm tall miniature power relay and solid-state relay

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Technical data

Notes

Notes on operation	FBS 2-6... plug-in bridge for the input side (A2) and FBS-2-8... plug-in bridge for the output side (11/21)

Product properties

Product type	Relay Module
Product family	RIFLINE complete
Application	Universal
Operating mode	100% operating factor
Mechanical service life	approx. 10^7 cycles

Insulation characteristics

Insulation	Safe isolation between input and output
	Basic insulation between the changeover contacts
Overvoltage category	III
Pollution degree	2

Data management status

Date of last data management	13.01.2025

Electrical properties

Service life electrical	see diagram
Maximum power dissipation for nominal condition	0.79 W
Test voltage (Winding/contact)	4 kV_{rms} (50 Hz, 1 min., winding/contact)
Test voltage (Changeover contact/changeover contact)	2.5 kV_{rms} (50 Hz, 1 min., changeover contact/changeover contact)
Rated surge voltage	6 kV (Input/output)
	4 kV (between the changeover contacts)

Input data

Coil side

Nominal input voltage U_N	24 V AC
Input voltage range	19.2 V AC ... 27.6 V AC (20 °C)
Input voltage range in reference to U_N	see diagram
Mains frequency	50/60 Hz
Drive and function	monostable
Drive (polarity)	polarized
Typical input current at U_N	33 mA
Typical response time	3 ms ... 12 ms
Typical release time range	3 ms ... 20 ms
Coil voltage	24 V AC
Protective circuit	Varistor

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Operating voltage display	Yellow LED

Output data

Switching

Contact switching type	2 changeover contacts
Type of switch contact	Single contact
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V (10 mA)
Limiting continuous current	8 A (see diagram)
Maximum inrush current	12 A (20 ms, N/O contacts)
Min. switching current	10 mA (5 V)
Interrupting rating (ohmic load) max.	192 W (at 24 V DC)
	96 W (at 48 V DC)
	60 W (at 60 V DC)
	44 W (at 110 V DC)
	57 W (at 220 V DC)
	2000 VA (for 250 V AC)
Utilization category CB Scheme (IEC 60947-5-1)	AC15, 1.5 A/240 V (N/O contact)
	AC15, 2 A/250 V (N/C contact)
	DC13, 2 A/24 V (N/C contact)
	DC13, 0.2 A/250 V (N/O contact)

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm² ... 1.5 mm²
Conductor cross section flexible	0.14 mm² ... 1.5 mm²
	0.14 mm² ... 1.5 mm² (Ferrule with plastic sleeve)
	0.14 mm² ... 1 mm² (Ferrule with plastic sleeve, two conductors on double terminal block)
Conductor cross section AWG	26 ... 16 (solid)
	26 ... 16 (flexible)

Dimensions

Drill hole

Diameter	3.2 mm
Width	16 mm
Height	96 mm
Depth	75 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V2 (Housing)

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Environmental and real-life conditions

Ambient conditions

Degree of protection (Relay base)	IP20 (Relay base)
Degree of protection (Relay)	RT III (Relay)
Ambient temperature (operation)	-40 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Approvals

Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

Standards and regulations

Standards/regulations	IEC 60947-5-1

Mounting

Mounting type	DIN rail mounting
Assembly note	in rows with zero spacing
Mounting position	any

chanhvinh.com


RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Drawings

Diagram



Permissible humidity for operation and storage.
The maximum permissible ambient temperature as specified in the data sheet must be observed.

Area A: Ice buildup at ambient temperatures ≤ 0°C must be prevented
Area B: Condensation at ambient temperatures > 0°C must be prevented

On 30 full days that are naturally distributed across an entire year, a humidity level of 95% is permissible at an ambient temperature ≤ 25°C.


chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Diagram



1 DC coils

2 AC coils

Operating voltage range


chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Diagram



1 AC, ohmic load
2 DC, ohmic load, contacts in series
3 DC, ohmic load
4 DC, L/R = 40 ms

Interrupting rating


chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333


Diagram



Service life reduction factor

chanhvinh.com

Diagram



1 250 V AC, ohmic load (DC coils)

2 250 V AC, ohmic load (AC coils)

Electrical service life


chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Diagram



Contact derating


chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Circuit diagram



AC coils

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/2903333

DNV GL
Approval ID: TAA000018V

DNV GL
Approval ID: TAA000018V

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Classifications

ECLASS

ECLASS-11.0	27371601
ECLASS-12.0	27371601
ECLASS-13.0	27371601

ETIM

ETIM 9.0	EC001437

UNSPSC

UNSPSC 21.0	39122300

chanhvinh.com

RIF-1-RPT-LV-24AC/2X21 - Relay module

2903333

https://www.phoenixcontact.com/pc/products/2903333

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	c06de5b9-42aa-493c-8110-291a393d5e4b

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com