chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



UL Recognized type 2 SPD and IEC type 2 surge protection plug with a varistor and thermal disconnect for use with VAL-US base elements, mechanical and visual fault warning

Product description

Surge protective device replacement plug

Your advantages

- Thermal disconnect device for each individual plug
- Optical, mechanical status indication for the individual arresters
- Pluggable
- Mechanical coding of all slots
- Consists of base element and plug

Commercial data

Item number	2910333
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL1321
Product key	CL1321
Catalog page	Page 90 (C-4-2019)
GTIN	4055626444468
Weight per piece (including packing)	35.1 g
Weight per piece (excluding packing)	29 g
Customs tariff number	85363030
Country of origin	DE

chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Technical data

Notes

General	Used in:

Product properties

Product type	Replacement plug
Product family	VALVETRAB MS
IEC test classification	II
	T2
EN type	T2
IEC power supply system	DC
Type	Male
Number of positions	1
Surge protection fault message	optical

Insulation characteristics

Overvoltage category	III
Pollution degree	2


Electrical properties

Nominal frequency f_N	50 Hz (60 Hz)

Connection data

Connection method	VALVETRAB plug-in system

Dimensions

Dimensional drawing	
Width	17.5 mm
Height	52.4 mm
Depth	55.3 mm
Horizontal pitch	1 Div.

Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PA 6.6/PBT
Material group	I

chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Housing material	PA 6.6
	PBT

Protective circuit

Mode of protection	L-N
	L-PEN
	N-PE
Direction of action	1L-N/PE
Nominal voltage U_N	60 V DC ±10 %
	-48 V DC ±10 % (RRH)
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	100 V DC
Residual current I_{PE}	≤ 450 µA
Standby power consumption P_C	≤ 35.00 mVA
Nominal discharge current I_n (8/20) µs	15 kA
Maximum discharge current I_{max} (8/20) µs	40 kA
Short-circuit current rating I_{SCCR}	25 kA
Voltage protection level U_p	≤ 0.55 kV
Residual voltage U_{res}	≤ 0.55 kV (at I_n)
	≤ 0.425 kV (at 10 kA)
	≤ 0.325 kV (at 5 kA)
	≤ 0.275 kV (at 3 kA)
TOV behavior at U_T	100 V AC (5 s / withstand mode)
Max. backup fuse with branch wiring	100 A (gG)

Additional technical data

Maximum discharge current I_{max} (8/20) µs	40 kA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl)
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation)	5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

Approvals

UL specifications

Maximum continuous operating voltage MCOV	100 V DC
UL type	type 4
Nominal discharge current I_n	20 kA
Maximum Surge Current per Phase	40 kA

chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Mode of protection	L-N
	L-G
	N-G
Nominal voltage	60 V DC
Power distribution system	Single phase
Measured limiting voltage MLV	720 V
SPD Type	4CA

Standards and regulations

Air clearances and creepage distances

Standards/regulations	EN 60664-1 / EN 61643-11
Standards/specifications	IEC 61643-11
Note	2011
Standards/specifications	EN 61643-11
Note	2012

Mounting

Mounting type	on base element

chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333


https://www.phoenixcontact.com/gb/products/2910333

Drawings

Circuit diagram



Dimensional drawing



chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/2910333

cUL Recognized
Approval ID: FILE E 330181

UL Recognized
Approval ID: FILE E 330181

cULus Recognized

chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Classifications

ECLASS

ECLASS-11.0	27130890
ECLASS-13.0	27171292

ETIM

ETIM 8.0	EC002496

UNSPSC

UNSPSC 21.0	39121600

chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

chanhvinh.com

VAL-US-48/40-P - Type 2 surge protection plug

2910333

https://www.phoenixcontact.com/gb/products/2910333

Accessories

VAL-US-48/40/1+0-FM - Type 2 surge protection device

2910343

https://www.phoenixcontact.com/gb/products/2910343



Surge protective device, single channel with remote indicator contact for 48 V DC.

VAL-US-48/40/1+1V-FM - Type 2 surge protection device

2910344

https://www.phoenixcontact.com/gb/products/2910344



Surge protective device, two channels with remote indicator contact for 48 V DC, 2-wire plus ground

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk