chanhvinh.com

EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216

https://www.phoenixcontact.com/gb/products/2944216

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power solid-state relay, with LED and protective circuit in input and output circuits, input: 12 V DC, output: 5 - 36 V DC/max. 1 A

Commercial data

Item number	2944216
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CK61C1
Product key	CK61C1
Catalog page	Page 138 (IF-2011)
GTIN	4017918081515
Weight per piece (including packing)	38.35 g
Weight per piece (excluding packing)	38.35 g
Customs tariff number	85364190
Country of origin	DE

chanhvinh.com

EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216

https://www.phoenixcontact.com/gb/products/2944216

Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area

Product properties

Product type	Solid-state relay module
Application	Output function
Operating mode	100% operating factor

Data management status

Date of last data management	03.05.2024

Insulation characteristics

Insulation	Basic insulation

Insulation characteristics

Insulation	Basic insulation

Electrical properties

Test voltage (Input/output)	3.5 kV AC (Input/output)

Input data

Nominal input voltage U_N	12 V DC
Input voltage range in reference to U_N	0.9 ... 1.1
Input voltage range	10.8 V DC ... 13.2 V DC
Switching threshold "0" signal in reference to U_N	≤ 0.33
Switching threshold "1" signal in reference to U_N	≥ 0.9
Typical input current at U_N	4 mA
Typical response time	0.1 ms
Typical turn-off time	0.2 ms
Status display	Yellow LED
Protective circuit	Reverse polarity protection; Polarity protection diode
Transmission frequency	500 Hz

Output data

Contact switching type	1 N/O contact
Design of digital output	electronic
Output nominal voltage	24 V DC
Output voltage range	5 V DC ... 36 V DC
Limiting continuous current	1 A (see derating curve)
Surge current	2 A (t = 1 s)
Peak offstate voltage	45 V DC (Collector-emitter reverse voltage)

chanhvinh.com

EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216

https://www.phoenixcontact.com/gb/products/2944216

Voltage drop at max. limiting continuous current	≤ 1 V
Output circuit	2-conductor, floating
Protective circuit	Reverse polarity protection; Polarity protection diode

Connection data

Input side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm² ... 4 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 12

Output side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm² ... 4 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 12

Dimensions

Width	10 mm
Height	75 mm
Depth	102 mm

Material specifications

Color	green (RAL 6021)
Flammability rating according to UL 94	V0

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	IEC 60664
	EN 50178

Mounting

Mounting type	DIN rail mounting
Assembly note	in rows with zero spacing
Mounting position	any

chanhvinh.com


EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216


https://www.phoenixcontact.com/gb/products/2944216

Drawings

Diagram



Circuit diagram



chanhvinh.com

EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216

https://www.phoenixcontact.com/gb/products/2944216

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/2944216

EAC
Approval ID: TR_TS_D_00573_c

EAC
Approval ID: RU*C-DE.*08.B.00010

chanhvinh.com

EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216

https://www.phoenixcontact.com/gb/products/2944216

Classifications

ECLASS

ECLASS-11.0	27371604
ECLASS-12.0	27371604
ECLASS-13.0	27371604

ETIM

ETIM 9.0	EC001504

UNSPSC

UNSPSC 21.0	39122300

chanhvinh.com

EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216

https://www.phoenixcontact.com/gb/products/2944216

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(a)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Hexahydromethylphthalic anhydride(CAS: n/a)
	Lead(CAS: 7439-92-1)
SCIP	5d73672a-2966-4b56-83d6-d53e98736a1b

chanhvinh.com

EMG 10-OV- 12DC/24DC/1 - Solid-state relay module

2944216

https://www.phoenixcontact.com/gb/products/2944216

Accessories

EMG-SGKS 10 - Marking material

2947585

https://www.phoenixcontact.com/gb/products/2947585



Equipment marker, narrow

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk