
chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in miniature power relay, with power contact, 1 changeover contact, input voltage 12 V DC

Your advantages

- Safe isolation between coil and contact side
- High degree of protection up to RT III depending on type (wash-proof)
- Power contacts up to 6 A

Commercial data

Item number	2961150
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	08
Product key	DK6921
Catalog page	Page 284 (C-5-2019)
GTIN	4017918159566
Weight per piece (including packing)	6.62 g
Weight per piece (excluding packing)	5 g
Customs tariff number	85364900
Country of origin	CZ

chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Technical data

Product properties

Product type	Single relay
Operating mode	100% operating factor
Mechanical service life	2x 10^7 cycles

Insulation characteristics

Overvoltage category	III
Pollution degree	3

Data management status

Date of last data management	02.05.2024

Electrical properties

Maximum power dissipation for nominal condition	0.17 W
Test voltage (Winding/contact)	4 kV AC (50 Hz, 1 min., winding/contact)

Input data

Coil side

Nominal input voltage U_N	12 V DC
Input voltage range	7.2 V DC ... 33 V DC
Input voltage range in reference to U_N	see diagram
Drive and function	monostable
Drive (polarity)	non-polarized
Typical input current at U_N	14 mA
Typical response time	5 ms
Typical release time	2.5 ms
Coil resistance	848 Ω ±10 % (at 20 °C)

Output data

Switching

Contact switching type	1 changeover contact
Type of switch contact	Single contact
Contact material	AgSnO
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V (at 100 mA)
Limiting continuous current	6 A
Maximum inrush current	10 A (4 s)
Min. switching current	10 mA (at 12 V)
Interrupting rating (ohmic load) max.	140 W (at 24 V DC)
	20 W (at 48 V DC)
	18 W (at 60 V DC)

chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150


https://www.phoenixcontact.com/pc/products/2961150

	23 W (at 110 V DC)
	40 W (at 220 V DC)
	1500 VA (for 250 V AC)
Switching capacity	2 A (at 24 V, DC13)
	0.2 A (at 110 V, DC13)
	0.1 A (at 220 V, DC13)
	3 A (at 24 V, AC15)
	3 A (at 120 V, AC15)
	3 A (at 230 V, AC15)
Motor load according to UL 508	1/4 HP, 240 - 277 V AC (N/O contact)
	1/6 HP, 240 - 277 V AC (N/C contact)

Connection data

Connection method	Plug / solder connection

Dimensions

Dimensional drawing	
Width	5 mm
Height	28 mm
Depth	15 mm

Material specifications

Color	white (RAL 9010)

Environmental and real-life conditions

Ambient conditions

Degree of protection	RT III
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Approvals

Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

Standards and regulations

Standards/regulations	IEC 60664
	EN 50178
	EN 61810-1

chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Mounting

Assembly note	in rows with zero spacing
Mounting position	any

chanhvinh.com


REL-MR- 12DC/21 - Single relay

2961150


https://www.phoenixcontact.com/pc/products/2961150

Drawings

Dimensional drawing



Circuit diagram




chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Diagram



1 250 V AC, ohmic load

Electrical service life


chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150


https://www.phoenixcontact.com/pc/products/2961150

Diagram



Interrupting rating

Drilling plan/solder pad geometry



a = pitch division 1.25 mm and 1.27 mm


chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Diagram



Operating voltage range


chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Diagram



Permissible humidity for operation and storage.
The maximum permissible ambient temperature as specified in the data sheet must be observed.

Area A: Ice buildup at ambient temperatures ≤ 0°C must be prevented
Area B: Condensation at ambient temperatures > 0°C must be prevented

On 30 full days that are naturally distributed across an entire year, a humidity level of 95% is permissible at an ambient temperature ≤ 25°C.

chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/2961150

cUL Recognized
Approval ID: FILE E 172140

UL Recognized
Approval ID: FILE E 172140

EAC
Approval ID: RU*C-DE.*08.B.00010

UL Recognized
Approval ID: FILE E 172140

VDE approval of drawings
Approval ID: 40032864

VDE approval of drawings
Approval ID: 40054426

cUL Recognized
Approval ID: FILE E 172140

VDE approval of drawings
Approval ID: 40010212

cUL Recognized
Approval ID: FILE E 172140

UL Recognized
Approval ID: FILE E 172140

chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Classifications

ECLASS

ECLASS-11.0	27371601
ECLASS-12.0	27371601
ECLASS-13.0	27371601

ETIM

ETIM 9.0	EC001437

UNSPSC

UNSPSC 21.0	39122300

chanhvinh.com

REL-MR- 12DC/21 - Single relay

2961150

https://www.phoenixcontact.com/pc/products/2961150

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com