chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in miniature power relay, with power contact for high continuous currents, 1 changeover contact, input voltage 24 V AC

Your advantages

- Switching current of up to 16 A

Commercial data

Item number	2961406
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CK6931
Product key	CK6931
Catalog page	Page 290 (C-5-2019)
GTIN	4017918937812
Weight per piece (including packing)	16.18 g
Weight per piece (excluding packing)	15.06 g
Customs tariff number	85364190
Country of origin	AT

chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Technical data

Product properties

Product type	Single relay
Operating mode	100% operating factor
Mechanical service life	1x 10^7 cycles

Data management status

Date of last data management	02.05.2024

Insulation characteristics

Overvoltage category	III
Pollution degree	3

Electrical properties

Service life electrical	see diagram
Maximum power dissipation for nominal condition	0.77 W
Test voltage (Winding/contact)	5 kV AC (50 Hz, 1 min., winding/contact)

Input data

Coil side

Nominal input voltage U_N	24 V AC
Input voltage range	18.72 V AC ... 37.2 V AC
Input voltage range in reference to U_N	see diagram
Mains frequency	50/60 Hz
Drive and function	monostable
Drive (polarity)	non-polarized
Typical input current at U_N	32 mA (50 Hz)
	24 mA (60 Hz)
Typical response time	3 ms ... 12 ms (depending on phase relation)
Typical release time range	2 ms ... 9 ms (depending on phase relation)
Coil resistance	350 Ω ±10 % (at 20 °C)

Output data

Switching

Contact switching type	1 changeover contact
Type of switch contact	Single contact
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	12 V (at 10 mA)
Limiting continuous current	16 A
Maximum inrush current	25 A (20 ms)
Min. switching current	10 mA (at 12 V)

chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406


https://www.phoenixcontact.com/gb/products/2961406

Interrupting rating (ohmic load) max.	384 W (at 24 V DC)
	58 W (at 48 V DC)
	48 W (at 60 V DC)
	50 W (at 110 V DC)
	80 W (at 220 V DC)
	4000 VA (for 250 V AC)
Switching capacity	2 A (at 24 V, DC13)
	0.2 A (at 110 V, DC13)
	0.2 A (at 250 V, DC13)
	6 A (at 24 V, AC15)
	6 A (at 120 V, AC15)
	6 A (at 250 V, AC15)
Motor load according to UL 508	1/2 HP, 120 V AC (N/O contact)
	1 HP, 240 V AC (N/O contact)
	1/3 HP, 120 V AC (N/C contact)
	3/4 HP, 240 V AC (N/C contact)
	1/4 HP, 200 ... 250 V AC

Connection data

Connection method	Plug / solder connection

Dimensions

Dimensional drawing	
Width	12.7 mm
Height	29 mm
Depth	15.7 mm

Material specifications

Color	white (RAL 9010)

Environmental and real-life conditions

Ambient conditions

Degree of protection	RT II
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Approvals

chanhvinh.com

Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

Standards and regulations

Standards/regulations	IEC 60664
	EN 50178
	EN 61810-1

Mounting

Assembly note	Can be aligned without spacing (> 70 °C ≥ 2.5 mm)
Mounting position	any

chanhvinh.com


REL-MR- 24AC/21HC - Single relay

2961406


https://www.phoenixcontact.com/gb/products/2961406

Drawings

Circuit diagram



Diagram



1 250 V AC, ohmic load (DC coils)
2 250 V AC, ohmic load (AC coils)

Electrical service life


chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Diagram



Permissible humidity for operation and storage.
The maximum permissible ambient temperature as specified in the data sheet must be observed.

Area A: Ice buildup at ambient temperatures ≤ 0°C must be prevented
Area B: Condensation at ambient temperatures > 0°C must be prevented

On 30 full days that are naturally distributed across an entire year, a humidity level of 95% is permissible at an ambient temperature ≤ 25°C.


chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Diagram



Service life reduction factor with various cos phi


chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Diagram



1 DC coils
2 AC coils

Operating voltage range


chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Dimensional drawing




chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Diagram



1 AC, ohmic load
2 DC, ohmic load
3 DC, L/R = 40 ms

Interrupting rating


chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Drilling plan/solder pad geometry



a = pitch division 2.5 mm

chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/2961406

cUL Recognized
Approval ID: FILE E 228652

UL Recognized
Approval ID: FILE E 228652

EAC
Approval ID: TR_TS_D_00573_c

UL Recognized
Approval ID: FILE E 172140

VDE Zeichengenehmigung
Approval ID: 40007758

VDE Zeichengenehmigung
Approval ID: 40048281

cUL Recognized
Approval ID: FILE E 172140

EAC
Approval ID: RU*C-DE.*08.B.00010

chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Classifications

ECLASS

ECLASS-11.0	27371601
ECLASS-12.0	27371601
ECLASS-13.0	27371601

ETIM

ETIM 9.0	EC001437

UNSPSC

UNSPSC 21.0	39122300

chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

chanhvinh.com

REL-MR- 24AC/21HC - Single relay

2961406

https://www.phoenixcontact.com/gb/products/2961406

Mandatory accessories

RIF-1-BPT/2X21 - Relay base

2900931

https://www.phoenixcontact.com/gb/products/2900931



Relay base RIF-1..., for miniature power relay with 1 or 2 changeover contacts or solid-state relays of the same design, Push-in connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

RIF-1-BSC/2X21 - Relay base

2900930

https://www.phoenixcontact.com/gb/products/2900930



RIF-1... relay base, for miniature power relay with 1 or 2 changeover contacts or identical solid-state relays, screw connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk