chanhvinh.com

WT-D HF 7,5X350 - Cable tie

3240716

https://www.phoenixcontact.com/gb/products/3240716

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable binders ideal for temporary fastening, with locking release, removable

Commercial data

Item number	3240716
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BE7133
Product key	BE7133
Catalog page	Page 618 (C-3-2019)
GTIN	4046356704328
Weight per piece (including packing)	3.82 g
Weight per piece (excluding packing)	3 g
Customs tariff number	39269097
Country of origin	PL

chanhvinh.com

WT-D HF 7,5X350 - Cable tie

3240716

https://www.phoenixcontact.com/gb/products/3240716

Technical data

Product properties

Product type	Cable tie
Type	Internal teeth
Tensile strength GRP	220 N

Dimensions

Width	7.5 mm
Length	350 mm

Material specifications

Color	transparent
Material	PA 6.6
Flammability rating according to UL 94	V2
Components	free from silicone and halogen

Cable/line

External cable diameter	6 mm ... 100 mm
Tensile strength	220 N

Environmental and real-life conditions

Ambient conditions

Optimum ambient temperature (storage/transport)	23.00 °C 50.00 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture.To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	-10 °C ... 60 °C
Resistance to UV radiation	no

Mounting

Mounting type	Can be removed

chanhvinh.com

WT-D HF 7,5X350 - Cable tie

3240716

https://www.phoenixcontact.com/gb/products/3240716

Classifications

ECLASS

ECLASS-13.0	27140702

ETIM

ETIM 9.0	EC000046

UNSPSC

UNSPSC 21.0	39121700

chanhvinh.com

WT-D HF 7,5X350 - Cable tie

3240716

https://www.phoenixcontact.com/gb/products/3240716

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk