chanhvinh.com

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, coding: A, on Socket straight M8 Snap-in, coding: A, cable length: 3 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Save time, thanks to installation with snap-in fast locking system

Commercial data

Item number	1417701
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	AF1BBA
Catalog page	Page 499 (C-6-2019)
GTIN	4055626123356
Weight per piece (including packing)	64.5 g
Weight per piece (excluding packing)	61.52 g
Customs tariff number	85444290
Country of origin	PL

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	3
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	48 V AC
	60 V DC
Nominal current I_N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100

Signaling

Status display	no
Status display present	no

Connector

Connection 1

Type	Plug straight M8
Number of positions	3
Coding type	A

Connection 2

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701


https://www.phoenixcontact.com/pc/products/1417701

Type	Socket straight M8 Snap-in
Number of positions	3
Locking type	Snap-in
Coding type	A

Cable/line

Cable length	3 m

PUR halogen-free black [PUR]

Dimensional drawing	
Cable weight	18 kg/km
UL AWM Style	20549 / 10493 (80°C/300 V)
Number of positions	3
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross section	3x 0.25 mm² (Signal line)
Wire diameter incl. insulation	1.17 mm ±0.02 mm
External cable diameter	3.60 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	brown, blue, black
Thickness, insulation	≥ 0.21 mm (Core insulation)
Thickness, outer sheath	approx. 0.50 mm
Overall twist	3 wires, twisted
Length of twist, overall twist	40 mm
Max. conductor resistance	≤ 78 Ω/km (at 20 °C)
Insulation resistance	≥ 100 GΩ*km (at 20 °C)
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 3000 V
Smallest bending radius, fixed installation	18 mm
Smallest bending radius, movable installation	36 mm
Dynamic load capacity (bending)	Max. bending cycles: 10000000, Bending radius: 44 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 m/s²

chanhvinh.com

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701

Dynamic load capacity (torsion)	Torsion: ±180 °/m, Torsion cycles: ≥2000000, Torsional frequency: 35 cycles/min.
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with UL 758/1581 FT2
	DIN EN 60332-2-2 (20 s)
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	hydrolysis and microbe resistant
	Highly resistant to acids, alkaline solutions and solvents
	Resistant to salt water
	partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Special properties	Flexible cable conduit capable
	Silicone-free
	Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-25 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations

M8

Standard designation	M8 connector
Standards/specifications	IEC 61076-2-104

chanhvinh.com


SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701


Drawings

Dimensional drawing



M8 x 1 male plug, straight version

Dimensional drawing



M8 snap-in sockets


chanhvinh.com

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701


https://www.phoenixcontact.com/pc/products/1417701

Schematic diagram



Pin assignment M8 plug, 3-pos., view male side

Schematic diagram



Pin assignment M8 socket, 3-pos., view female side


chanhvinh.com

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701

Circuit diagram



Contact assignment of M8 plugs/sockets

chanhvinh.com

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/1417701

UL Listed
Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	-	-

cUL Listed
Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	-	-

EAC-RoHS
Approval ID: RU D-DE.HB35.B.00387

cULus Listed

chanhvinh.com

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 9.0	EC001855

UNSPSC

UNSPSC 21.0	26121600

chanhvinh.com

SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - Sensor/actuator cable

1417701

https://www.phoenixcontact.com/pc/products/1417701

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

EF3.0 Climate Change

CO2e kg	1.161 kg CO2e

Phoenix Contact 2025 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com