chanhvinh.com

Ultra-Grip
Domed Head

Carbon Steel
Mandrel: Carbon Steel



d	l	g	DESCRIPTION	d_h	d_k	k	d_m	S	T	BULK PACK ARTICLE	BULK PACK BOX QTY	/1,000 KG
mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.8	10.1	1.6 - 7.0	SD670UG	4.9 - 5.1	9.2 - 9.8	2.1	3.0	6,500	5,330	62323	2,000	
	14.1	5.5 - 11.1	SD6110UG							62324	2,000	
	14.1	1.6 - 11.1	SD6110UGX							62325	2,000	
6.4	13.8	2.0 - 9.5	SD895UG	6.6 - 7.0	12.7 - 13.3	2.8	4.0	11,800	10,000	62338	1,000	
	20.3	9.0 - 16.0	SD8160UG							62339	1,000	
	20.3	2.0 - 16.0	SD8160UGX							62340	1,000	

Ultra-Grip
100° Countersunk

Carbon Steel
Mandrel: Carbon Steel



d	l	g	DESCRIPTION	d_h	d_k	k	d_m	S	T	BULK PACK ARTICLE	BULK PACK BOX QTY	/1,000 KG
mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.8	11.9	3.2 - 8.5	SK685UG	4.9 - 5.1	8.1 - 8.7	1.7	3.0	6,500	5,330	62326	2,000	
	16.2	7.5 - 12.5	SK6125UG							62327	2,000	
6.4	16.6	4.0 - 12.0	SK8120UG	6.6 - 7.0	9.7 - 10.3	2.0	4.0	11,800	10,000	62341	1,000	
	23.1	10.5 - 18.5	SK8185UG							62342	1,000	

d=Nominal Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); d_h=Hole Size (Min - Max); d_k=Flange Diameter (Min - Max);
k=Flange Thickness (Max); d_m=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Items marked "on request" are subject to minimum order quantities or values and made to order lead times. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu