chanhvinh.com

Ultra-Grip
Domed Head



Stainless Steel
Mandrel: Stainless Steel

d	l	g	DESCRIPTION	d_h	d_k	k	d_m	S	T	BULK PACK ARTICLE	BULK PACK BOX QTY	KG /1,000
mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.8	10.1	1.6 - 7.0	SSD670UG	4.9 - 5.1	9.2 - 9.8	2.1	3.0	5,780	4,220	62328	2,000	
	14.1	5.5 - 11.1	SSD6110UG							62329	2,000	
	14.1	1.6 - 11.1	SSD6110UGX							62330	2,000	
6.4	13.8	2.0 - 9.5	SSD895UG	6.6 - 7.0	12.7 - 13.3	2.8	4.0	10,450	8,000	62343	1,000	
	20.3	9.0 - 16.0	SSD8160UG							62344	1,000	
	20.3	2.0 - 16.0	SSD8160UGX							62345	1,000	

Ultra-Grip
100° Countersunk



Stainless Steel
Mandrel: Stainless Steel

d	l	g	DESCRIPTION	d_h	d_k	k	d_m	S	T	BULK PACK ARTICLE	BULK PACK BOX QTY	KG /1,000
mm	mm	mm		mm	mm	mm	mm	N	N			kg
4.8	11.9	3.2 - 8.5	SSK685UG	4.9 - 5.1	8.1 - 8.7	1.7	3.0	5,780	4,220	62331	2,000	
	16.2	7.5 - 12.5	SSK6125UG							62332	2,000	
6.4	16.6	4.0 - 12.0	SSK8120UG	6.6 - 7.0	9.7 - 10.3	2.0	4.0	10,450	8,000	62346	1,000	
	23.1	10.5 - 18.5	SSK8185UG							62347	1,000	

d=Nominal Diameter; *l*=Body Length (+/- 0.5mm); *g*=Grip Range (Min - Max); d_h=Hole Size (Min - Max); d_k=Flange Diameter (Min - Max);
k=Flange Thickness (Max); d_m=Nominal Mandrel Diameter; *S*=Nominal Shear Strength; *T*=Nominal Tensile Strength

The POP® Riveting Systems catalogue contains details of our core range only. Other rivet configurations are available. Items marked "on request" are subject to minimum order quantities or values and made to order lead times. Please enquire to Emhart Customer Service. For the latest catalogue digital version please visit www.emhart.eu