chanhvinh.com

PERFORMANCE MADE SMARTER



2-wire programmable RTD transmitter

5332A


– RTD or Ohm input
– Accuracy: Better than 0.05% of selected range
– Programmable sensor error value
– For DIN form B sensor head mounting

Application
- Linearized temperature measurement with Pt100...Pt1000 or Ni100...Ni1000 sensor.
- Conversion of linear resistance variation to a standard analog current signal, for instance from valves or Ohmic level sensors.

Technical characteristics
- Within a few seconds the user can program PR5332A to measure temperatures within all ranges defined by the norms.
- Dedicated programmable non-isolated 4-wire RTD transmitter.
- RTD and resistance inputs have cable compensation for 2-, 3- and 4-wire connection.
- Continuous check of vital stored data for safety reasons.

Mounting / installation
- For DIN form B sensor head or DIN rail mounting with the PR fitting type 8421.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

chanhvinh.com

Order

Type	Version	
5332	Simple, no approvals	: N
	General purpose, Zone 2, ATEX, IECEx	: A

Environmental Conditions

Operating temperature..... -40°C to +85°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree (encl./terminal)..... IP68 / IP00

Mechanical specifications

Dimensions..... Ø 44 x 20.2 mm
Weight approx..... 50 g
Wire size..... 1 x 1.5 mm^2 stranded wire
Screw terminal torque..... 0.4 Nm

Common specifications

Supply
Supply voltage..... 7.2...35 VDC
Internal power dissipation..... 25 mW…0.8 W

Response time
Response time (programmable)..... 1...60 s

Voltage drop..... 7.2 VDC
Warm-up time..... 5 min.
Programming..... Loop Link
Signal / noise ratio..... Min. 60 dB
EEprom error check..... < 3.5 s
Accuracy..... Better than 0.05% of selected range
Signal dynamics, input..... 20 bit
Signal dynamics, output..... 16 bit
Effect of supply voltage change..... < 0.005% of span / VDC
EMC immunity influence..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst..... < ±1% of span

Input specifications

Common input specifications
Max. offset..... 50% of selected max. value

RTD input
RTD type..... Pt100, Ni100, lin. R
Cable resistance per wire..... 5 Ω (max.)
Sensor current..... Nom. 0.2 mA
Effect of sensor cable resistance (3-/4-wire)..... < 0.002 Ω / Ω
Sensor error detection..... Yes

Linear resistance input
Linear resistance min....max..... 0 Ω...5000 Ω

Output specifications

Common output specifications
Updating time..... 440 ms

Current output
Signal range..... 4…20 mA
Min. signal range..... 16 mA
Load (@ current output)..... ≤ (Vsupply - 7.2) / 0.023 [Ω]
Load stability..... ≤ 0.01% of span / 100 Ω
Sensor error indication..... Programmable 3.5…23 mA
NAMUR NE43 Upscale/Downscale..... 23 mA / 3.5 mA

of span..... = of the presently selected range

I.S. / Ex marking

ATEX..... II 3 G Ex nA [ic] IIC T4...T6 Gc, II 3 G Ex ic IIC T4...T6 Gc, II 3 D Ex ic IIIC Dc
IECEx..... Ex nA [ic] IIC T4...T6 Gc, Ex ic IIC T4...T6 Gc, Ex ic IIIC Dc

Observed authority requirements

Directives
EMC..... 2014/30/EU
ATEX..... 2014/34/EU
RoHS..... 2011/65/EU

EAC..... TR-CU 020/2011
EAC Ex..... TR-CU 012/2011

Approvals

ATEX..... KEMA 10ATEX0002 X
IECEx..... DEK 13.0035X