chanhvinh.com

PERFORMANCE MADE SMARTER

Loop-powered LCD indicator

5531B



– 4 digit 1/8 DIN (48 x 96 mm) loop-powered LCD display
– Easy push-button configuration
– Backlit LCD display is readable in low light conditions
– Display can be mounted in the safe area or in I.S. / Ex zone

Application

- The 5531 indicator is powered by the 4 to 20 mA current loop and is easily scaled to display the correct process value.
- Because it does not require separate power wiring, the 5531 is perfect for remote display of process loops.
- The 5531B can be mounted in Ex Zone 1.
- The 5531B1 Ex display includes the 8501 enclosure and can be mounted in Ex Zone 2 or 22 (gas or dust).
- The 5531B2 includes the 8501 enclosure and can be mounted in Ex Zone 1, 2, 21 or 22 (gas or dust).


Technical characteristics

- With a full measurement range of 3.6 to 23 mA, the 5531 is NAMUR NE43 compliant.
- The display can be push-button scaled to any range between -9999 to 9999, and reverse display action is possible.
- The LCD backlight can be set to half or full intensity for easy viewing in low light conditions.
- The display only requires 1.5 VDC, (75 Ω loop load), with the backlight turned off.
- The input is HART® transparent.
- The front push-buttons can be disabled to prevent unauthorized adjustment.

Mounting / installation

- Once panel mounted with the included gasket, the 5531 provides IP65 ingress protection.

Connections



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

chanhvinh.com

Order:

Type	Input signal area classification	Field enclosure
5531B1	4...20 mA from safe, zone 2 and 22	Yes
5531B	4...20 mA from zone 0	No
5531B2	4...20 mA from zone 0 and 20	Yes

Environmental Conditions

Specifications range..... -20°C to +60°C
Storage temperature..... -20°C to +60°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree..... IP65, from front

Mechanical specifications

Dimensions (HxWxD)..... 48 x 96 x 120 mm
Cut out dimensions..... 44.5 x 91.5 mm
Weight approx..... 200 g
Cable glands and cable diameter..... M16 x 1.5 / Ø 5...8 mm
Wire size, connector terminal 1 - 4..... 0.13...2.08 mm^2 / AWG 26...14 stranded wire

Common specifications

Supply
Supply voltage..... Input loop-powered

Response time
Response time (0...90%, 100...10%)..... < 1 s

EMC immunity influence..... < ±0.5% of span
Signal / noise ratio..... > 60 dB
Updating time..... 500 ms

Input specifications

Current input
Measurement range..... 3.6...23 mA
Loop error detection, 4...20 mA: Low..... ~ < 3 mA
Loop error detection, 4...20 mA: High..... ~ > 24 mA

Input voltage drop, without backlight..... < 1.5 V @ 20 mA
Input voltage drop, with full backlight..... < 10.5 V @ 20 mA

Output specifications

Display:
Display readout..... ± 9999 (4 digits)
Digit height..... 16 mm

Approvals

EMC..... 2004/108/EC
ATEX 94/9/EC..... KEMA 05ATEX1044 X (5531A/B1)
ATEX 94/9/EC..... KEMA 05ATEX1105 X (5531B/B2)
EAC..... TR-CU 020/2011
EAC Ex TR-CU 012/2011..... RU C-DK.GB08.V.00410