chanhvinh.com

PERFORMANCE MADE SMARTER



Programmable LED indicator

5714

– 4-digit 14-segment LED display
– Input for mA, V, Ohm, RTD, TC and potentiometer
– 2 relays and analog output
– Universal supply
– Front key programmable

Application

- Display for digital readout of current / voltage / resistance / temperature or potentiometer signals.
- Process control with 2 potential-free relays and / or analog output.
- For local readout in extremely wet atmospheres with a specially designed splash-proof cover.

Technical characteristics


- 4-digit LED indicator with 13.8 mm 14-segment characters. Max. display readout -1999...9999 with programmable decimal point and relay ON / OFF indication.
- All standard operational parameters can be adjusted to any application by way of the front function keys.
- Help texts in eight languages can be selected via a menu item.
- PR5714 is available fully-configured according to specifications ready for process control and visualization.
- Inputs, outputs, and supply are floating and galvanically separated.
- In versions with relay outputs the user can minimize the installation test time by activating / deactivating each relay independently of the input signal.

Mounting / installation


- To be mounted in panel front. The included rubber packing must be mounted between the panel cutout hole and the display front to obtain a protection degree of IP65 (type 4X). For extra protection in extreme environments, PR5714 can be delivered with a specially designed splash-proof cover as accessory.

Applications


Input signals:



Output signals:



Supply:



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

chanhvinh.com

Order:

Type	Version	
5714	Standard	: A
	2 relays	: B
	Analog output	: C
	Analog output and 2 relays	: D

Environmental Conditions

Operating temperature..... -20°C to +60°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree (mounted in panel)..... IP65 / Type 4X

Mechanical specifications

Dimensions (HxWxD)..... 48 x 96 x 120 mm
Cut out dimensions..... 44.5 x 91.5 mm
Weight approx..... 230 g
Wire size, pin 41-46 (max.)..... 0.05...1.31 mm^2 AWG 30...16 stranded wire
Wire size, others, max..... 0.05...3.31 mm^2 / AWG 30...12 stranded wire
Vibration..... IEC 60068-2-6
2...13.2 Hz..... ±1 mm
13.2...100 Hz..... ±0.7 g

Common specifications

Supply

Supply voltage, universal..... 21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Max. required power..... 2.5 W (5714A)
Max. required power..... 3.0 W (5714B/C)
Max. required power..... 3.5 W (5714D)
Internal power dissipation..... 2.2 W (5714A)
Internal power dissipation..... 2.7 W (5714B/C)
Internal power dissipation..... 3.2 W (5714D)

Isolation voltage

Isolation voltage, test / working..... 2.3 kVAC / 250 VAC

Response time

Temperature input, programmable (0...90%, 100...10%)..... 1...60 s
mA / V input (programmable)..... 0.4...60 s

Auxiliary supplies

2-wire supply (pin 46...45)..... 25...15 VDC / 0...20 mA

Signal / noise ratio..... Min. 60 dB (0...100 kHz)
Accuracy..... Better than 0.1% of sel. range
EMC immunity influence..... < ±0.5% of readout

Input specifications

RTD input

RTD type..... Pt10/20/50/100/200/250; Pt300/400/500/1000; Ni50/100/120/1000; Cu10/20/50/100
Cable resistance per wire..... 50 Ω (max.)
Sensor current..... Nom. 0.2 mA
Effect of sensor cable resistance (3-/4-wire)..... < 0.002 Ω / Ω

Linear resistance input

Linear resistance min....max..... 0 Ω...10000 Ω

Potentiometer input

Potentiometer min....max..... 10 Ω...100 kΩ

TC input

Thermocouple type..... B, E, J, K, L, N, R, S, T, U, W3, W5, LR
CJC via int. mounted sensor..... ±(2.0°C + 0.4°C * Δt)
Δt =..... Internal temp.-ambient temp.
Sensor error detection..... Yes
Sensor error current: When detecting / else..... Nom. 2 µA / 0 µA

Current input

Measurement range..... 0...23 mA
Programmable measurement ranges..... 0...20 and 4...20 mA
Input resistance..... Nom. 20 Ω + PTC 25 Ω
Sensor error detection..... Loop break 4...20 mA

Voltage input

Measurement range..... 0...12 VDC
Programmable measurement ranges..... 0/0.2...1; 0/2...10 VDC
Input resistance..... Nom. 10 MΩ

Output specifications

Display

Display readout..... -1999...9999 (4 digits)
Decimal point..... Programmable
Digit height..... 13.8 mm
Display updating..... 2.2 times / s
Input outside input range is indicated by..... Explanatory text

Current output

Signal range..... 0...23 mA
Programmable signal ranges..... 0...20/4...20/20...0/20...4 mA
Load (@ current output)..... ≤ 800 Ω
Load stability..... ≤ 0.01% of span / 100 Ω
Sensor error indication..... 0 / 3.5 / 23 mA / none
NAMUR NE43 Upscale/Downscale..... 23 mA / 3.5 mA
Output limitation, on 4...20 and 20...4 mA signals..... 3.8...20.5 mA
Output limitation, on 0...20 and 20...0 mA signals..... 0...20.5 mA
Current limit..... ≤ 28 mA

Relay output

Relay functions..... Setpoint
Hysteresis..... 0...100%
ON and OFF delay..... 0...3600 s
Sensor error reaction..... Break / Make / Hold
Max. voltage..... 250 VAC / VDC
Max. current..... 2 A
Max. AC power..... 500 VA
Max. DC current, resistive load ≤ 30 VDC..... 2 ADC
Max. DC current, resistive load > 30 VDC..... See manual for details

Observed authority requirements

EMC..... 2014/30/EU
LVD..... 2014/35/EU
RoHS..... 2011/65/EU
EAC..... TR-CU 020/2011

Approvals

DNV-GL Marine..... Stand. f. Certific. No. 2.4
EU RO Mutual Recognition Type Approval..... MRA000000Z
UL..... UL 508 / C22.2 no. 14