chanhvinh.com

pressmaster
QUALITY TO HAND


Product

KCC 2511



KCC-2511 is a crimping tool for coaxial connectors, 10.9 mm, 5.41 mm, 2.54 mm, 1.69 mm/.213", .429", .100", .067", HEX-Crimp.

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



Die profile


Crimp profile

TECHNICAL DATA
Length: 256 mm/10.08"
Width: 22 mm/0.87"
Height: 80 mm/3.15"
Weight: 560 gr/1.23 lb
Crimp dimensions mm/mm^2:
5,41 mm/10,90 mm/2,54 mm/1,69 mm
Crimp dimensions inch/AWG:
.213"/.429"/.100"/.067"
Connector: Coaxial connector
Description: For example BNC, TNC, N connectors on RG 58, RG 8, RG 11, Ethernet, Thinnet.
Life span, cycles: 50,000
Cables: 9914, RG114A/U, RG115A/U, RG12A/U, RG133A/U, RG142B/U, RG144/U, RG165/U, RG166/U, RG1A/U, RG213/U, RG214/U, RG215/U, RG216/U, RG22/U, RG223/U, RG225/U, RG227/U, RG22B/U, RG26A/U, RG302/U, RG391/U, RG58C/U, RG63B/U, RG65A/U, RG79B/U

Pressmaster AB
P.O. Box 3, Industrivägen
SE-796 21 Älvdalen, Sweden
Tel: +46 (0)251-451 00
info@pressmaster.se
www.pressmaster.com