chanhvinh.com

Power Inductor
Automotive Grade
AWVS Series

Overview

Power inductors are passive electronic components used in various circuits to store energy in a magnetic field when electrical current flows through them. They are critical in filtering, energy storage, and noise suppression in power electronic systems.
They are designed to handle higher currents and are optimized for minimal power loss and thermal efficiency.

Benefits

1. Automotive grade available
2. No thermal aging
3. High current and efficiency, Magnetic epoxy sealing(Seme-shield)

Applications

1. Automotive Systems for Infotainment, MCU, Dashboard, CCD Module
2. Media player, Audio class
3. Net working, LCD Panel/TV,
4. Base stations, 5G infrastructure, and signal processing systems.
5. Telematics

Product Information

Series	L (mm)	W(mm)	T (mm)	Inductance (μH)
AWVS	3.2	2.5	1.5	0.22 ~ 1200
	3.2	2.5	1.5	
	4.0	4.0	1.2	
	4.0	4.0	1.5~2.0	
	5.0	5.0	1.7~2.2	
	5.0	5.0	4.0	
	5.0	5.0	3.7~4.2	
	6.0	6.0	1.7~2.2	
	6.0	6.0	2.5~3.0	
	6.0	6.0	4.2~4.7	
	6.0	6.0	4.5	
	8.0	8.0	3.7~4.2	
	8.0	8.0	4.0	





chanhvinh.com

YAGEO PULSE GROUP


AWVS00606045 Series Specification

AEC-Q200

1 Scope:

This specification applies to Wire Wound Power Inductors

2 Part Numbering:




3 Rating:

Operating Temperature: - 4 0℃ ~ 1 2 5℃(Including self - temperature rise)

Storage Temperature: - 4 0℃ ~ 1 2 5℃

(The storage temperature range is for after the assembly)

4 Marking:



Ex Marking : 220

Marking color : Black

5 Standard Testing Condition

	Unless otherwise specified	In case of doubt
Temperature	Ordinary Temperature(15 to 35℃)	20 to 30℃
Humidity	Ordinary Humidity(25 to 85% RH)	50 to 80 %RH


chanhvinh.com

YAGEO PULSE GROUP

AWVS00606045 Series Specification

AEC-Q200

6 Configuration and Dimensions:



Dimensions in mm

TYPE	606045
A	6.0±0.2
B	6.0±0.2
C	$4.5^{+0.2}_{-0.3}$
D	1.8±0.3
E	5.0 typ.

Net Weight (grms)

SIZE CODE	Net Weight (grms)
606045	0.645 (typ).

7 Electrical Characteristics:

Part No.	Inductance (uH)	Test Freq.	RDC (mΩ)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVS00606045R47□00	0.47	100kHz,1V	8	16.5(14.85)	7.8(7.02)	20,30	R47
AWVS006060451R0□00	1.0	100kHz,1V	12	12.2(10.50)	6.5(5.80)	20,30	1R0
AWVS006060451R2□00	1.2	100kHz,1V	13	10.6(9.50)	5.9(5.30)	20,30	1R2
AWVS006060451R5□00	1.5	100kHz,1V	15	10.4(9.30)	5.9(5.30)	20,30	1R5
AWVS006060451R8□00	1.8	100kHz,1V	17	9.6(8.60)	5.6(5.00)	20,30	1R8
AWVS006060452R2□00	2.2	100kHz,1V	18.4	8.8(7.90)	5.1(4.50)	20,30	2R2
AWVS006060452R3□00	2.3	100kHz,1V	19	8.8(7.90)	5.0(4.50)	20,30	2R3
AWVS006060453R0□00	3.0	100kHz,1V	22	7.8(7.00)	4.4(3.90)	20,30	3R0
AWVS006060453R3□00	3.3	100kHz,1V	24	7.5(6.70)	4.3(3.80)	20,30	3R3
AWVS006060453R6□00	3.6	100kHz,1V	24	7.5(6.70)	4.3(3.80)	20,30	3R6
AWVS006060453R9□00	3.9	100kHz,1V	26	7.0(6.30)	4.0(3.60)	20,30	3R9
AWVS006060454R5□00	4.5	100kHz,1V	31	6.7(6.00)	3.9(3.50)	20,30	4R5
AWVS006060454R7□00	4.7	100kHz,1V	31	6.7(6.00)	3.9(3.50)	20,30	4R7
AWVS006060455R1□00	5.1	100kHz,1V	33	6.0(5.40)	3.5(3.10)	20,30	5R1
AWVS006060455R6□00	5.6	100kHz,1V	40	5.5(4.90)	3.3(2.90)	20,30	5R6
AWVS006060456R3□00	6.3	100kHz,1V	40	5.5(4.90)	3.3(2.90)	20,30	6R3
AWVS006060456R8□00	6.8	100kHz,1V	43	5.3(4.70)	3.2(2.80)	20,30	6R8
AWVS006060458R2□00	8.2	100kHz,1V	53	4.6(4.10)	2.9(2.60)	20,30	8R2
AWVS00606045100□00	10	100kHz,1V	57	4.5(4.00)	2.7(2.40)	20,30	100
AWVS00606045150□00	15	100kHz,1V	80	3.4(3.00)	2.2(1.90)	20,30	150
AWVS00606045180□00	18	100kHz,1V	100	3.1(2.70)	1.8(1.60)	20,30	180
AWVS00606045220□00	22	100kHz,1V	125	3.0(2.70)	1.9(1.70)	20,30	220
AWVS00606045270□00	27	100kHz,1V	160	2.5(2.20)	1.3(1.10)	20,30	270
AWVS00606045330□00	33	100kHz,1V	165	2.3(2.00)	1.4(1.20)	20,30	330
AWVS00606045470□00	47	100kHz,1V	245	1.9(1.70)	1.2(1.00)	20,30	470

NOTE: □-tolerance M=±20% / T=±30%

1.Operating temperature range -40℃~125℃(Including self-temperature rise)

2.Isat for Inductance drop 30% from its value without current.

3.Irms for a 40℃ temperature rise from 25℃ ambient.

chanhvinh.com

YAGEO GROUP PULSE

AWVS00606045 Series Specification

AEC-Q200

Part No.	Inductance (uH)	Test Freq.	RDC (mΩ)±30%	Isat(A) Typ.(Max)	Irms(A) Typ.(Max)	Tolerance (±%)	Marking
AWVS00606045560□00	56	100kHz,1V	310	1.7(1.50)	1.1(0.99)	20,30	560
AWVS00606045680□00	68	100kHz,1V	330	1.6(1.40)	1.0(0.90)	20,30	680
AWVS00606045820□00	82	100kHz,1V	490	1.50(1.30)	0.85(0.76)	20,30	820
AWVS00606045101□00	100	100kHz,1V	500	1.3(1.10)	0.8(0.72)	20,30	101
AWVS00606045181□00	180	100kHz,1V	1280	0.95(0.85)	0.50(0.45)	20,30	181
AWVS00606045221□00	220	100kHz,1V	1300	0.82(0.73)	0.38(0.34)	20,30	221
AWVS00606045331□00	330	100kHz,1V	1800	0.7(0.63)	0.35(0.31)	20,30	331
AWVS00606045471□00	470	100kHz,1V	2900	0.52(0.46)	0.32(0.28)	20,30	471
AWVS00606045561□00	560	100kHz,1V	4300	0.57(0.51)	0.29(0.26)	20,30	561
AWVS00606045681□00	680	100kHz,1V	5000	0.46(0.41)	0.26(0.23)	20,30	681
AWVS00606045102□00	1000	100kHz,1V	6000	0.4(0.36)	0.22(0.19)	20,30	102

chanhvinh.com

chanhvinh.com


YAGEO PULSE GROUP

AWVS00606045 Series Specification

AEC-Q200

8 AWVS00606045 Series

8.1 Construction:



8.2 Material List:

NO	Part	Material
1	Core	Ferrite
2	Terminal	Ag/Ni/Sn
3	Wire	Copper(180℃)
4	Epoxy	Magnetic powder resin

chanhvinh.com


YAGEO PULSE GROUP

AWVS00606045 Series Specification

AEC-Q200

9 Reliability of Wire Wound Power Inductors

1-1.Mechanical Performance

	Item	Specification	Test Method
1-1-1	Board Flex	The forces applied on the right conditions must not damage the terminal electrode and the ferrite.	Test device shall be soldered on the substrate Substrate Dimension: 100x40x1.6mm Deflection: 2.0mm Keeping Time: 60 sec 
1-1-2	Terminal Strength	The chip must not damage the terminal electrode and the ferrite.	Appendix 1 Note(AEC-Q200-005):Force of 1.8 kg for 60 seconds.
1-1-3	Solderability	The electrodes shall be at least 95% covered with new solder coating.	Pre-heating: 150℃, 1min Solder Composition: Sn/3.0Ag/0.5Cu Solder Temperature: 245±5℃ Immersion Time: 4±1sec
1-1-4	Resistance to Soldering Heat	Appearance:No damage Inductance change shall be within ±10%.	Pre-heating: 150℃, 1min Solder Composition: Sn/Ag3.0/Cu0.5 Solder Temperature: 260±5℃ Immersion Time: 10±1sec
1-1-5	Resistance to Solvents	There must be no change in appearance or obliteration of marking.	Inductors must withstand 6 minutes of alcohol or water.
1-1-6	Mechanical Shock	The forces applied on the right conditions must not damage the terminal electrode and the ferrite.	Pulse shape：Half-sine waveform Impact acceleration：100 g Pulse duration：6 ms Number of shocks：18 shocks (3 shocks for each face) Orientation：Bottom, top, left, right, front and rear faces
1-1-7	Vibration	Appearance:No damage Inductance change shall be within ±10%.	Vibration waveform: Sine waveform Vibration frequency: 10Hz~2000Hz Vibration acceleration: 5g Sweep rate: 0.764386otcave/minute Duration of test: 12 cycles each of 3 orientations 20 minutes for each cycle Vibration axes: X, Y & Z

1-2.Environmental Performance


No	Item	Specification	Test Method
1-2-1	High Temperature Exposure (Storage)	Appearance:No damage (for microscope of CASTOR MZ-420X)Inductance change shall be within ±10%.	Temperature: 125±3℃ Time: 1000hrs Measured after exposure in the room condition for 24hrs
1-2-2	Operational Life		Temperature: 125±2℃ Appliend Current : Rated Current Time: 1000± 24 hrs Measured after exposure in the room condition for 24hrs
1-2-3	Biased Humidity		Temperature: 85±2℃ Relative Humidity: 85% Time: 1000hrs Measured after exposure in the room condition for 24hrs
1-2-4	Temperature Cycling		Total cycles: 1000 cycles Temperature Cycling Test Conditions : -40 to +125 ℃ Soak Mode Condition： 30 minutes Measured after exposure in the room condition for 24hrs
1-2-5	ESD		Test mode：Contact Discharge Discharge level：±6KV, Discharge interval：1 second Polarity of the output voltage：Positive and negative Number of discharge：Discharge +/- for 1 time for the 2 test points.
			Test Mode：Air Discharge Discharge level：±12KV, ±16KV, ±25KV Discharge interval：＜5 seconds Polarity of the output voltage：Positive and negative Number of discharge：Discharge +/- for 1 time for the 1~2 test points.

chanhvinh.com

YAGEO PULSE GROUP

AWVS00606045 Series Specification

AEC-Q200



Reflow profile

Lead-Free(LF)標準溫度分析範圍 **Refer to J-STD-020C**

管制項目 Item.	升溫區 Ramp-up	預熱區 Pre-heating	迴焊區 Reflow	Peak Temp	冷卻區 Cooling
溫度範圍 Temp.scope	R.T ~ 150℃	150℃ ~ 200℃	Above 217℃	260±5℃	Peak Temp.~150℃
標準時間 Time spec.	–	60 ~ 180 sec	60 ~ 150 sec	20 ~ 40 sec	–
實際時間 Time result	–	75 ~ 100 sec	90 ~ 120 sec	20 ~ 35 sec	–

NOTE :

1. Re-flow possible times : within 2 times
2. Nitrogen adopted is recommended while in re-flow
3. Products can only be soldered with reflow

chanhvinh.com

YAGEO PULSE GROUP


AWVS00606045 Series Specification

AEC-Q200

10 Packaging:

10.1 Packaging -Cover Tape


The force for tearing off cover tape is 10 to 130 grams in the arrow direction.



10.2 Packaging Quantity

TYPE	PCS/REEL
606045	1000

10.3 Reel Dimensions



Dimensions in mm

TYPE	A	B	C	D
606045	330	100	13	16


chanhvinh.com

AWVS00606045 Series Specification

AEC-Q200


10 Packaging:

10.4 Tape Dimensions in mm



TYPE	A0	B0	K0	D	E	F	W	P	P0	P2
606045	6.25	6.25	4.65	1.55	1.75	7.5	16	12	4	2

11 Recommended Land Pattern:



Dimensions in mm

TYPE	A	B	C
606045	5.7	2.0	2.4

12 Note:

1. Please make sure that your product has been evaluated and confirmed against your specifications when our product is mounted to your product.
2. Do not knock nor drop.
3. All the items and parameters in this product specification have been prescribed on the premise that our product is used for the purpose,under the condition and in the environment agreed upon between you and us. You are requested not to use our product deviating from such agreement.
4. The storage period is less than 12 months. Be sure to follow the storage conditions (Temperature: 5 to 40°C, Humidity: 10 to 75% RH or less).
   If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
5. Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
6. The moisture sensitivity level (MSL) of products is classified as level 1.

chanhvinh.com


YAGEO PULSE GROUP

AWVS00606045 Series Specification

AEC-Q200


12 Note:

7. Void Appearance tolerance Limit




Exposed wire tolerance limit of coating resin part on product side.
The unilateral should be no more than two holes.

A≦ W/2	GOOD
A> W/2	NG




The appearance standard pf the chipping size in top side.

B≦ W/8	GOOD
B> W/8	NG



Electrode appearance criterion for exposed wire.

C≦ L/4	GOOD
C> L/4	NG



External appearance criterion for exposed wire

Exposed end of the winding wire at the side should be acceptable.

chanhvinh.com


YAGEO PULSE GROUP

AWVS00606045 Series Specification

AEC-Q200

13 Graph: AWVS00606045 Series Graph


AWVS006060451R0□00




AWVS006060451R0□00




AWVS006060451R2□00




AWVS006060451R2□00




AWVS006060451R5□00




AWVS006060451R5□00



AWVS006060451R8□00



AWVS006060451R8□00



chanhvinh.com


chanhvinh.com

YAGEO PULSE GROUP


AWVS00606045 Series Specification

AEC-Q200


AWVS006060452R2□00




AWVS006060452R2□00




AWVS006060452R3□00




AWVS006060452R3□00




AWVS006060453R0□00




AWVS006060453R0□00



AWVS006060453R3□00



AWVS006060453R3□00




chanhvinh.com

YAGEO PULSE GROUP


AWVS00606045 Series Specification

AEC-Q200


AWVS006060453R6□00




AWVS006060453R6□00




AWVS006060453R9□00




AWVS006060453R9□00




AWVS006060454R5□00




AWVS006060454R5□00



AWVS006060454R7□00



AWVS006060454R7□00




chanhvinh.com

YAGEO GROUP PULSE


AWVS00606045 Series Specification

AEC-Q200


AWVS006060455R1□00




AWVS006060455R1□00




AWVS006060455R6□00




AWVS006060455R6□00




AWVS006060456R3□00




AWVS006060456R3□00



AWVS006060456R8□00



AWVS006060456R8□00



chanhvinh.com

YAGEO GROUP PULSE


AWVS00606045 Series Specification

AEC-Q200


AWVS006060458R2□00




AWVS006060458R2□00




AWVS00606045100□00




AWVS00606045100□00




AWVS00606045150□00




AWVS00606045150□00



AWVS00606045180□00



AWVS00606045180□00




chanhvinh.com

YAGEO PULSE GROUP


AWVS00606045 Series Specification

AEC-Q200


AWVS00606045220□00




AWVS00606045220□00




AWVS00606045270□00




AWVS00606045270□00




AWVS00606045330□00




AWVS00606045330□00



AWVS00606045470□00



AWVS00606045470□00




chanhvinh.com

YAGEO PULSE GROUP


AWVS00606045 Series Specification

AEC-Q200


AWVS00606045560□00




AWVS00606045560□00




AWVS00606045680□00




AWVS00606045680□00




AWVS00606045101□00




AWVS00606045101□00



AWVS00606045221□00



AWVS00606045221□00




chanhvinh.com

YAGEO GROUP PULSE


AWVS00606045 Series Specification

AEC-Q200


AWVS00606045331□00




AWVS00606045331□00




AWVS00606045102□00




AWVS00606045102□00




BWVS00606045181□00




BWVS00606045181□00



AWVS00606045471□00



AWVS00606045471□00




chanhvinh.com

YAGEO GROUP PULSE


AWVS00606045 Series Specification

AEC-Q200


AWVS00606045561□00




AWVS00606045561□00




AWVS00606045681□00




AWVS00606045681□00




AWVS00606045R47□00



AWVS00606045R47□00



AWVS00606045820□00



AWVS00606045820□00

