chanhvinh.com

EMI Ferrite Bead

BBSY Series

Overview

EMI ferrite beads are made of ferrite material, which can block high-frequency noise while allowing required signals to pass through, providing high impedance and noise attenuation to improve signal integrity/efficiency and reduce power loss.

Benefits

1. Compliance with EMI regulations.
2. Reduced power loss and improved system efficiency
3. Operating temperature range: -55 ~ +125°C
4. Improved signal integrity

Applications

1. Wearable Devices
2. Industrial
3. Communications
4. Consumer Electronics

Product Information

Series	Size Code (JIS/EIA)	Impedance (Ω)
BBSY	0603/0201 1005/0402	10 ~ 2200



chanhvinh.com

BBSY00100505 Series Specification

1 Scope: This specification applies to MULTILAYER FERRITE CHIP BEADS

2 Part Numbering:



3 Rating:

Operating Temperature: - 55℃ ~ 125℃(Including self - temperature rise)

Storage Temperature: - 55℃ ~ 125℃(after PCB)
- 5℃~40℃,Humidity 40%~70%(before PCB)

4 Marking:

No Marking

5 Standard Testing Condition

	Unless otherwise specified	In case of doubt
Temperature	Ordinary Temperature(15 to 35℃)	20 to 30℃
Humidity	Ordinary Humidity(25 to 85% RH)	50 to 80 %RH

chanhvinh.com

YAGEO PULSE GROUP

BBSY00100505 Series Specification

6 Configuration and Dimensions:



Dimensions in mm

TYPE	100505
A	1.00±0.1
B	0.50±0.1
C	0.50±0.1
D	0.25±0.1

Net Weight (grms)

Size Code	Net Weight (grms)
100505	0.0014

7 Electrical Characteristics:

Part No.	Impedance (Ω)	Test Freq.	RDC (Ω)Max.	Rated Current (mA)Max.
BBSY00100505100□00	10	100 MHz,200 mV	0.025	1000
BBSY00100505110□00	11	100 MHz,200 mV	0.05	500
BBSY00100505150□00	15	100 MHz,200 mV	0.1	500
BBSY00100505190□00	19	100 MHz,200 mV	0.1	500
BBSY00100505220□00	22	100 MHz,200 mV	0.15	500
BBSY00100505300□00	30	100 MHz,200 mV	0.2	500
BBSY00100505320□00	32	100 MHz,200 mV	0.2	500
BBSY00100505330□00	33	100 MHz,200 mV	0.2	500
BBSY00100505400□00	40	100 MHz,200 mV	0.2	500
BBSY00100505470□00	47	100 MHz,200 mV	0.2	500
BBSY00100505500□00	50	100 MHz,200 mV	0.2	500
BBSY00100505600□00	60	100 MHz,200 mV	0.2	500
BBSY00100505700□00	70	100 MHz,200 mV	0.15	600
BBSY00100505750□00	75	100 MHz,200 mV	0.2	500
BBSY00100505800□00	80	100 MHz,200 mV	0.2	500
BBSY00100505900□00	90	100 MHz,200 mV	0.25	500
BBSY00100505101□00	100	100 MHz,200 mV	0.25	500
BBSY00100505121□00	120	100 MHz,200 mV	0.19	550
BBSY00100505151□00	150	100 MHz,200 mV	0.4	400
BBSY00100505181□00	180	100 MHz,200 mV	0.4	400
BBSY00100505221□00	220	100 MHz,200 mV	0.29	450
BBSY00100505241□00	240	100 MHz,200 mV	0.4	400
BBSY00100505301□00	300	100 MHz,200 mV	0.5	300
BBSY00100505331□00	330	100 MHz,200 mV	0.5	300

NOTE: □-tolerance Y=±25% / T=±30%

1.Operating temperature range - 5 5℃ ~ 1 2 5℃(Including self - temperature rise)

2.Rate Current : Applied the current to coils, the temperature rise shall not be more than 30℃

chanhvinh.com

BBSY00100505 Series Specification

Part No.	Impedance (Ω)	Test Freq.	RDC (Ω)Max.	Rated Current (mA)Max.
BBSY00100505471□00	470	100 MHz,200 mV	0.5	300
BBSY00100505481□00	480	100 MHz,200 mV	0.5	300
BBSY00100505601□00	600	100 MHz,200 mV	0.52	300
BBSY00100505102□00	1000	100 MHz,200 mV	0.65	300
BBSY00100505182□00	1800	100 MHz,200 mV	1.4	100
BBSY00100505222□00	2200	100 MHz,200 mV	1.4	100

chanhvinh.com

BBSY00100505 Series Specification

8 BBSY00100505 Series

8.1 Construction:



8.2 Material List:

No	Part	Material
1	Ferrite Substance	NiO-CuO-ZnO-Ferrite
2	Silver electrode	Ag
3	Silver electrode	Ag
4	Cu plating	Cu
5	Ni plating	Ni
6	Sn plating	Sn

chanhvinh.com

YAGEO GROUP PULSE

BBSY00100505 Series Specification

9 Reliability Of Ferrite Multilayer Chip Bead

1-1.Mechanical Performance

No	Item	Specification	Test Method
1-1-1	Flexure Strength	The forces applied on the right conditions must not damage the terminal electrode and the ferrite	Test device shall be soldered on the substrate Substrate Dimension: 100x40x1.6mm Deflection: 2.0mm  Keeping Time: 30sec *For 100505, substrate dimension is 100x40x0.8mm
1-1-2	Vibration		Test device shall be soldered on the substrate Oscillation Frequency: 10 to 55 to 10Hz for 1min Amplitude: 1.5mm Time: 2hrs for each axis (X, Y & Z), total 6hrs
1-1-3	Resistance to Soldering Heat	Appearance: No damage More than 75% of the terminal electrode should be covered with solder. Impedance : within ±30% of initial value	Pre-heating: 150℃, 1min Solder Composition: Sn/Ag3.0/Cu0.5(Pb-Free) Solder Temperature: 260±5℃ Immersion Time: 10±1sec
1-1-4	Solder ability	The electrodes shall be at least 95% covered with new solder coating	Pre-heating: 150℃, 1min Solder Composition: Sn/Ag3.0/Cu0.5(Pb-Free) Solder Temperature: 245±5℃(Pb-Free) Immersion Time: 4±1sec
1-1-5	Terminal Strength Test	No split termination 	Test device shall be soldered on the substrate, then apply a force in the direction of the arrow. Force : 5N Keeping Time: 10±1sec

1-2.Environmental Performance

No	Item	Specification	Test Method
1-2-1	Temperature Cycle	Appearance: No damage Impedance: within±30% of initial value	One cycle: Step / Temperature (℃) / Time (min) 1 / -55±3 / 30 2 / 25±2 / 3 3 / 125±3 / 30 4 / 25±2 / 3 Total: 100cycles Measured after exposure in the room condition for 24hrs
1-2-2	Humidity Resistance		Temperature: 40±2℃ Relative Humidity: 90 ~ 95% / Time: 1000hrs Measured after exposure in the room condition for 24hrs
1-2-3	High Temperature Resistance		Temperature: 125±3℃ / Relative Humidity: 0% Applied Current: Rated Current /Time: 1000hrs Measured after exposure in the room condition for 24hrs
1-2-4	Low Temperature Resistance		Temperature: -55±3℃ Relative Humidity: 0% / Time: 1000hrs Measured after exposure in the room condition for 24hrs

chanhvinh.com

BBSY00100505 Series Specification



Reflow profile

Lead-Free(LF)標準溫度分析範圍 **Refer to J-STD-020C**

管制項目 Item.	升溫區 Ramp-up	預熱區 Pre-heating	迴焊區 Reflow	Peak Temp	冷卻區 Cooling
溫度範圍 Temp.scope	R.T ~ 150℃	150℃ ~ 200℃	Above 217℃	260±5℃	Peak Temp.~150℃
標準時間 Time spec.	-	60 ~ 180 sec	60 ~ 150 sec	20 ~ 40 sec	-
實際時間 Time result	-	75 ~ 100 sec	90 ~ 120 sec	20 ~ 35 sec	-

NOTE :

1. Re-flow possible times : within 2 times
2. Nitrogen adopted is recommended while in re-flow
3. Products can only be soldered with reflow

chanhvinh.com

BBSY00100505 Series Specification

10 Packaging:

10.1 Packaging -Cover Tape

The force for tearing off cover tape is 10 to 100 grams in the arrow direction.



10.2 Packaging Quantity

TYPE	PCS/REEL
060303	15000
100505	10000

10.3 Reel Dimensions



Dimensions in mm

TYPE	A	B	C	D
060303	178	60	12	1.5
100505	178	60	12	1.5

chanhvinh.com

BBSY00100505 Series Specification

10 Packaging:

10.4 Tape Dimensions in mm



TYPE	A	B	T	W	P	F
060303	0.37	0.67	0.42	8	2	3.5
100505	0.62	1.12	0.60	8	2	3.5

11 Recommended Land Pattern:



Dimensions in mm

TYPE	A	B	C
100505	0.4	1.2 ~ 1.4	0.5

12 Note:

1. Please make sure that your product has been evaluated and confirmed against your specifications when our product is mounted to your product.
2. Do not knock nor drop.
3. All the items and parameters in this product specification have been prescribed on the premise that our product is used for the purpose,under the condition and in the environment agreed upon between you and us. You are requested not to use our product deviating from such agreement.
4. Please keep the distance between transformer/coil and other components (refer to the standard IEC 950)
5. The moisture sensitivity level (MSL) of products is classified as level 1.

chanhvinh.com

BBSY00100505 Series Specification

13 Graph:

BBSY00100505100Y00



BBSY00100505110Y00



BBSY00100505150Y00



BBSY00100505190Y00



BBSY00100505220Y00



BBSY00100505300Y00



BBSY00100505320Y00



BBSY00100505330Y00



chanhvinh.com

YAGEO PULSE GROUP

BBSY00100505 Series Specification

13 Graph:

BBSY00100505400Y00



BBSY00100505470Y00



BBSY00100505500Y00



BBSY00100505600Y00



BBSY00100505700Y00



BBSY00100505750Y00



BBSY00100505800Y00



BBSY00100505900Y00



chanhvinh.com

YAGEO GROUP PULSE

BBSY00100505 Series Specification

13 Graph:

BBSY00100505101Y00



BBSY00100505121Y00



BBSY00100505151Y00



BBSY00100505181Y00



BBSY00100505221Y00



BBSY00100505241Y00



BBSY00100505301Y00



BBSY00100505331Y00



chanhvinh.com

chanhvinh.com

BBSY00100505 Series Specification

13 Graph:

BBSY00100505471Y00



BBSY00100505481Y00



BBSY00100505601Y00



BBSY00100505102Y00



BBSY00100505182Y00



BBSY00100505222Y00

