
chanhvinh.com

GNSS Active Patch Antenna

GNSSL1L2182530

Pulse
a YAGEO company



Features:

- *Ultra low noise 30dB amplifiers*
- *Stacked L1 / L2 patch antenna*
- *Single RF input with DC bias*
- *High rejection filters to suppress out of band interference*
- *ESD Protected*
- *For 15dB version use P/N: GNSSL1L2182515*

Applications:

- *GPS, Glonass, Galileo, Beidou, IRNSS*
- *Multiband satellite navigation receivers*
- *L1 and L2 band devices*

Electrical specifications[1] @ 25° C

Antenna type	Nominal Impedance	Polarization	Radiation pattern
Patch	50Ω	RHCP	Directional

Frequency (MHz)	L1: 1561-1602	L2: 1227
Return Loss (dB)	< -10	< -9
Radiating Element Peak Gain (dBi)	>4	>3
Radiating Element Peak Gain (dBic)	>4	>0
Avg. Efficiency (%)	>80	>60
LNA Gain (dB) Typical	28	32
Noise Figure (dB)	1.7 @1575MHz	1.8 @1227MHz
Operating Voltage[2] (VDC)	2.5 - 18	
Current Consumption (mA)	Max. 16	

Mechanical Specifications


Dimension Length x Width x Height (w/o cable)	**Fixing method**	**Antenna Material**	**Connector Type**	**Cable Type**
30mm*30mm*13.09mm / 1.181”x1.181”x.515”	Adhesive 3M RP16	Ceramic+PCBA+cable	I-PEX MHF	Ø1.13mm
Cable Length	**Weight**	**RoHS- Compliant**	**Storage and operating Temperature**	
100mm/3.937”	12 grams	Yes	-40°C to 85°C	

Notes:

1. The product is ESD sensitive, must be handled carefully and strictly according to the ESD requirements.
2. LNA internal voltage stabilized by LDO (Low dropout regulator)

chanhvinh.com

Mechanical Drawing




All dimensions are in mm / inches


chanhvinh.com

Testing Setup

Module is tested on 80*80mm ground plane.




Active Antenna Block Diagram




chanhvinh.com

Return Loss




LNA Out of band rejection




m2: 1.227 GHz 31.64 dB	m1: 1.575 GHz 28.39 dB	m3: 0.617 GHz -54.90 dB	m4: 0.96 GHz -31.05 dB
m5: 1.71 GHz -36.76 dB	m6: 2.7 GHz -47.20 dB	m7: 4.5 GHz -35.52 dB	m8: 7.15 GHz -24.41 dB

chanhvinh.com


LNA Gain




S21 GNSSL1L2
m1: 1.575 GHz 28.76 dB
m2: 1.561 GHz 29.13 dB
m3: 1.602 GHz 28.12 dB



S23 GNSSL1L2
m1: 1.227 GHz 32.52 dB




S21 GNSSL1L2
m1: 1.575 GHz 28.76 dB
m2: 1.227 GHz -19.19 dB
m3: 0.617 GHz -60.90 dB
m4: 0.96 GHz -44.66 dB
m5: 1.71 GHz -34.12 dB




S23 GNSSL1L2
m1: 1.227 GHz 32.52 dB
m2: 1.575 GHz -17.66 dB
m3: 0.617 GHz -61.48 dB
m4: 0.96 GHz -29.55 dB
m5: 1.71 GHz -39.04 dB

LNA Noise Figure




L1 Noise Figure




L2 Noise Figure

chanhvinh.com

Radiating Element Efficiency




L1 Band




L2 Band

Radiating Element Peak Gain (Linear)




L1 Band




L2 Band


Radiation Patterns RHCP (dBic)



L1 RHCP Pattern @1575 MHz



L2 RHCP Pattern @1227 MHz



L2 3D RHCP Pattern @1227 MHz

chanhvinh.com

Reliability Tests

Temperature change	-40℃ to +85 °C, MIL-STD 810G Method 503.5. 1.Room Temperature to -40 °C (2hours) 2.Storage for 2 hours at -40 °C 3. -40 °C to 85 °C (2hours) 4. Storage for 2 hours at 85 °C 5. 85 °C to -40 °C (2hours) 6.Repeat from 2 to 5 for 5 times 7. -40 °C increase to room temperature within 2 hours (Total 44 Hrs) No loss of function after tests.
Storage test	-40°C to +85°C, MIL STD 810G Method 501.5 (high) Method 502.5 (low) 1.Room Temperature to -40°C within 2 hours 2.Storage for 24 hours at -40°C; 3. -40°C to room temperature within 2 hours 4.Room Temperature to +85°C within 2 hours 5.Storage for 24 hours at 85°C; 6. 85°C room temperature within 2 hours(Total 56 Hrs) No loss of function after tests.
Shock test	1.Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen (18 shocks) 2.Peak value: 1,500g's 3.Duration: 0.5ms 4.Waveform: Half si. No loss of function after tests.
Drop test	Drop test (single device) for mounted device, the antenna needs to be fixed to PCB and then assemble PCBA into the covers for the test, please do the test with Armadillo antenna, only need the PCB and top/bottom cover for the tests.
Vibration test	Random vibration input of 60 min/axis, all three perpendicular axis. Transportation frequency 5-500 Hz using Fig 514.6C-I and Table 514.6-II of MIL STD 810G section 514.6, performed only upon customer request., no loss of function after tests.
ESD Test	According to IEC/EN 61000-4-2 Electromagnetic compatibility Test voltage ±2KV, voltage polarity: + and - Discharge times: 3 times per polarity, discharge frequency: 1 time/second

Package

Antennas packed in tray (ESD requirements according to DIN EN 61340-5.1) and carton box

Each antenna wrapped in foam bag
240 PCS/ carton box
Carton box dimensions (MM)：405x300x180

For More Information:
Americas - antennas.us@pulseelectronics.com | Europe – antennas.eu@pulseelectronics.com | Asia – antennas.as@pulseelectronics.com | Questions? +1-800-ANTENNA
Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright , 2020. Pulse Electronics, Inc. All rights reserved.
Company address: Pulse Electronics, a YAGEO Company, 15255 Innovation Drive, Suite #100, San Diego, CA 92128