chanhvinh.com

SMT Power Inductors

Power Beads - PA051XNL, PA121XNL, PA151XNL Series

Pulse
a YAGEO company



- **Current Rating:** *Over 70Apk*
- **Inductance Range:** *72nH to 470nH*
- **Four Package Sizes:**
  - **PA0512/PA1212:** *7.0 x 7.0 x 4.96mm Max*
  - **PA0511/PA1211:** *10.2 x 7.0 x 4.96mm Max*
  - **PA0515:** *11.2 x 11.2 x9.0mm Max*
  - **PA0513/PA1513:** *13.5 x 13.0 x 8.0mm Max*

Electrical Specifications @ 25°C - Operating Temperature -40°C to +130°C [7,8]

Part Number	Inductance @ 0A$_{DC}$ (nH ±20%)	Inductance @ Irated (nH TYP)	Irated [1] (A_{DC})	DCR [2] (mΩ)	Saturation Current [3] (TYP)		Heating [4] Current (A TYP)
					25°C	100°C	
PA0512NL and PA1212NL - 7.0mm x 7.0mm x 4.96mm Max							
PA0512.700NLT	72	72	31	0.32 ±9.4%	58	45	31
PA0512.101NLT	105	102	31		46	38	
PA0512.151NLT	150	134	24		30	24	
PA1212.700NLT	72	72	31	0.46 ±6.5%	58	45	31
PA1212.101NLT	105	102	31		46	38	
PA1212.151NLT	150	134	24		30	24	
PA0511NL and PA1211NL - 10.2mm x 7.0mm x 4.96mm Max							
PA0511.850NLT	85	85	31	0.39 ±7.7%	70+	70	31
PA0511.900NLT	100	100	31		70	65	
PA0511.101NLT	120	120	31		52	42	
PA0511.151NLT	155	150	31		40	36	
PA0511.221NLT	220	176	25		33	25	
PA1211.850NLT *	85	85	31	0.55 ±7.3%	70+	70	31
PA1211.900NLT *	100	100	31		70	65	
PA1211.101NLT	120	120	31		52	42	
PA1211.151NLT	155	150	31		40	36	
PA1211.221NLT	220	176	25		33	25	
PA0515NL - 11.2mm x 11.2mm x 9.0mm Max							
PA0515.221NLT	225	225	35	0.63 ±9.5%	68	59	35
PA0515.271NLT	270	280	35		50	44	
PA0515.321NLT	325	325	35		43	36	
PA0515.471NLT	470	380	23		30	23	

chanhvinh.com

SMT Power Inductors

Power Beads - PA051XNL, PA121XNL, PA151XNL Series

Pulse a YAGEO company

Electrical Specifications @ 25°C - Operating Temperature -40°C to +130°C [7,8]							
Part Number	Inductance @ 0A$_{DC}$ (nH ±20%)	Inductance @ Irated (nH TYP)	Irated [1] (A_{DC})	DCR [2] (mΩ)	Saturation Current [3] (TYP)		Heating [4] Current (A TYP)
					25°C	100°C	
PA0513NL and PA1513NL - 13.5mm x 13.0mm x 8.0mm Max							
PA0513.211NLT	210	210	45	0.32 ±9.4%	71	64	45
PA0513.261NLT	260	260	45		60	55	
PA0513.321NLT	320	285	41		50	45	
PA0513.441NLT	440	363	30		35	30	
PA1513.211NLT	210	210	45	0.53 ±11.3%	71	64	45
PA1513.261NLT	260	260	45		60	55	
PA1513.321NLT	320	285	41		50	45	
PA1513.441NLT	440	363	30		35	30	


Notes:

1. The rated current as listed is either the saturation current or the heating current depending on which value is lower.
2. The nominal DCR tolerance is by design. The nominal DCR is measured from point ⓐ to point ⓑ, as shown below on the mechanical drawing.
3. The saturation current is the typical current which causes the inductance to drop by 20% at the stated ambient temperatures (25°C and 100°C). This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effects) to the component.
4. The heating current is the DC current which causes the part temperature to increase by approximately 40°C. This current is determined by soldering the component on a typical application PCB, and then applying the current to the device for 30 minutes without any forced air cooling.
5. In high volt*time applications, additional heating in the component can occur due to core losses in the inductor which may necessitate derating the current in order to limit the temperature rise of the component. To determine the approximate total losses (or temperature rise) for a given application, the coreloss and temperature rise curves can be used.
6. Pulse complies to industry standard tape and reel specification EIA481.
7. The temperature of the component (ambient plus temperature rise) must be within the stated operating temperature range.
8. For part marking only the PA0513 series has the name 'Pulse' marked on the part. Due to component size, the remaining series' of parts are marked only with the Pulse PN, Date Code and Country of Origin.

* Contact Pulse for availability

Mechanical


PAXXXX.XXXNLT




SUGGESTED PAD LAYOUT

Dimensions: Inches / mm

Unless otherwise specified, all tolerances are: ±.010 / 0,25



Schematic



chanhvinh.com

SMT Power Inductors

Power Beads - PA051XNL, PA121XNL, PA151XNL Series


Pulse a YAGEO company

Dimensions (inches/mm)


Part Number	A (MAX)	B (MAX)	C (MAX)	D (NOM)	E (NOM)	F (NOM)	G (NOM)	H (NOM)	Ao	Bo	Ko	Po	W	Parts/Reel	Weight (grams)
PA0512/PA1212	.276 7,00	.276 7,00	.195 4,96	.060 1,52	.098 2,49	.120 3,05	.080 2,03	.130 3,30	.287 7,29	.290 7,36	.215 5,46	.472 12,00	.630 16,00	1000	0.94
PA0511/PA1211	.400 10,16	.276 7,00	.195 4,96	.060 1,52	.098 2,49	.120 3,05	.080 2,03	.250 6,35	.295 7,49	.405 10,29	.205 5,21	.472 12,00	.945 24,00	1000	1.35
PA0515	.440 11,18	.440 11,18	.354 9,00	.100 2,54	.080 2,03	.100 2,54	.120 3,05	.210 5,33	.453 11,50	.453 11,50	.378 9,60	.945 24,00	.945 24,00	250	4.5
PA0513/PA1513	.530 13,46	.510 12,95	.315 8,00	.100 2,54	.200 5,08	.300 7,62	.125 3,18	.280 7,11	.516 13,10	.539 13,70	.386 9,80	.630 16,00	.945 24,00	400	5.7

PA0512NL & PA1212NL

Inductance vs Current




CoreLoss vs Flux Density




where ΔB = .86 * L(nH) * ΔI

PA0511NL & PA1211NL

Inductance vs Current



CoreLoss vs Flux Density



where ΔB = .57 * L(nH) * ΔI


chanhvinh.com

SMT Power Inductors

Power Beads - PA051XNL, PA121XNL, PA151XNL Series


Pulse a YAGEO company

Temp Rise vs Power Dissipation



Total Power Dissipation (W) = CopperLoss + CoreLoss
CopperLoss = I_{RMS}^2 * R_{DC} (mΩ) / 1000
CoreLoss = (from graph)


Temp Rise vs Power Dissipation




Total Power Dissipation (W) = CopperLoss + CoreLoss
CopperLoss = I_{RMS}^2 * R_{DC} (mΩ) / 1000
CoreLoss = (from table)


Typical Inductance vs Current

PA0513NL / PA1513NL






CoreLoss vs Flux Density



ΔB (gauss) where ΔB = .23 * L(nH) * ΔI

Temp Rise vs Power Dissipation



Total Power Dissipation (W) = CopperLoss + CoreLoss
CopperLoss = I_{RMS}^2 * R_{DC} (mΩ) / 1000 - **CoreLoss** = (from graph)


chanhvinh.com


SMT Power Inductors

Power Beads - PA051XNL, PA121XNL, PA151XNL Series


Typical Inductance vs Current

PA0515NL






CoreLoss vs Flux Density



Temp Rise vs Power Dissipation



For More Information:

Americas - prodinfo_power@pulseelectronics.com | **Europe -** power-apps-europe@pulseelectronics.com | **Asia -** power-apps-asia@pulseelectronics.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2021. Pulse Electronics, Inc. All rights reserved.