chanhvinh.com

Heat Shrink Tubing

RND components

Features

- Thin-walled flexible flame retardant heat-shrink tubing
- Shrink ratio: 2:1
- Good for general insulation, and similar tasks
- Comes in a handy white dispenser box that makes it easy to use and avoid waste
- Excellent chemical and solvent resistance

Specification

Material	Polyolefin
Shrink Ratio	2:1
Shrink Temperature	90 °C
Service Temperature Range	-55 ... 125 °C
Colour	Black, Clear, Green, White, Red, Yellow, Blue, Yellow/Green
Dielectric Strength	>20 kV
Longitudinal Change	0 ± 10 % max.

Product Range

Type	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Reel / Length	Colour
RND 465-01109	1.2	0.6	0.40	15 m	Black
RND 465-01110	1.2	0.6	0.40	15 m	Yellow
RND 465-01111	1.2	0.6	0.40	15 m	Green
RND 465-01112	1.2	0.6	0.40	15 m	White
RND 465-01113	1.2	0.6	0.40	15 m	Clear
RND 465-01114	1.6	0.8	0.45	15 m	Black
RND 465-01115	1.6	0.8	0.45	15 m	Red
RND 465-01116	1.6	0.8	0.45	15 m	Yellow
RND 465-01117	1.6	0.8	0.45	15 m	Clear
RND 465-01118	2.4	1.2	0.45	15 m	Black
RND 465-01119	2.4	1.2	0.45	15 m	Red
RND 465-01120	2.4	1.2	0.45	15 m	Yellow
RND 465-01121	2.4	1.2	0.45	15 m	Clear
RND 465-01122	3.2	1.6	0.45	15 m	Black
RND 465-01123	3.2	1.6	0.45	15 m	Red
RND 465-01124	3.2	1.6	0.45	15 m	Yellow
RND 465-01125	3.2	1.6	0.45	15 m	Blue
RND 465-01126	3.2	1.6	0.45	15 m	Clear
RND 465-01127	4.8	2.4	0.45	10 m	Black
RND 465-01128	4.8	2.4	0.45	10 m	Red
RND 465-01129	4.8	2.4	0.45	10 m	Yellow
RND 465-01130	4.8	2.4	0.45	10 m	Green
RND 465-01131	4.8	2.4	0.45	10 m	Blue
RND 465-01132	4.8	2.4	0.45	10 m	White
RND 465-01133	4.8	2.4	0.45	10 m	Clear

RND is a trademark of Distrelec

chanhvinh.com

Heat Shrink Tubing

RND components

Type	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Reel / Length	Colour
RND 465-01134	6.4	3.2	л⇕пр	10 m	Black
RND 465-01135	6.4	3.2	л⇕пр	10 m	Red
RND 465-01136	6.4	3.2	л⇕пр	10 m	Yellow
RND 465-01137	6.4	3.2	л⇕пр	10 m	Green
RND 465-01138	6.4	3.2	л⇕пр	10 m	Clear
RND 465-01139	9.5	4.8	л⇕пр	10 m	Black
RND 465-01140	9.5	4.8	0.45	10 m	Red
RND 465-01141	9.5	4.8	0.45	10 m	Blue
RND 465-01142	9.5	4.8	0.45	10 m	White
RND 465-01143	9.5	4.8	0.45	10 m	Clear
RND 465-01144	12.7	6.4	0.55	5 m	Black
RND 465-01145	12.7	6.4	0.55	5 m	Red
RND 465-01146	12.7	6.4	0.55	5 m	Yellow
RND 465-01147	12.7	6.4	0.55	5 m	Green
RND 465-01148	12.7	6.4	0.55	5 m	Blue
RND 465-01149	12.7	6.4	0.55	5 m	Clear
RND 465-01150	19.1	9.5	0.55	5 m	Black
RND 465-01151	19.1	9.5	0.55	5 m	Red
RND 465-01152	19.1	9.5	0.55	5 m	Green
RND 465-01153	19.1	9.5	0.55	5 m	Blue
RND 465-01154	19.1	9.5	0.55	5 m	White
RND 465-01155	19.1	9.5	0.55	5 m	Clear
RND 465-01156	25.4	12.7	0.65	5 m	Black
RND 465-01157	25.4	12.7	0.65	5 m	Red
RND 465-01158	25.4	12.7	0.65	5 m	Green
RND 465-01159	25.4	12.7	0.65	5 m	Blue
RND 465-01160	25.4	12.7	0.65	5 m	Clear
RND 465-01161	1.6	0.8	0.45	15 m	Yellow / Green
RND 465-01162	3.2	1.6	0.45	15 m	Yellow / Green
RND 465-01163	4.8	2.4	0.45	10 m	Yellow / Green
RND 465-01164	6.4	3.2	0.45	10 m	Yellow / Green
RND 465-01165	9.5	4.8	0.45	10 m	Yellow / Green
RND 465-01166	12.7	6.4	0.55	5 m	Yellow / Green
RND 465-01186	3.2	1.6	0.45	15 m	Brown
RND 465-01187	4.8	2.4	0.45	10 m	Brown
RND 465-01188	9.5	4.8	0.45	10 m	Brown
RND 465-01189	12.7	6.4	0.55	5 m	Brown
RND 465-01190	19.1	9.5	0.55	5 m	Brown
RND 465-01191	25.4	12.7	0.65	5 m	Brown
RND 465-01192	3.2	1.6	0.45	15 m	Grey
RND 465-01193	4.8	2.4	0.45	10 m	Grey
RND 465-01194	9.5	4.8	0.45	10 m	Grey
RND 465-01195	12.7	6.4	0.55	5 m	Grey
RND 465-01196	19.1	9.5	0.55	5 m	Grey
RND 465-01197	25.4	12.7	0.65	5 m	Grey