chanhvinh.com

SLI-580x/SLA-580x/SLA580x Series

Data Sheet

■ Features


- Viewing angle 2θ 1/2 : 10°

■ Outline




Color Type: U D Y M E B

■ Dimensions



Tolerance : ±0.2
(unit : mm)

■ Recommended Solder Pattern



(unit : mm)

■ Specifications

Part No.	Chip Structure	Emitting Color	Absolute Maximum Ratings (Ta=25°C) Power Dissipation P_D(mW)	Forward Current I_F(mA)	Peak Forward Current I_{FP}(mA)	Reverse Voltage V_R(V)	Operating Temp. T_{opr}(°C)	Storage Temp. T_{stg}(°C)	Electrical and Optical Characteristics (Ta=25°C) Forward Voltage V_F Typ. (V)	I_F (mA)	Reverse Current I_R Max. (μA)	V_R (V)	Peak Wavelength λp Typ. (nm)	I_F (mA)	Luminous Intensity I_V Min. (mcd)	Typ. (mcd)	I_F (mA)
SLI-580UT	AlGaInP	Red	125	50	200*2	9	-30～+85	-40～+100	1.9	20	100	9	630	20	2000	5000	20
SLI-580DT		Orange											611		1350		
SLI-580YT		Yellow											591				
SLA-580MT	GaP	Yellowish green	75	25	60*1	4	-25～+85	-30～+100	2.3		10	4	563		200	470	

Part No.	Chip Structure	Emitting Color	Absolute Maximum Ratings (Ta=25°C) Power Dissipation P_D(mW)	Forward Current I_F(mA)	Peak Forward Current I_{FP}(mA)	Reverse Voltage V_R(V)	Operating Temp. T_{opr}(°C)	Storage Temp. T_{stg}(°C)	Electrical and Optical Characteristics (Ta=25°C) Forward Voltage V_F Typ. (V)	I_F (mA)	Reverse Current I_R Max. (μA)	V_R (V)	Dominant Wavelength λD Typ. (nm)	I_F (mA)	Luminous Intensity I_V Min. (mcd)	Typ. (mcd)	I_F (mA)
SLA580ENT	InGaN	GREEN	120	30	100*2	5	-20～+80	-30～+100	3.3	20	100	5	527	20	6100	27000	20
SLA580BNT		BLUE											470		1350	4000	

*1 : Duty1/5, 200Hz,*2 : Duty1/10, 1kHz

©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■Electrical Characteristics Curves

Reference

Fig.1 Forward Current - Forward Voltages




Fig.2 Luminous Intensity - Atmosphere Temperature




Fig.3 Luminous Intensity - Forward Current





Fig.4 Derating




©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■Electrical Characteristics Curves


Reference

Fig.1 Forward Current - Forward Voltages




FORWARD VOLTAGE : V_F [V]

Fig.2 Luminous Intensity - Atmosphere Temperature




ATMOSPHERE TEMPERATURE : Ta [ºC]

Fig.3 Luminous Intensity - Forward Current



FORWARD CURRENT : I_F [mA]

Fig.4 Derating



AMBIENT TEMPERATURE : Ta [ºC]


©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■Electrical Characteristics Curves


Reference

Fig.1 Forward Current - Forward Voltages




FORWARD VOLTAGE : V_F [V]

Fig.2 Luminous Intensity - Atmosphere Temperature




ATMOSPHERE TEMPERATURE : Ta [°C]

Fig.3 Luminous Intensity - Forward Current



FORWARD CURRENT : I_F [mA]

Fig.4 Derating




AMBIENT TEMPERATURE : Ta [°C]


©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■Viewing Angle

Reference





©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■Rank Reference of Brightness*

*Measurement tolerance:±10%

Red(U)

(Ta=25ºC, I_F=20mA)

Rank	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT
Iv (mcd)	47～68	68～100	100～150	150～220	220～330	330～470	470～680	680～1000	1000～1500	1500～2200	2200～ 3300	3300～4700	4700～6800	6800～10000
SLI-580UT														

Orange(D)

(Ta=25ºC, I_F=20mA)

Rank	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT
Iv (mcd)	47～68	68～100	100～150	150～220	220～330	330～470	470～680	680～1000	1000～1500	1500～2200	2200～ 3300	3300～4700	4700～6800	6800～10000
SLI-580DT														

Yellow (Y)

(Ta=25ºC, I_F=20mA)

Rank	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT
Iv (mcd)	47～68	68～100	100～150	150～220	220～330	330～470	470～680	680～1000	1000～1500	1500～2200	2200～ 3300	3300～4700	4700～6800	6800～10000
SLI-580YT														

Yellowish Green(M)

(Ta=25ºC, I_F=20mA)

Rank	XE	XF	XG	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT
Iv (mcd)	47～68	68～100	100～150	150～220	220～330	330～470	470～680	680～1000	1000～1500	1500～2200	2200～ 3300	3300～4700	4700～6800	6800～10000
SLA-580MT														

Green(E)

(Ta=25ºC, I_F=20mA)

Rank	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT	XU	XV	XW
Iv (mcd)	135～240	200～360	300～520	420～750	610～1100	900～1650	1350～2400	2000～ 3600	3000～5200	4200～7500	6100～11000	9000～16500	13500～24000	20000～36000
SLA580ENT														

Blue(B)

(Ta=25ºC, I_F=20mA)

Rank	XH	XJ	XK	XL	XM	XN	XP	XQ	XR	XS	XT	XU
Iv (mcd)	135～240	200～360	300～520	420～750	610～1100	900～1650	1350～2400	2000～ 3600	3000～5200	4200～7500	6100～11000	9000～16500
SLA580BNT												

©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■Part No. Construction

*"-"will be taken out for emitting color B/E series.

Special Code will be applied for Emitting color B/E series.

Chromaticity rank (for white LED)

Rank sign (Brightness Rank)*

S	L	I	–	5	8	0	U		T		T	3	2		XS
Series name				Package type			Emitting Color		Resin Color		Taping Specification				

SLA	1-Die Circular Type High Brightness LED Lamps
SLI	1-Die Circular Type Low Current High Brightness LED Lamps
SLR	1-Die Circular Type LED Lamps
SLD	1-Die Oval Type High Brightness LED Lamps

V	Red
U	Red
U2	Red
D	Orange
Y	Yellow
Y2	Yellow
M	Yellowish green
P	Green
E	Green
B	Blue

R	<Red>DiffusedColored
U	<Orange>DiffusedColored
Y	<Yellow>DiffusedColored
G	<Yellowish green>DiffusedColored
C	Transparent Colored
RC	
T	Transparent Coloreless

3F	1-Element straight bulk
T□□	See Taping specifications

*Concerning the Brightness rank.
*Please refer to the rank chart above for luminous intensity classification.
*Part name is individual for each rank.
*When shipped as sample,the part name will be a representative part name.
General products are free of ranks.
Please contact sales if rank appointment is needed.

©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■ATTENTION POINTS IN HANDLING

Visual light emitting diode does not contain reinforcement materials such as glass fillers.
Therefore if sudden thermal and mechanical shock are given, destruction or inferiority of luminous intensity may occur. Please take care of the handling.

■FIXATION METHOD

1． ATTENTION POINTS

(1) Please do not give excessive heat over storage temperature to resin.
In case that the product has to be heated in oven for the glue fixing of surface mount parts, this LED should be mounted after the glue fixing.


(2) Please avoid stress to resin at high temperature.

2． TERMINATION PROCESSING

(1) In case of termination processing, please fix the termination


(2) Processing position, and process the reverse side of LED body.
If stress is given during processing, It may cause non-lighting failure.

(3) Please process before soldering.




3． ASSEMBLY ON PC BOARD

(1) In case of soldering on PCB, If the operation is done with stress, it may cause non-lighting failure during soldering or using. Please design the through-holes of PCB suitable for lead pins space or lead pins space after forming to avoid the physical stress on resin.



(2) Using spacer between LED’s body and PCB is recommended.
In case of direct mount on PCB(SLR/SLI-343 series), please take care about clinch of LED pins to avoid the remained stress and solder heat stress.
Enough evaluation is requested before deciding assembly and soldering conditions.
Please consult with us if any problems in the evaluation stage.



©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

4．SOLDERING（Sn-3Ag-0.5Cu）

(1) Please make soldering rapidly under the following temperature and time conditions.
(2) Please avoid stress to LED lamp during soldering.
(3) In case of double peak flow soldering, the temperature gap during 1st and 2nd soldering to be less than 100 degree C.

<Recommendable soldering conditions>

ARTIICLE		SOLDERINGTEMP	OPERATION TIME	Remarks
Soldering Dip	Pre-heat	Max. 100℃	60sec Max.	–
	Soldering Bath	Max. 265℃	5sec Max.	In case of double peak flow soldering, the operation time is counted from the beginning of 1st peak to the end of 2nd peak.
Soldering Iron		Max. 400℃	3sec Max.	The iron should not touch the LED's body.

5．CLEANING

In case of cleaning, some solvents may cause damage of resin or cause non-lighting failure, so please check the solvent before actual use.
The recommendable cleaning solvent is alcoholic one such as isopropyl alcohol.


<RECOMMENDABLE CLEANING CONDITIONS>

METHOD	CONDITIONS
Cleaning by solvent	Temperature of solvent : Max. 45℃ Immersion time : Max. 3min
Cleaning by solvent	Ultrasonic out : Max. 15W/Liter Cleaning time : Max. 3min


6．RECOMMENDABLE ROUND PATTERN

Round pattern depends on the material PCB, density and circuit arrangement.
Our recommendation is as follow：


<2 lead pin type>



<3 lead pin type/2.5mm pitch>



＜3 lead pin type/2.0mm pitch>



■ATTENTION ON STORAGING

Storage in dry box is most desirable, but if it is not possible, we recommend following conditions.

<RECOMMENDABLE STORAGE CONDITIONS>

ARTICLE	Temperature	Humidity	Expiration Date
CONDITIONS	5～30℃	Max.60%RH	Within 1 year

Poor storage conditions may cause some failure as bellow.

(1) Lead pins may corrode if it is stored in the environment of high temperature and humidity and lead to defective soldering.
(2) In case of soldering after LED's body absorb moisture highly, destruction or inferiority of luminous intensity may occur.

©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

■APPLICATION METHOD

1. Precaution for Drive System and Off Mode

・Design the circuit without the electric load exceeding the ABSOLUTE MAXIMUM RATING that applies on the products.

・If drive by constant voltage, it may cause current deviation of the LED and result in deviation of luminous intensity, so we recommend to drive by constant current. (Deviation of VF Value will cause deviation of current in LED.)

・Furthermore, for off mode, please do not apply voltage neither forward nor reverse. Especially, for the products with the Ag-paste used in the die bonding, there's high possibility to cause electrc migration and result in function failure.

2. Operation Life Span

There's possibility for intensity of light drop according to working conditions and environments (applied current, surrounding temperature and humidity, corrosive gases), please call our Sales staffs for inquiries about the concerned application below.

(1) Longtime intensity of light life

(2) On mode all the time

3. Usage

The Product is LED. We are not responsible for the usage as the diode such as Protection Chip, Rectifier, Switching and so on.

■OTHERS

1. Surrounding Gas

Notice that if it is stored under the condition of acid gas (chlorine gas, sulfured gas) or alkali gas (ammonia), it may result in low soldering ability (caused by the change in quality of the plating surface) or optical characteristics changes (light intensity, chrominance) and change in quality of die bonding (Ag-paste) materials. All of the above will cause function failure of the products. Therefore, please pay attention to the storage environment for mounted product (concern the generated gas of the surrounding parts of the products and the atmospheric environment).

2. Electrostatic Damage

The product is part of semiconductor and electrostatic sensitive, there's high possibility to be damaged by the electrostatic discharge.

Please take appropriate measures to avoid the static electricity from human body and earthing setting of production equipment. The resistance values of electrostatic discharge (actual values) are different varies with products, therefore, please call our Sales staffs for inquiries.

3. Electromagnetic Wave

Applications with strong electromagnetic wave such as, IH cooker, will influence the reliability of LED, therefore please evaluate before using it.

©2023 ROHM Co., Ltd. All rights reserved

chanhvinh.com

Notes

1) The information contained herein is subject to change without notice.

2) Before you use our Products, please contact our sales representative and verify the latest specifications.

3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors.
Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Poducts beyond the rating specified by ROHM.

4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.

6) The Products are intended for use in general electronic equipment (i.e. AV/OA devices, communication, consumer systems, gaming/entertainment sets) as well as the applications indicated in this document.

7) The Products specified in this document are not designed to be radiation tolerant.

8) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, servers, solar cells, and power transmission systems.

9) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.

10) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.

11) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.

12) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.

13) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.

14) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.

ROHM SEMICONDUCTOR

Thank you for your accessing to ROHM product informations.
More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/

© 2015 ROHM Co., Ltd. All rights reserved.

chanhvinh.com

General Precaution

1. Before you use our Products, you are requested to carefully read this document and fully understand its contents. ROHM shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any ROHM's Products against warning, caution or note contained in this document.

2. All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the latest information with a ROHM sales representative.

3. The information contained in this document is provided on an "as is" basis and ROHM does not warrant that all information contained in this document is accurate and/or error-free. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting from inaccuracy or errors of or concerning such information.

© 2015 ROHM Co., Ltd. All rights reserved.