

chanhvinh.com



PIN OUT


CN1 (568B)			CN2 (568B)
WHITE-ORANGE	1	1	WHITE-ORANGE
ORANGE	2	2	ORANGE
WHITE-GREEN	3	3	WHITE-GREEN
GREEN	6	6	GREEN
BLUE	4	4	BLUE
WHITE-BLUE	5	5	WHITE-BLUE
WHITE-BROWN	7	7	WHITE-BROWN
BROWN	8	8	BROWN



NOTE:

1. Fluke Channel Test ISO 11801 channel Class Ea
2. RoHS2.0 AND REACH compliant
3. Electrical test:100% open short & miss wire test;
4. OPERATING TEMPERATURE:-10℃ ~ 60℃
5. Print word: CAT6A U/UTP 4x2x32AWG/7 LSZH ISO11801 & EN50173 & ANSI/TIA568C.2

ITEM No.	LENGTH
21.15.0980	500±30mm
21.15.0981	1000±30mm
21.15.0984	1500±50mm
21.15.0982	2000±50mm
21.15.0983	3000±70mm
21.15.0985	5000±70mm



MATERIAL LIST

NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
③	CABLE	CAT.6A U/UTP CABLE (32AWG BC*1P)*4+JACKET:LSZH/WHITE,OD:3.4±0.2mm	1	
②	Over mold	48P PVC/WHITE	2	
①	Plug	RJ45 8P8C Unshielded Plug, PIN GOLD PLATED 3u", TRANSPARENT	2	

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		NEW	2018-07-20	A

DESC.	ROLINE Cat. 6A UTP Patch Cord, LSOH, Slim, White

SECOMP