chanhvinh.com

Datasheet

RS PRO Piezo Audio Transducer

EN RS Stock No: 181-2758



A. SCOPE


This specification applies piezo audio indicator, 1812688

B. SPECIFICATION

No.	Item	Unit	Specification	Condition
1	Resonant frequency	KHz	2.8 ± 0.5	
2	Operating Volt. range	AC/DC	60~ 250	
3	Current consumption	mA	MAX 16	at 220VDC/AC
4	Sound pressure level	dB	MIN 82	at 30cm/220VDC/AC
5	Rated Voltage	VDC	220	
6	Tone		Slow Pulse (1.2Hz±20%)	at 220VDC /AC
7	Operating temp.	℃	-30 ~ +85	
8	Storage temp.	℃	-40 ~ +95	
9	Dimension	mm	φ42.5.x H42.0	See appearance drawing
10	Weight (MAX)	gram	56.0	
11	Material		ABS UL-94 1/16” HB HIGH HEAT（BLACK）	
12	Terminal		Pin type (/Plating Sn)	See appearance drawing
13	Environmental Protection Regulation		RoHS	
14	Storage life	month	6	6 months preservation at room temp. (25±3℃), Humidity40%

chanhvinh.com


C. APPEARANCE DRAWING



Tol : ± 0.5
Unit : mm

D. MEASURING METHOD

S.P.L. Measuring Circuit




Mic : RION S.P.L meter UC30 or equivalent

E. MECHANICAL CHARACTERISTICS

No.	Item	Test Condition	Evaluation standard
1	Solderability	Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of +270±5℃ for 3±1 seconds. .	90% min. lead terminals shall be wet with solder. (Except the edge of terminal)
2	Soldering Heat Resistance	Lead terminal are immersed up to 1.5mm from sounder's body in solder bath of +300±5℃ for 3± 0.5 seconds or +260±5℃ for 10±1 seconds.	No interference in operation
3	Terminal Mechanical Strength	The force 10 seconds of 9.8N (1.0kg) is applied to each terminal in axial direction.	No damage and cutting off
4	Vibration	Buzzer shall be measured after being applied vibration of amplitude of 1.5mm with 10 to 55hz band of vibration frequency to each of 3 per-pendicular directions for 2 hours.	The value of oscillation frequency/ current consumption should be in 10% compared with initial ones .The SPL should be in ± 10dB compared with initial one.
5	Drop test	**The part only shall be dropped from a height of 75cm onto a 40mm thick wooden board 3 times in 3 axes (X.Y.Z). (a total of 9 times).**	

F. ENVIRONMENT TEST

No.	Item	Test Condition	Evaluation standard
1	High temp. test	After being placed in a chamber at +95℃ for 240 hours	Being placed for 4 hours at +25℃, buzzer shall be measured. The value of oscillation frequency/ current consumption should be in±10% compared with initial ones .The SPL should be in±10dB compared with initial one.
2	Low temp. test	After being placed in a chamber with –40℃for 240 hours	
3	Humidity test	After being placed in a chamber at +40℃ and 90±5% relative humidity for 240 hours	
4	Temp. cycle test	The part shall be subjected to 5 cycles. One cycle shall be consist of：	

G. RELIABILITY TEST

No.	Item	Test condition	Evaluation
1	Operating life test	1.Continuous life test 48 hours continuous operation at +70℃ with rated voltage applied. 2.Intermittent life test A duty cycle of 1 minute on, 1 minutes off, a minimum of 5000 times at room temp.(+25±2℃)and rated voltage applied. .	Being placed for 4 hours at +25℃, buzzer shall be measured. The value of oscillation frequency/ current consumption should be in ±10% compared with initial ones .The SPL should be in ±10dB compared with initial one. .

TEST CONDITION.

Standard Test Condition： a) Temperature：+5 ~ +35℃ b) Humidity：45-85% c) Pressure：860-1060mbar

Judgement Test Condition： a) Temperature：+25 ± 2℃ b) Humidity：60-70% c) Pressure：860-1060mbar

chanhvinh.com