chanhvinh.com

ENGLISH

Instruction Data sheet

DIGITAL PROCESS INDICATOR

Stock Number: 1981166



77 x 35 DIN Size
Digital Process Indicator

- 4 Digits Display
- Easily adjustable from front panel
- Between -1999 and 9999 display adjustment scale
- Adjustable decimal point
- Selectable universal process Input
  (0-10V⎓ , 0-1V⎓, 0-60mV⎓, 0-20mA ⎓, 4-20mA ⎓)
- Adjustable input filter
-Minimum and maximum measured values in the memory storage
-Maximum or minimum measurement value can be shown continuously on the display
-User can be adjust device's reading value for selected input type
-Alarm output
-Relay or SSR driver output (It must be determined in order.)
-Adjustable alarm set value from front panel
-Programming mode password protection

chanhvinh.com

ENGLISH

Specifications

Input
Configurable Universal process input (V, mA)

Output
None

Environmental Rating and Physical Specification
Storage / Operating Temperature: -40 °C to +85 °C / 0 °C to +50 °C
Storage / Operating Humidity: 90 % max. (None condensing)
Protection Class : IP65 at front, IP20 at rear.

Supply Voltage
10 - 30 Vdc

Dimensions
77x35mm

Electrical Wirings

