chanhvinh.com

Internal

FEATURES

RS PRO ATEX Screw Plug, Nylon, Without Locknut

RS Stock No.: 2116793, 2116795, 2116794



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

RS PRO ATEX Screw Plug, Nylon, Without Locknut

Product Description

Suitable for use in Zones 1, 2, 21, 22

General Specifications

Material:	PA (NYLON), UL94V-2
O-Ring:	Silicone Rubber
Color:	Black (RAL9005)
Working temperature:	-20 to 80 degree centigrade
Flammability rating:	UL94V-2
Marking:	Ex eb Ⅱ C Gb/ Ex tD A21 IP68
Protection rating:	IP68

Approvals

Declarations	MFR Declaration of Conformity
Hazardous Area Certification	ATEX / IECEx
Standards Met	

RS PRO ATEX Screw Plug, Nylon, Without Locknut

Similar Products

RS Aricle No. (will be replaced by RS new Art NO. later)	Thread Size	Material	GL mm	H mm	W mm	Color	IP Rating	Min. Operating Temp.	Max. Operating Temp.	Locknut Included
2116793	M20x1.5	PA, Silicone Rubber	9	13	25	Black	IP68	-20°C	+80°C	No
2116794	M25x1.5	PA, Silicone Rubber	10.5	15.5	30	Black	IP68	-20°C	+80°C	No
2116795	M40x1.5	PA, Silicone Rubber	11.5	16	46	Black	IP68	-20°C	+80°C	No

