Indicators

Features

- Bezel finish: Stainless Steel 316L.
- Flush chamfered bezel style.
- Voltage: 12 to 24V AC/DC.
- Termination: 200mm long wires, 20 AWG
- Sealing: IP67 and IP69K.
- Supplied with fixing nut, spring washer and O ring panel seal.
- Ø25 mm panel mount

RS PRO Indicators

RS Stock No.: 2538512



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Indicators

Product Description

Panel mount LED indicators with 18.2 mm coloured Fresnel lens with above panel sealing to IP67 & IP69K.

TYPICAL APPLICATIONS

- Professional Electrical Appliances
- Communications systems.
- Civil engineering and off-highway vehicles.
- Oil & Gas.
- Food and Beverage.
- Security.
- Machine Tools.
- Process Controls.

General Specifications

Light Output Colour	Blue
Lamp Type	LED
Termination Type	200mm Wires
Type	Panel Mount Indicator
Bezel Style	Chamfer
Bezel Colour	Stainless Steel
Intensity	2000 mcd
Type Of Illumination	Fixed Light
LED Colour	Blue
Viewing Angle	60°
Life Expectancy	100000hours
Applications	Professional Electrical Appliances
Operating Humidity	45 to 85%
Brightness	2000 mcd

Electrical Specifications

Voltage Rating	12 to 24V AC/DC
Current Rating	30mA
Rectifier	Half Wave
Voltage Tolerance	10%
Insulation Resistance	4000 MΩ at 500 VDC
Maximum Power Dissipation	55mW
Wavelength	450 nm
Weight	35g

chanhvinh.com

Indicators

Mechanical Specifications

Mounting Hole Size	25mm
Length	41.5mm
Shape	Round
Lamp Size	18.2mm

Operation Environment Specifications

Temperature Rating	-40 to +85°C (-40 °F to +185 °F)

Protection Category

IP Rating	IP67 & IP69K

Approvals

Compliance/ Certifications	UL
Declarations	EN60529