chanhvinh.com

FEATURES

- Material: Polyamide with nickel-plated brass thread
- Colour: Black (RAL 9005)
- Flame-retardant: V2(UL94)
- Protection degree: IP68
- Performance: Self-extinguishing, free of halogen, phosphor and cadmium, passed RoHS
- Fit with conduit size: AD28.5

RS PRO Conduit Connector

RS Stock No.: 2650011



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Conduit Connector

Product Description

- *Connecting with the plastic conduits to protect the cables against dust and water.*
- *Widely used in industry such as machine building, electric equipment, electric control system, etc.*
- *Easy to install and disassemble, extremely to save time.*

General Specifications

Conduit Connector Type	Straight
Material	Polyamide with Nickel-Plated Brass Thread
Colour	Black
Coating Material	Uncoated
Resistant To	UV
Packing	4 Pcs / Pack
Thread Type	Metric / Male
Thread Details	M25

Conduit Connector

Mechanical Specifications

Thread Size	M25×1.5
Fits to Conduit Size	AD28.5
Thread Outer Diameter	25mm
Thread Length	13mm
Aperture	18mm
Outer Diameter of the Connector	37mm
Total length	52mm
Wrench size	39mm
Weight Per Pieces	44.25g/pcs
Weight Per Pack	177g/pack
Volume Per Pack(Length*Width*Height)	(L)230*(W)160*(H)60mm

Operation Environment Specifications

Maximum Operating Temperature	+100°C
Minimum Operating Temperature	-40° C

Protection Category

IP Rating	IP 68

Approvals

Compliance/Certifications	CE / UL
Standards Met	ROHS 2.0 Directive 2011/65/EU,REACH