chanhvinh.com

Pneumatic Quick Connect Couplings

Features

- Maximum operating pressure is 35 bar.
- Operating temperature range -20°C to +100°C.
- Material: Brass / Steel with Nickel Plated Finish
- Single Shut Off (One side is with valve)
- Flow 660 l/min
- British Profile DN5.5
- Compatible with:

  TST SWING COUPLING P

  PCL 60

  PARKER - RECTUS 19

RS PRO Pneumatic Quick Connect Coupling

RS Stock No.: 0325502



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

Pneumatic Quick Connect Couplings

Product Description

RS PRO Series 19 Quick Connect Couplings

Pneumatic quick-connect coupling connectors are found across industry in pneumatic systems as diverse as robotic assembly lines and other equipment.

- Maximum operating pressure is 35 bar.
- Operating temperature range -20°C to +100°C.
- Material: Brass / Steel with Nickel Plated Finish
- Single Shut Off (One side is with valve)
- Flow 660 l/min
- British Profile DN5.5
- Compatible with:
  TST SWING COUPLING P
  PCL 60
  PARKER - RECTUS 19


Specifications

Manufacturer Series	019
Coupling Type	Quick Connect Coupling Plug
Connection Standard	DN 5.5 British Profile
Connection Standard Compatible With	TST SWING COUPLING P; PCL 60; PARKER-RECTUS 19
Minimum Operating Temperature	-20°C
Maximum Operating Temperature	+100°C
Maximum Operating Pressure	35bar
Flow	660 l/min
Flow Direction & Sealing	Through Type Coupling
Material	Steel
Finish	Nickel Plated
Connection Type	Hose Barb
Thread Size	N/A
Thread Standard	N/A
Thread Gender	N/A
Coupling Gender	Male
Threaded Connection	N/A
Seal material	N/A
Hose Barb Connection	13 mm


Pneumatic Quick Connect Couplings

Specifications


Plug Profile Serie 019



Dimensions (mm)		
SW	L	ØD
-	58	15



Materials



Material Code


A = Steel Nickel Plated

B = Steel Nickel Plated


C = Brass Nickel Plated

S = Steel Nickel Plated

Air



Water



Series 19 Quick Connect Couplings

0 - 35 bar (0-508 PSI)	-20° to + 100°C (NBR) -4° to + 212°F	Shut Off Type	
OM 300 - 00750 OM 100 - 01000 OM 250 - 00500	FLOW 660 lt/min	DN 5.5 mm	