chanhvinh.com

FEATURES

- Maximum operating temperature of 105°C
- A voltage rating of 600/1000V
- Single core cable design

RS PRO Black Single Core x 16.0sqmm (Class 6 PCW), HRPVC Insulated, 600/1000V, Tri-Rated

RS Stock No.: 760-8727



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price

Tri-rated Cable

Product Description

From RS PRO, comes a range of high quality and great value Tri-rated cables. Manufactured with a premium annealed copper conductor and insulated with PVC (Polyvinyl Chloride), these Tri-rated cables are a fantastic solution for use in control panels and other types of electrical equipment.

General Specifications

Type	Tri-rated
Tri-rated	Yes
Sheath Colour	Black
Fire Behaviour	Flame Retardant
Application	Electrical cabinets, Industrial electrical installations, Small electronic devices, Relay and instrumentation panels, Control metering, Motor starters

Electrical Specifications

Voltage Rating	600/1000V
Current Rating	100A
Conductor Material	462/0.20mm Plain Annealed Copper (Class 5 to IEC 60228)
Insulation Material	HRPVC (Type TI3 to BS EN 50363)
Conductor Resistance	1.21 Ω/km @ 20°C (Maximum)

Mechanical Specifications

Length	100m
Cross Sectional Area	16mm^2
Outer Diameter	9.2mm
American Wire Gauge	6
Core Strands	126/0.4mm
Size of Strands	0.4mm
Insulation Wall Thickness	1.60mm (Nominal)
Diameter Over Insulation	Lower Limit: 6.70mm; Upper Limit: 9.00mm

chanhvinh.com

Operation Environment Specifications

Temperature Range	-15 to +105°C

Approvals

Compliance/Certifications	UL & CSA
Standards Met	UL 1283 & CSA Type TEW & BS 6231 Type CK