chanhvinh.com

ENGLISH

Datasheet

Switchgear Cable

8114429 8114501
8114431 8114491
8114435 8114504
8114438 8114508
8114444 8114517



22OCT15

Cable Data Sheet

Insulation: PVC (Type TI1 to BS EN 50363)
Insulation Radial Thickness: 0.80mm
Diameter Over Insulation:3.60mm (Maximum)

Voltage Rating: 600/1000V
Conductor Resistance: 13.3 Ω/km @ 20°C (Nominal)
Cable Weight: 22.50 kg/km (Nominal)
Standard:BS 6231:2006

TECHNICAL INFORMATION

Conductors:	Plain annealed copper, Class 5 to BS EN 60228.
Insulation:	Heat Resisting PVC.
Voltage Rating:	600V between conductor and earth, 1000V between conductors.
Max. Conductor Temp:	105°C in air, 60°C in oil.
Min. bend radius:	6 x overall diameter.

AWM Size	Size (mm²)	Max diam of wires in conductor mm	Maximum resistance at 20°C Ω/Km	UL Style	Nominal R/T(mm)	Nominal Diam (mm)	Current Rating (A)	Weight (Kg/km)
22	0.5	0.21	39.0	1015	0.8	2.6	11	11
20	0.75	0.21	26.0	1015	0.8	2.8	14	14
18	1	0.21	19.5	1015	0.8	3	17	17
16	1.5	0.26	13.3	1015	0.8	3.3	21	22
14	2.5	0.26	7.98	1015	0.8	3.7	30	33
12	4	0.31	4.95	1015	0.8	4.3	41	49
10	6	0.31	3.30	1015	0.8	5.1	53	71
8	10	0.41	1.91	1028	1.2	6.8	75	124
6	16	0.41	1.21	1283	1.58	9.2	100	199
4	25	0.41	0.78	1283	1.58	10.6	136	290
2	35	0.41	0.554	1283	1.58	11.6	167	387
1	50	0.41	0.386	1284	2.1	14.4	190	570
2/0	70	0.51	0.272	1284	2.1	16.5	240	781
3/0	95	0.51	0.206	1284	2.1	18.7	300	1025
4/0	120	0.51	0.121	1284	2.1	20	340	1280

Current ratings are based on a conductor operating temperature of 85°C and an ambient air temperature of 45°C and are for a single panel wire in free air.

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.