chanhvinh.com

ENGLISH

Datasheet

RS Pro 6 Core Security Cable 0.19 mm² CSA, Polyvinyl Chloride PVC Sheath, 100m

RS Stock No: **820-0182**



Product Details

RS Pro 6-core security cable of 100 m, has grade 1 tinned annealed copper conductors for enhanced conductivity. This 0.19 mm² CSA cable comes with white PVC sheath and insulation to provide high flexibility. The cable meets BS EN 50363-4-1:2005, BS 7655-4.2:2000 standards.

Features and Benefits

- 7 strands
- Grade 1 tinned annealed copper conductors
- PVC insulated
- Lead and tin free
- White PVC sheath
- Easy to strip
- Flexible

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.

chanhvinh.com

ENGLISH

Specifications:

Bedding Material	PVC
Cable Shape	Multicore
Conductor Material	Tinned Annealed Copper
Conductor Resistance	92 Ω/km
Core Strands	7/0.19 mm
Current Rating	1 A per Core
Insulation Material	PVC
Jacket Ripcord	Yes
Maximum Operating Temperature	+70°C
Minimum Operating Temperature	-50°C
Number of Cores	6
Number of Strands	7
Operating Temperature Range	-50 to +70°C
Outer Diameter	4.9 mm
Reel Length	100 m
Screened/Unscreened	Unscreened
Sheath Colour	White
Sheath Material	PVC
Size of Strands	0.19 mm
Standards Met	BS EN 50363-4-1; BS4737
Voltage Rating	50 V
Minimum Insulation Resistance	50 MΩ/Km

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.

chanhvinh.com

ENGLISH

Construction

7 Strands of Grade 1 tinned annealed copper conductors insulated with coloured PVC, lead and tin free BS EN 50363-4-1:2005 Grade TI 1 assembled in a compact circular formation and sheathed overall with white PVC, lead and tin free BS 7655-4.2:2000 Grade Type 6.

Overall Diameter

4 Core 3.5mm +/- 5%

6 Core 4.9mm +/- 5%

8 Core 4.5mm +/- 5%

Colour Coding of Cores

4 Core : red, yellow, blue, black

6 Core : red, yellow, blue, black, white, green

8 Core : red, yellow, blue, black, white, green, brown, orange

Voltage Rating : 50 V

Current Rating : 1 amp per core

Operating Temprature : -50 to +70 degrees C

Conductor Resistance : < 92 Ohms per Km exceeding the requirements of BS4737

Minimum Insulation Resistance : 50m Ohms per Km

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.