chanhvinh.com

ENGLISH

Stock No: 827-4206
RS Pro SY Control Screened Cable, 5 Core



SY cables are number coded control and connecting cables for flexible use and fixed installation for medium mechanical use. They are for use in dry, damp and wet rooms. They may only be installed outdoors with UV observation of the temperature range. At room temperature it is generally resistant against acids, caustics solutions and certain oils. SY cables are used as supply and interconnecting cable for controlling machine tools, production lines, control equipment on conveyors, also for use in measuring regulating and computer units. Suitable for free movement without forced guidance and tensile stress. The braiding of galvanised steel wires are an additional mechanical protection.

Technical data:

Conductor	: Bare copper, fine wire strand in accordance to IEC 60 228 that is VDE 0295, class 5
Core insulation	: PVC compound TI1 in accordance to VDE 0207
Identification	: In acc. To VDE 0293, black cores with white numbers with or without green/yellow ground conductor
Inner sheath	: PVC compound TM2 in acc. to VDE 0207
Braid	: Galvanised steel wire braid
Outer sheath	: Transparent PVC compound TM2 in acc. To VDE 0207
Nominal voltage	: 300/500 V
Test voltage	: 3,000 V ac
Temperature range	: For flexible use -5 up to +70° maximum conductor temperature Fixed installation -40 up to +80° maximum conductor temperature
Minimum bending radius	: Fixed installation 12.5 x cable diameter
Flame retardant	: In acc. to IEC 60 332.1 resp. VDE 0472 part 804
EC directive	: This cable confirms to ECD 73/23/EEC (low voltage directive)

chanhvinh.com

Specifications:

Description	Number of Cores x Cross Sectional Area (mm^2)	Outer Diameter (mm)	Weight Kg/Km
Cable, SY, 3 Core, 2.5mm, 50M	3 x 2.5	10.6	206
Cable, SY, 4 Core, 2.5mm, 50M	4 x 2.5	11.5	260
Cable, SY, 5 Core, 2.5mm, 50m	5 x 2.5	12.6	307
Cable SY, 7 Core, 2.5mm, 50M	7 x 2.5	13.9	374
Cable SY, 3 Core, 0.75mm, Per M	3 x 0.75	7.9	113
Cable, SY, 4 Core, 0.75mm, Per M	4 x 0.75	8.5	129
Cable, SY, 5 Core, 0.75mm, Per M	5 x 0.75	9.2	148
Cable, SY, 7 Core, 0.75mm, Per M	7 x 0.75	9.9	174
Cable, SY, 3 Core, 1mm, Per M	3 x 1	8.3	125
Cable, SY, 4 Core, 1mm, Per M	4 x 1	8.9	145
Cable, SY, 5 Core, 1mm, Per M	5 x 1	9.6	168
Cable, SY, 7 Core, 1mm, Per M	7 x 1	10.4	144
Cable, SY, 3 Core, 1.5mm, Per M	3 x 1.5	9	151
Cable, SY, 4 Core, 1.5mm, Per M	4 x 1.5	9.7	176
Cable, SY, 5 Core, 1.5mm, Per M	5 x 1.5	10.6	207
Cable, SY, 7 Core, 1.5mm, Per M	7 x 1.5	11.5	264
Cable, SY, 3 Core, 2.5mm, Per M	3 x 2.5	10.6	206
Cable, SY, 4 Core, 2.5mm, Per M	4 x 2.5	11.5	260
Cable, SY, 5 Core, 2.5mm, Per M	5 x 2.5	12.6	307
Cable, SY, 5 Core, 4mm, 50M	5 x 4	14.1	338
Cable, SY, 5 Core, 6mm, 50M	5 x 6	16.7	530